

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : C10G 21/00, 53/06		A1	(11) International Publication Number: WO 00/52115
			(43) International Publication Date: 8 September 2000 (08.09.00)
(21) International Application Number: PCT/GB00/00635 (22) International Filing Date: 23 February 2000 (23.02.00) (30) Priority Data: 9904808.4 2 March 1999 (02.03.99) GB (71) Applicants (for all designated States except US): BP OIL INTERNATIONAL LIMITED [GB/GB]; Britannic House, 1 Finsbury Circus, London EC2M 7BA (GB). BP REFINERY (KWINANA) PTY. LIMITED [AU/AU]; Mason Road, Kwinana, W.A. 6167 (AU). (72) Inventors; and (75) Inventors/Applicants (for US only): DAVIES, John, Philip [GB/GB]; 24 Houblon Road, Richmond, Surrey TW10 6DE (GB). GRACE, Kellie, Peta [AU/AU]; 20 Merton Street, Albert Park, VIC 3206 (AU). (74) Agent: SMITH, Julian, Philip, Howard; BP International Limited, Patents & Agreements, Chertsey Road, Sunbury on Thames, Middlesex TW16 7LN (GB).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report.	
(54) Title: OIL TREATMENT PROCESS (57) Abstract A process for the production of a process oil, the process comprising: a) contacting a petroleum distillate with a polar solvent in an extraction column which operates with a bottom temperature of 30 to 80°C, b) withdrawing a primary raffinate from the column of step a), c) contacting the primary raffinate with a polar solvent in an extraction column which operates at a bottom temperature that is higher than the bottom temperature of the extraction column of step a), and in the range of 60 to 90 °C, d) withdrawing a secondary extract from the column of step c), and e) removing said polar solvent from said secondary extract.			