

TITLE OF THE INVENTION

COMMUTATION TYPE DC BREAKER

BACKGROUND OF THE INVENTION

5 [Field of Technology]

The present invention relates to a commutation type DC breaker and more particularly to a structure of a commutation type DC breaker for supplying charges stored in a commutation capacitor to a main switch in an opposite
10 direction to a main circuit current, producing a current zero point, thereby breaking the main switch.

[Description of Related Art]

Fig. 3 is a drawing for explaining the breaking principle of the commutation type DC breaker. As shown in
15 Fig. 3, a commutation type DC breaker 18 or 19 is connected between a direct current source 60 and a load 70 and includes a main switch 3 with the main circuit current supplied, a supersaturation reactor 10, a commutation circuit composed of a commutation capacitor 8 and a
20 commutation switch 2, a charging power source, not drawn, for the commutation capacitor, and a control unit for controlling the aforementioned units. Further, the commutation type DC breaker 19 is connected to an external circuit, the commutation capacitor, and the supersaturation
25 reactor via contactors 14A, 14B, and 14C.

When an excessive current is supplied to the main circuit 17A, the commutation type DC breaker 19 releases the main switch 3 and simultaneously turns on the commutation switch 2. At this time, the charges stored in the commutation capacitor 8 are discharged via the main switch 3 and a high frequency discharge current (a commutation current) accompanying discharge of the capacitor is supplied to the main switch 3. If the commutation current is superimposed on the main circuit current in this way, a current zero point is generated in the main circuit current and then the main circuit current is cut off (refer to Patent Documents 1 and 2).

Fig. 4 is a cross sectional view showing an example of the conventional commutation type DC breaker 19 arranged in a power board. In Fig. 4, a numeral 40 indicates a power board and it includes a front storage box 40A, a DC breaker storage box 41, and a back storage box 42A. In the front storage box 40A, a power board control unit 30A, terminal boards 20A, 20B and 20C, and a front door 31 are arranged. In the DC breaker storage box 41, the commutation type DC breaker 19 is arranged.

The commutation type DC breaker 19 includes the main switch 3, a main switch drive unit 1 for driving the main switch, main switch control circuits 4 to 7 for controlling the main switch drive unit, the commutation switch 2, the

commutation capacitor 8, the supersaturation reactor, and a non-linear resistor 9 which are units necessary for commutation, and these units are arranged in the DC breaker storage box 41. On the back of the main switch 3, a main
5 circuit conductor 17 is arranged. The main circuit conductor 17 is connected to a bus 13 via the main switch 3. A numeral 11 indicates an overcurrent detector mounted on the main circuit conductor. In the back storage box 42A, a cable 44 connected to an external load (a feeder) is stored.
10 The cable is connected to the main circuit conductor 17 via a connecting conductor 21. Further, on the cable connecting conductor 21, a meter DC transformer 26, a DC transformer 23A, and a feeder failure selection unit 22 are mounted.

As shown in Fig. 4, the conventional commutation type
15 DC breaker 19 includes the main switch 3, commutation switch 2, commutation capacitor 8, supersaturation reactor 10, and non-linear resistor 9 and for example, the commutation capacitor 8 and non-linear resistor 9 are arranged in the power board 40 in the vicinity of the main
20 switch 3.

Patent Document 1: Japanese Patent Laid-open No. 2000-48686

Patent Document 2: Japanese Patent Laid-open No. 2001-143581

SUMMARY OF THE INVENTION

In the commutation type DC breaker, as mentioned above, the breaking method generates a zero point in the main circuit current by the commutation current from the capacitor, thereby breaking the main switch, so that the number of units composing the commutation type DC breaker is larger than that of an ordinary AC breaker and these units are arranged in the power board storing the main unit of the commutation type DC breaker.

Therefore, the arrangement of the units must be designed as a whole of the power board in consideration of connection with the main unit of the commutation type DC breaker (the main switch) and the design and manufacture of the power board having the built-in commutation type DC breaker requires much labor and time and causes higher costs.

The present invention was developed with the foregoing problems in view and integrally structures the main unit of the commutation type DC breaker (the main switch) and the units necessary for commutation, thereby lightening the burden imposed on the design and manufacture of the DC circuit power board having the built-in commutation type DC breaker.

The present invention adopts the following means to solve the above problems.

In a commutation type DC breaker having a main switch inserted in series into a main circuit for connecting a DC source and a load, a commutation capacitor, a reactor, and a commutation switch for supplying charges stored in the commutation capacitor to the main switch in an opposite direction to a main circuit current, producing a current zero point, thereby breaking the main switch, characterized in that the commutation capacitor, the reactor, and the commutation switch which are composed a commutation circuit and a control circuit for controlling the turning on or off of the main switch and the commutation switch are loaded on a frame with the main switch loaded.

The present invention has the aforementioned structure, so that the burden imposed on the design and manufacture of the DC circuit power board having the built-in commutation type DC breaker can be lightened.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a drawing for explaining the commutation type DC breaker relating to an embodiment of the present invention.

Fig. 2 is a drawing showing an embodiment of the present invention that the commutation type DC breaker is stored in the power board.

Fig. 3 is a drawing for explaining the principle of the

commutation type DC breaker.

Fig. 4 is a cross sectional view showing the conventional commutation type DC breaker arranged in the power board.

5

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Hereinafter, the preferred embodiment of the present invention will be explained with reference to the accompanying drawings. Fig. 1 is a drawing for explaining the commutation type DC breaker relating to an embodiment of the present invention. As shown in Fig. 1, a commutation type DC breaker 18 provides with the main switch 3, the main switch drive unit 1 for driving the main switch, the main switch control circuits 4 to 7 for controlling the main switch drive unit 1, and the commutation switch 2, commutation capacitor 8, supersaturation reactor 10, and non-linear resistor 9 which are units necessary for commutation, and these units are loaded on the frame 47.

Here, the main switch control units 4 to 7 are arranged on the upper part of the main switch drive unit 1 and the commutation capacitor 8 is arranged behind the commutation switch 2 (on the back side of the frame for loading the commutation type DC breaker 18). Further, the supersaturation reactor 10 and non-linear resistor 9 are arranged behind the main switch 3.

Behind the frame 47, a contactor 14 connected with the main circuit conductor 17 arranged in the DC breaker storage box 40 is arranged and the contactor 14 is connected to the main switch 3 via a link conductor 15 arranged between the commutation capacitor 8 and the non-linear resistor 9.

The commutation capacitor 8 loads a plurality of capacitors into which the capacity necessary to generate a zero point in the current flowing through the main switch 3 is divided. The other units composing the commutation type DC breaker 18, for example, the non-linear resistor 9 and supersaturation reactor 10 can be divided and loaded into a plurality of parts. Further, when dividing and loading the units, so as to ensure the insulation performance, the units are arranged with a predetermined air spatial distance kept, thus the overall commutation type DC breaker can be miniaturized.

As mentioned above, the main switch 3 composing the commutation type DC breaker 18, the main switch drive unit 1 for driving the main switch 3, the main switch control circuits 4 to 7 for controlling the main switch drive unit 1, and the commutation switch 2, commutation capacitor 8, supersaturation reactor 10, and non-linear resistor 9, which are units necessary for commutation, and these are loaded on the frame 47. The frame 47 is provided with

wheels 48 supported movably, so that the commutation type DC breaker 18 loaded on the frame 47 can be wholly transferred in or out from the power board 40. Thus the commutation type DC breaker 18 can be handled as a DC
5 breaker movable by hand.

Therefore, in manufacturing of the products, a reduction in the part manufacturing costs and improvements in operation efficiency due to mass production can be realized. Further, a verification test can be conducted by
10 a single DC breaker and products can be stably supplied.

Fig. 2 is a drawing showing an embodiment of the present invention that the commutation type DC breaker 18 of the present invention is stored in the power board. In Fig. 2, the numeral 40 indicates a power board and it
15 includes the front storage box 40A, DC breaker storage box 41, and back storage box 42A. In the front storage box 40A, the power board control unit 30, terminal boards 20, and front door 31 are arranged. In the DC breaker storage box 41, the DC breaker 18 shown in Fig. 1 is arranged. A
20 numeral 16 indicates a partition plate, which partitions between the DC breaker 18 and the main circuit conductor 17 arranged on the back side of the breaker storage box 41. On the back of the partition plate 16, the main circuit conductor 17 is arranged. The main circuit conductor 17 is
25 connected to the bus 13 via the main switch 3. The numeral

11 indicates the overcurrent detector mounted on the main circuit conductor. In the back storage box 42A, a cable 44 connected to an external load (a feeder) is stored. The cable is connected to the main circuit conductor 17 via the
5 connecting conductor 21. Further, on the cable connecting conductor 21, the meter DC transformer 26, DC transformer 23A, and feeder failure selection unit 22 are mounted.

According to this embodiment, the kind, constitution, and arrangement of the units installed inside the front
10 storage box 40A and back storage box 42A composing the power board 40 are changed, thus the specifications and use of the DC circuit power board can be changed without altering the constitution of the DC breaker storage box 41. Namely, the DC breaker storage box 41 can be standardized.
15 Therefore, the burden imposed on the design and manufacture of the DC circuit power board can be lightened. Further, the overall height of the power board can be reduced, thus miniaturization, weight reduction, and cost savings can be realized in the DC circuit power board.

20 Further, in the case of maintenance checks or parts exchanges of the power board 40, the front door 31 arranged on the front of the power board 40 is opened and then the movable commutation type DC breaker 18 is pulled out from the front storage box 40A. By doing this, the DC breaker is
25 separated from the main circuit conductor 17 in the portion

of the contactor 14, and overall the commutation type DC
breaker 18 can be checked safely, and parts exchanges can
be executed. Further, in the power board 40 after the
commutation type DC breaker 18 is pulled out, no person can
5 approach the main circuit conductor 17 due to the partition
plate 16, so that the internal checks can be executed
safely.

As explained above, according to this embodiment, the
commutation type DC breaker can be structured on a movable
10 frame as a simple body. Therefore, mass production of
articles of the same design can be realized. Therefore, in
the power board for storing the DC breaker as a simple body,
the design of the commutation type DC breaker itself is not
necessary.

15 As mentioned above, when the commutation type DC
breaker of this embodiment is adopted, when designing a DC
circuit power board of a different use and specification,
the DC breaker can be standardized, and the DC breaker
storage box can be miniaturized and reduced in weight, and
20 the labor and time of design and manufacturing can be
reduced, thus a commutation type DC breaker facilitating
maintenance checks at a low cost can be provided.

WHAT IS CLAIMED IS

1. A commutation type DC breaker comprising a main switch inserted in series into a main circuit for connecting a DC source and a load, a commutation capacitor, a reactor, and a commutation switch for supplying charges stored in the commutation capacitor to the main switch in an opposite direction to a main circuit current, producing a current zero point, thereby breaking the main switch,

characterized in that the commutation capacitor, the reactor, and the commutation switch which are composed a commutation circuit and a control circuit for controlling the turning on or off of the main switch and the commutation switch are loaded on a frame with the main switch loaded.

2. A commutation type DC breaker according to Claim 1, wherein the main switch includes a contactor freely connectable to and separable from a main circuit conductor installed in a power board, and the frame is provided with a wheel supported movably, and the frame can be wholly transferred in or out from the power board including the main circuit conductor.