

METHODS AND DEVICES FOR RANDOM ACCESS POWER CONTROL IN A COMMUNICATIONS NETWORK

TECHNICAL FIELD

- 5 The invention relates to methods and devices in a communications network, in particular, for designing a random access transmission power setting of a communication device.

BACKGROUND

In modern cellular radio systems, a radio network has a strict control on the behavior of a
10 user equipment, UE. Uplink transmission parameters like frequency, timing, and power are regulated via downlink DL control signaling from the base station to the UE.

At power-on or after a long standby time, the UE is not synchronized in the uplink. A first step in accessing the network is therefore to obtain synchronization to the network. This is
15 usually done by the UE by listening to downlink signals and obtain from this signals downlink timing synchronization, an estimate of the frequency error, and also an estimate of the DL path loss. Even though the UE is now time-synchronized to the DL, signals transmitted by the UE are still not aligned with the desired reception timing at the base station due to an unknown round trip timing. Therefore, before commencing traffic, the UE has to carry out
20 a Random Access (RA) procedure to the network. After the RA, eNodeB can estimate the timing misalignment of the UE uplink and send a correction message. The random access procedure may also be used by synchronized UEs without valid uplink allocations for data transmission, in order to request such allocations.

25 Usually, a Physical Random Access Channel (PRACH) is provided for the UE to request access to the network. An access burst is used which contains a preamble with a specific sequence with good autocorrelation properties. The PRACH can be orthogonal to the traffic channels. For example, in GSM a special PRACH slot is defined.

Because multiple UEs can request access at the same time, collisions may occur
30 between requesting UEs. Therefore LTE defines multiple RA preambles. A UE performing RA randomly picks a preamble out of a pool and transmits it. The preamble represents a random UE ID which is used by the eNodeB when granting the UE access to the network.

The eNodeB receiver can resolve RA attempts performed with different preambles and send a response message to each UE using the corresponding random UE IDs. In case that multiple UEs simultaneously use the same preamble a collision occurs and most likely the RA attempts are not successful since the eNodeB cannot distinguish between
 5 the two users with the same random UE ID. In LTE 64 preambles are provided in each cell. Preambles assigned to adjacent cells are typically different to insure that a RA in one cell does not trigger any RA events in a neighboring cell. Information that must be broadcasted is therefore the set of preambles that can be used for RA in the current cell.

- 10 The power used by the UE to transmit a RA preamble is typically calculated via open-loop power control. The UE measures the power on some downlink signals with known transmit power – e.g. reference signals or synchronization signals – and calculates the DL path loss. The power of the signals used to estimate the path must be known, therefore this information must be signaled to the UE, either via broadcasted in initial access or
 15 possibly via dedicated signaling in handover.

The path-loss is calculated as

$$PL = P_{RS,RX} - P_{RS,TX}$$

- where $P_{RS,RX}$ and $P_{RS,TX}$ are the received and transmitted power in dBm of the signal
 20 used for path-loss estimation, respectively.

- In order to maintain a certain quality criteria for RA reception a minimum signal to noise (interference) ratio at the base station is required. The base station is aware of the present interference situation and can thus calculate the minimum required signal power
 25 $P_{0,RACH}$ the RA signal must have at the base station to fulfill the required quality criteria.

This power level is also signaled to the UE. Using this power level together with the previous calculated path loss the UE now calculates

$$P_{RACH} = \min \{ P_{0,RACH} - PL + (N - 1) \Delta_{RACH}, P_{\max} \},$$

- 30 which is the transmit power needed to achieve the power level $P_{0,RACH}$ at the base station. This implies that the path loss – which has been calculated in the DL – is the

same for the UL, which typically is not the case for FDD systems. Therefore open loop power control is a rather coarse mechanism. To overcome this limitation very often power ramping is applied. Here each subsequent attempt is performed with a by Δ_{RACH} increased transmission power. In above formula this is reflected by the term

5 $(N-1) \cdot \Delta_{RACH}$, where N is the transmission attempt number.

The interference level at eNodeB and thus also the required target receive power

$P_{0,RACH}$ depends on many factors and can vary over a wide range. Typically,

$P_{0,RACH}$ is encoded and transmitted with a rather low number of bits – e.g. 4 bit – and
10 spans around a range of 30 dB.

It is expected that LTE systems will be deployed in a wide range of scenarios, from pico cells to very large cells of up to 100 km and beyond. Since the RA is the first procedure performed by the UE to access the network it is of vital importance that random access
15 works in all anticipated scenarios. If RA fails the UE cannot access the network.

In order to insure satisfactory RA performance the LTE standard defines multiple preamble formats. For the FDD mode four preambles are defined, the TDD mode even specifies an additional fifth preamble. Some of these preambles are designed for larger
20 cells and are thus longer than other preambles. The reception power and consequently the performance of the random access procedure are affected by RA configuration.

SUMMARY

There is an object of embodiments herein to achieve an efficient random access
25 procedure.

Embodiments relate to a method in a first communication device within a communications network for designing a random access transmission power setting of the first communication device.

30

The first communication device receives data from a second communication device on a radio channel indicating a random access reception power. The first communication

device then determines a desired random access reception power of the second communication device based on the received data and a parameter of random access configuration that influences a detection performance of the random access at the second communication device. Furthermore, the first communication device determines a random
5 access transmission power to use based on the desired random access reception power and designs the random access transmission power setting of the first communication device in accordance with the determined random access transmission to use.

In order to perform the method a first communication device is provided. The first
10 communication device comprises a receiving arrangement configured to receive data from a second communication device on a radio channel indicating a random access reception power to detect a random access transmission. The first communication device further comprises a control unit arranged to determine a desired random access reception power of the second communication device based on the received data and a parameter of
15 random access configuration that influences a detection performance of the random access at the second communication device. The control unit is further arranged to determine a random access transmission power design setting based on the desired random access reception power.

20 In some embodiments, a method in a second communication device within a communications network for transmitting data over a radio channel is provided.

The second communications device determines a desired random access reception power from a first communication device such that the second communication device is
25 enabled to detect a random access request from the first communication device using a parameter of random access configuration. The second communication device then determines data based on the desired random access reception power and a parameter of random access configuration and transmits the data over a radio channel to the first communication device.

30

In order to perform the method a second communication device is provided. The second communication device comprises a control unit arranged to determine a desired random access reception power from a first communication device such that the second communication device is enabled to detect a random access request from the first
35 communication device. The control unit is further arranged to determine data based on

the desired random access reception power and a parameter of random access configuration. The second communication device further comprises a transmitting arrangement configured to transmit the data over a radio channel to the first communication device.

5

Embodiments relate to methods and devices wherein the power setting of transmission takes the preamble format into account and the following random access procedure will be more efficient.

10 BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments will now be described in more detail in relation to the enclosed drawings, in which:

Figure 1 shows a schematic overview of a communication device in a communications network,

15 Figure 2 shows the missed detection performance over signal to noise ratio for the five preamble formats defined in LTE,

Figure 3 shows a schematic combined method and signaling scheme,

Figure 4 shows a schematic flowchart of a method in a first communication device,

Figure 5 shows a schematic overview of a first communication device,

20 Figure 6 shows a schematic flowchart of a method in a second communication device, and

Figure 7 shows a schematic overview of a second communication device.

DETAILED DESCRIPTION OF EMBODIMENTS

25 Embodiments of the present invention will be described more fully hereinafter with reference to the accompanying drawings, in which embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey
30 the scope of the invention to those skilled in the art. Like numbers refer to like elements throughout.

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms "a",

"an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "comprises" "comprising," "includes" and/or "including" when used herein, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the
5 presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to
10 which this invention belongs. It will be further understood that terms used herein should be interpreted as having a meaning that is consistent with their meaning in the context of this specification and the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

15 The present invention is described below with reference to block diagrams and/or flowchart illustrations of methods, apparatus (systems) and/or computer program products according to embodiments of the invention. It is understood that several blocks of the block diagrams and/or flowchart illustrations, and combinations of blocks in the block diagrams and/or flowchart illustrations, can be implemented by computer program
20 instructions. These computer program instructions may be provided to a processor of a general purpose computer, special purpose computer, and/or other programmable data processing apparatus to produce a machine, such that the instructions, which execute via the processor of the computer and/or other programmable data processing apparatus, create means for implementing the functions/acts specified in the block diagrams and/or
25 flowchart block or blocks.

The present invention is described herein as employed in and with a communications device, also denoted a mobile device. In the context of the invention, the mobile device may e.g. be a mobile phone, a PDA (Personal Digital Assistant), base station or any other
30 type of portable computer such as laptop computer.

A communications network may e.g. a cellular mobile communications network such as a GPRS network, a third generation WCDMA network, a LTE or the like. Given the rapid development in communications, there will of course also be future type wireless
35 communications networks with which the present invention may be embodied.

A communication device comprises a user equipment, a base station, a controller node, a combination thereof, and/or the like.

- 5 A control unit may comprise a single processing unit, or a plurality of processing units. Similarly, a memory unit may comprise a single or a plurality of memory units, for example, internal and/or external memories.

In Figure 1, a schematic overview of a communication device 10, such as a UE or the like
10 in a communications network 1 is shown. At power-on or after a long standby time, the UE 10 is not synchronized in an uplink 4 to a base station 20. A first step in accessing the network is therefore to obtain synchronization to the network 1. This is usually done by the UE 10 by listening to signalling on a downlink 3 and to obtain from this signals downlink timing synchronization, an estimate of the frequency error, and also an estimate of the DL
15 path loss.

The base station 20 signals an indication of a desired random access reception power to the UE 10 such that the base station 20 is enabled to detect a random access request from the UE 10.

20

The UE 10 determines random access transmission power to use based on a determined desired random access reception power of a second communication device. The desired random access reception power is being based on the received indication and a parameter of random access configuration that influences a detection performance of the
25 random access at the second communication device.

For example, a parameter of random access configuration that influences a detection performance of the random access at the second communication device may be preamble format. With a longer preamble the eNodeB receiver can over a longer time
30 accumulate the received signal power and thus can operate at signal to noise ratios lower than those required for shorter preambles.

The additional fifth preamble in TDD mode on the other hand is very short and therefore requires higher signal to noise ratios.

35

Even though with the existing solution $P_{0,RACH}$ can be chosen out of an approximately 30 dB wide interval the useful interval for a specific preamble is lower. For example, the short TDD preamble will not work with $P_{0,RACH}$ values from the lower end of the interval, whereas the long preambles will typically not require the highest

5 $P_{0,RACH}$ values.

- Different RA configurations require different signal powers at the eNodeB receiver to achieve the same detection performance and embodiments correct the transmission power to account for these different levels. This implies that the value range of required
- 10 receive powers is better adapted to the individual preamble formats /basic cyclic shift values and/or the like than without correction. The cyclic shift value is a parameter for obtaining a cyclic shift unit of the root sequence, and subgroups may be ordered according to the cyclic shift value.
- 15 In Figure 2, the missed detection performance over signal to noise ratio is shown for the five preamble formats defined in LTE. Preamble formats 0,1 are illustrated with curves L0,L1. Preamble formats 2 and 3 are illustrated with curves L2, L3 and the short preamble format 4 is illustrated in curve L4. As can be seen preamble format 3 requires 9 dB less signal to noise ration than preamble format 4 to achieve a missed detection rate of 1e-3.
- 20 It is proposed to add to the formula describing the required transmit power a preamble format dependent correction term. This would shift the range of the desired receive power up or down to a power interval more appropriate for the used preamble.
- 25 Since the preamble format is anyway signaled to the UE, the UE knows which preamble to use and thus also knows the preamble dependent offset. For preamble formats 0 and 1 (normal long) this offset could be zero, for preamble formats 2 and 3 (long preambles) negative and for preamble format 4 (very short preamble) positive.
- 30 Another interpretation is that the bit pattern signaling $P_{0,RACH}$ is differently interpreted according to the preamble format.

A further possibility is to use different offsets for different purposes of the P_{RACH} transmission. For example, a (time critical) P_{RACH} transmission in the target cell after handover could use a positive offset as compared to other P_{RACH} transmissions.

5 The formula used to calculate the RA transmit power

$$P_{RACH} = \min \{ P_{0,RACH} - PL + (N - 1) \Delta_{RACH}, P_{\max} \}$$

is now modified by an offset depending on the preamble format;

$$P_{RACH} = \min \{ P_{0,RACH} - PL + (N - 1) \Delta_{RACH} + \Delta_{\text{Preamble}}, P_{\max} \}$$

10 .

A possible setting for Δ_{Preamble} could be e.g. 0 dB, -3 dB, and 8 dB respectively for normal long preambles (formats 0, 1), long preambles (formats 2, 3) and short preamble (format 4). With a range of [-120, -90] dBm for $P_{0,RACH}$ the effective range for $P_{0,RACH} - \Delta_{\text{Preamble}}$ becomes now [-120, -90], [-123, -93], and [-112, -82] for the normal, long, and
 15 short preamble formats, respectively. These intervals fit better to the typically needed signal power levels for the different preambles.

Another interpretation is to leave the original formula unchanged, i.e.

$$P_{RACH} = \min \{ P_{0,RACH} - PL + (N - 1) \Delta_{RACH}, P_{\max} \},$$

20 but interpret the bit pattern signaling $P_{0,RACH}$ differently.

Table 1 shows a possible mapping of signaled $P_{0,RACH}$ index to actual $P_{0,RACH}$ value.

Signaled $P_{0,RACH}$ index	$P_{0,RACH}$ value for preamble formats 0 and 1 in dBm	$P_{0,RACH}$ value for preamble formats 2 and 3 in dBm	$P_{0,RACH}$ value for preamble format 4 in dBm
0	-120	-123	-112
1	-118	-121	-110
2	-116	-119	-108
3	-114	-117	-106
14	-92	-95	-84
15	-90	-93	-82

Table 1: The signalled $P_{0,RACH}$ index is mapped to different $P_{0,RACH}$ values depending on the preamble format. In this example, wide configuration preamble formats 0, 1 and 2, 3 have the same mapping.

In some embodiments the formula for the RA transmit power is modified with yet another correction term depending on the basic cyclic value NCS used to construct the RA preamble. Depending on the NCS value different thresholds are needed to maintain a certain false alarm rate. A higher threshold value improves false alarm rate but negatively impacts missed detections.

Here also the alternative interpretation is possible that signaled $P_{0,RACH}$ index is mapped to different $P_{0,RACH}$ values depending on NCS.

We also note that above invention applies even in the case if multiple preamble formats are permitted within a single cell. Depending which preamble a UE chooses to perform RA with it applies the appropriate correction term.

During the descriptions we assumed preambles of different length and based on the length they have different detection capabilities. However, even other differences between preambles may lead to different detection capabilities. Also in this case above invention is applicable.

5

The different RA preambles require different signal powers at the eNodeB receiver to achieve the same detection performance. Embodiments propose to add a correction term to the signaled value of the required RA receive power to account for these different levels. This implies that the value range of required receive powers is better adapted to
10 the individual preambles than without correction.

Since the preamble format is anyway signaled to the UE no additional signaling is required.

15 Referring to figure 3, a schematic combined method and signaling scheme is shown. The signaling is performed between a first communication device 10 and a second communication device 20. In the illustrated example, the first communication device 10 comprises a user equipment and the second communication device 20 comprises a base station. A desired reception power of the base station is based on a parameter of random
20 access configuration and in the illustrated example the parameter is a random access preamble format. However, it should be understood that such a parameter may instead comprises random access a basic cyclic shift value, a combination thereof and/or the like.

In step S1, the base station 20 calculates desired reception power P_{desired} based on
25 quality criteria, RA parameters, and/or the like.

In step S2, the base station 20 determines a pointer value indicating a power value based on the P_{desired} and the random access preamble format that influences a detection performance of a random access operation of the user equipment at the base station.

30

In some embodiments, a P_{signaled} is a calculated value from P_{desired} taken into account an offset value related to the random access preamble format. In the next step the base station looks up the value P_{signaled} in a table or a value closest to P_{signaled} . An index value is determined from the table corresponding to the matched/closest to value and this
35 index value is used as the pointer value.

In some embodiments, the P_{desired} is looked up in a table comprising a plurality of columns each corresponding to a value of the parameter of random access configuration. An index value is determined from the table corresponding to the P_{desired} or a value
5 closest to the P_{desired} and this index value is used as the pointer value.

In step S3, the base station 20 transmits the pointer value to the user equipment 10 over a radio channel, for example, as a unicast, a broadcast, and/or a multicast.

10 In step S4, the user equipment 10 receives the pointer value, reads the pointer value and determines a random access transmission power to use.

In some embodiments, the user equipment 10 uses the pointer value in a table to find the P_{signaled} . Based on the P_{signaled} and the random access preamble format, which is
15 known from previous signaling or determined by the user equipment based on the received signal carrying the pointer value, the P_{desired} is determined. For example, an offset power value based on the preamble format is added to the P_{signaled} . P_{desired} is then used to determine the random access transmission power to use.

20 In some embodiments, the user equipment 10 uses the pointer in a table of rows and columns together with the random access preamble format, pointer value defining the row and the random access preamble format defining the column, to determine P_{desired} .

In step S5, the user equipment sets itself up in an operational mode arranged to use the
25 determined random access transmission power.

In step S6, the user equipment performs a random access procedure and transmits random access data over a radio channel to the base station using the determined random access transmission power.

30

In figure 4, a schematic flow chart of a method in a first communications device is shown. The method is for designing the transmission power setting of the first communication device taken into account a parameter of random access configuration that influences a detection performance of the random access at the second communication device. The
35 parameter may be a preamble format, a basic cyclic shift value, and/or the like.

In step 42, the first communications device receives data from a second communication device on a radio channel indicating a desired random access reception power. The data may be a pointer value to be used in a table or the like.

5

In step 44, the first communication device determines a desired random access reception power of the second communication device based on the received data and a parameter of random access configuration that influences a detection performance of the random access at the second communication device.

10

In some embodiments, the received data comprises a pointer value indicating a signalled random access reception power in a table of random access reception power and the step of determining the desired random access reception power is based on the signalled random access reception power and the parameter of random access configuration. The

15 step of determining desired random access reception power may furthermore comprise to calculate the desired random access reception power by adding/subtracting an offset value to the signalled random access reception power wherein the offset value is based on the parameter of random access configuration.

20 In some alternative embodiments, the received data comprises a pointer value indicating a desired random access reception power in a table of desired random access reception power and the step of determining the desired random access reception power comprises to use the pointer value in a table together with the parameter of random access configurations. The table may, in some embodiments, comprise rows and columns, which
25 are defined by pointer values and values of the parameter of random access configuration.

In step 46, the first communication device determines a random access transmission power to use based on the desired random access reception power.

30

In some embodiments, the step of determining desired random access transmission power to use further comprises to take into account power path loss between the first communication device and the second communication device.

In step 48, the first communication device sets itself up in an operational mode to use the determined random access transmission power.

In optional step 50, the first communication device performs a random access procedure
5 using the determined random access transmission power.

In order to perform the method a first communication device is provided. The first communication device may be a user equipment, such as a mobile phone, a PDA, a laptop; a base station, a controller, a combination thereof, and/or the like.

10

In figure 5, a schematic overview of a first communication device illustrated as a user equipment is shown. The first communication device 10 is being arranged to communicate with a second communication device to set the transmission power setting design of the first communication device taken a parameter of random access
15 configuration that influences a detection performance of the random access transmission at the second communication device into account. The parameter may be preamble format, basic cyclic shift value, and/or the like.

The first communication device 10 comprises a receiving arrangement 103 configured to
20 receive a signal from a second communication device on a radio channel indicating a random access reception power to detect a random access transmission from the first communication device.

The first communication device 10 further comprises a control unit 101 arranged to
25 determine a desired random access reception power of the second communication device based on the received data and the parameter of random access configuration that influences a detection performance of the random access transmission at the second communication device. The control unit 101 further being arranged to determine a random access transmission power design setting based on the desired random access reception
30 power. In some embodiments, the control unit 101 is further arranged to take into account power path loss between the first communication device and the second communication device to determine random access transmission power.

The received data may, in some embodiments, comprise a pointer value arranged to
35 indicate a signalled random access reception power in a table of random access reception

power stored on a memory unit 107 in the first communication device. The control unit 101 then being arranged to determine the desired random access reception power based on the signalled random access reception power pointer and the parameter of random access configuration.

5

Furthermore, the control unit 101 may further be arranged to calculate the desired random access reception power by adding/subtracting an offset value to the signalled random access reception power wherein the offset value is based on the parameter of random access configuration.

10

In some alternative embodiments, the received data comprises a pointer value indicating a desired random access reception power in a table of desired random access reception power stored on the memory unit 107 in the first communication device. The control unit 101 then being arranged to use the pointer value in a table together with the parameter of random access configuration to determine the desired random access reception power. The table may comprise rows and columns, which are defined by pointer values and values of the parameter of random access configuration.

15

In some embodiments, the memory unit 107 has the data and table/s stored thereon as well as applications arranged to be executed on the control unit 101 to perform the methods.

20

The control unit 101 may, in some embodiments, be arranged to perform a random access operation using the random access transmission power design and to transmit a random access request over a transmitting arrangement 105 of the first communication device to the second communication device or a different communication device.

25

The first communication device comprises a UE, a base station, a base station controller and/or the like.

30

In figure 6, a schematic overview of a method in a second communication device for transmitting data over a radio channel is shown.

In step 52, the second communication device determines a desired random access reception power from a first communication device such that the second communication

35

device is enabled to detect a random access request from the first communication device using a parameter of random access configuration that influences a detection performance of the random access at the second communication device.

- 5 In step 54, the second communication device determines data based on the desired random access reception power and the parameter of random access configuration. The parameter of random access configuration comprises a preamble format, a basic cyclic shift value of the random access configuration and/or the like.
- 10 In some embodiments, the second communication device further determines a signalled random access reception power based on the desired random access reception power and the parameter of random access configuration. A pointer value is then being retrieved from a table of signalled random access reception power based on the determined signalled random access reception power and then included into the data.
- 15 In some embodiments, the signalled random access reception power may be calculated from the desired random access reception power and an offset value wherein the offset value is based on the parameter of random access configuration.
- 20 In some embodiments, the second communication device further determines a pointer in a table of desired random access reception power. The pointer value is determined based on the determined desired random access reception power and the parameter of random access configuration. The data comprises the pointer value and the table may be a table of desired random access reception power comprising rows and columns, which are
- 25 defined by pointer values and values of the parameter of random access configuration.

In step 56, the second communication device transmits the data over a radio channel to the first communication device.

- 30 In order to perform the method a second communication device is provided. The second communication device may comprise a base station, a controller, a user equipment, a combination thereof, and/or the like.

In Figure 7, a schematic overview of a second communication device 20 is shown.

The second communication device 20 comprises a control unit 201 arranged to determine a desired random access reception power from a first communication device such that the second communication device is enabled to detect a random access request from the first communication device.

5

The control unit 201 furthermore being arranged to determine data based on the desired random access reception power and a parameter of random access configuration that influences a detection performance of the random access at the second communication device. The parameter of random access configuration may comprise a preamble format,
10 a basic cyclic shift value of the random access configuration and or the like.

In some embodiments, the control unit 201 is further arranged to determine a signalled random access reception power based on the desired random access reception power and the parameter of random access configuration stored on a memory unit 207. In
15 addition, the control unit 201 is arranged to determine a pointer value based on the determined signalled random access reception power from a table of signalled random access reception power. The transmitted data then comprises the determined pointer value.

20 It should here be noted that the control unit 201 may then be arranged to calculate the desired signalled random access transmission reception power by using the desired random access reception power and an offset in the calculation, the offset being related to the parameter of random access configuration.

25 In some alternative embodiments, the transmitted data comprises a pointer value and the control unit 201 is arranged to determine the data by determining a pointer value in a table of desired random access reception power. The pointer value is arranged to be determined based on the determined desired random access reception power and the parameter of random access configuration. The table comprises rows and columns, which
30 are defined by pointer values and values of the parameter of random access configuration.

The second communication device 20 comprises additionally a transmitting arrangement 205 configured to transmit the data over a radio channel to the first communication
35 device.

The second communication device comprises a base station, a base station controller, a UE and/or the like.

- 5 In some embodiments, the memory unit 207 has the data and table/s stored thereon as well as applications arranged to be executed on the control unit 201 to perform the methods. The second communication device 20 may additionally comprise a network interface 209 to communicate with the communications network and a receiving arrangement 203 arranged to receive a random access request and/or the like.

10

- In the drawings and specification, there have been disclosed exemplary embodiments of the invention. However, many variations and modifications can be made to these embodiments without substantially departing from the principles of the present invention. Accordingly, although specific terms are employed, they are used in a generic and
15 descriptive sense only and not for purposes of limitation, the scope of the invention being defined by the following claims.

CLAIMS

1. A method in a first communication device within a communications network for designing a random access transmission power setting of the first communication device comprising the steps of:
 - 5 - receiving (42) data from a second communication device on a radio channel indicating a random access reception power,
 - determining (44) a desired random access reception power of the second communication device based on the received data and a parameter of random access configuration that influences a detection performance of the random
 - 10 access at the second communication device,
 - determining (46) a random access transmission power to use based on the desired random access reception power, and
 - designing (48) the random access transmission power setting of the first communication device in accordance with the determined random access
 - 15 transmission to use.
2. A method according to claim 1, wherein the received data comprises a pointer value indicating a signalled random access reception power in a table of random access reception power and the step of determining (44) the desired random
- 20 access reception power is based on the signalled random access reception power and the parameter of random access configuration.
3. A method according to claim 2, wherein the step of determining desired random access reception power further comprises to calculate the desired random access
- 25 reception power by adding/subtracting an offset value to the signalled random access reception power wherein the offset value is based on the parameter of random access configuration.
4. A method according to claim 1, wherein the received data comprises a pointer
- 30 value indicating a desired random access reception power in a table of desired random access reception power and the step of determining the desired random access reception power comprises to use the pointer value in a table together with the parameter of random access configuration.

5. A method according to claim 4, wherein the table comprises rows and columns, which are defined by pointer values and values of the parameter of random access configuration.
- 5 6. A method according to any of the claims 1-5, further comprising the step of:
performing a random access using the random access transmission power setting.
7. A method according to any of claims 1-6, wherein the step of determining random
access transmission power to use further comprises to take into account power
10 path loss between the first communication device and the second communication
device.
8. A method according to any of claims 1-7, wherein the parameter of random access
configuration comprises a preamble format and/or a basic cyclic shift value of the
15 random access configuration and/or the like.
9. A first communication device (10) comprising a receiving arrangement (103)
configured to receive data from a second communication device on a radio
channel indicating a random access reception power to detect a random access
20 transmission, characterised in that the first communication device comprises a
control unit (101) arranged to determine a desired random access reception power
of the second communication device based on the received data and a parameter
of random access configuration that influences a detection performance of the
random access at the second communication device and to determine a random
25 access transmission power design setting based on the desired random access
reception power.
10. A first communication device (10) according to claim 9, wherein the received data
comprises a pointer value arranged to indicate a signalled random access
30 reception power in a table of random access reception power stored on a memory
unit (107) in the first communication device, and the control unit (101) is further
arranged to determine the desired random access reception power based on the
signalled random access reception power pointer and the parameter of random
access configuration.

11. A first communication device (10) according to claim 10, wherein the control unit (101) is further arranged to calculate the desired random access reception power by adding/subtracting an offset value to the signalled random access reception power wherein the offset value is based on the parameter of random access configuration.
12. A first communication device (10) according to claim 9, wherein the received data comprises a pointer value indicating a desired random access reception power in a table of desired random access reception power stored on a memory unit (107) in the first communication device, and the control unit (101) is arranged to use the pointer value in a table together with the parameter of random access configuration to determine the desired random access reception power.
13. A first communication device (10) according to claim 12, wherein the table comprises rows and columns, which are defined by pointer values and values of the parameter of random access configuration.
14. A first communication device (10) according to any of the claims 9-13, wherein the control unit (101) is arranged to perform a random access operation using the random access transmission power design and transmitting a random access request over a transmitting arrangement (105) of the first communication device.
15. A first communication device (10) according to any of claims 9-14, wherein the control unit (101) is further arranged to take into account power path loss between the first communication device and the second communication device to determine random access transmission power.
16. A first communication device (10) according to any of claims 9-15, wherein the parameter of random access configuration comprises a preamble format and/or a basic cyclic shift value of the random access configuration and/or the like.
17. A method in a second communication device within a communications network for transmitting data over a radio channel comprising the steps of:
- determining (52) a desired random access reception power from a first communication device such that the second communication device is enabled to

detect a random access request from the first communication device using a parameter of random access configuration,

- determining (54) data based on the desired random access reception power and a parameter of random access configuration, and

5 - transmitting (56) the data over a radio channel to the first communication device.

18. A method according to claim 17, wherein the step of determining data comprises to determine a pointer value to be included into the data, wherein a signalled random access reception power is determined based on the desired random
10 access reception power and the parameter of random access configuration and the determined signalled random access reception power is indicated by a pointer value retrieved from a table of signalled random access reception power, and the pointer value is included into the data.

15 19. A method according to claim 18, wherein the signalled random access reception power is calculated from the desired random access reception power and an offset value wherein the offset value is based on the parameter of random access configuration.

20 20. A method according to claim 17, wherein the transmitted data comprises a pointer value and the step of determining data comprises to determine the pointer value in a table of desired random access reception power, the pointer value is determined based on the determined desired random access reception power and the parameter of random access configuration.

25 21. A method according to claim 20, wherein the table of desired random access reception power comprises rows and columns, which are defined by pointer values and values of the parameter of random access configuration.

30 22. A method according to any of claims 17-21, wherein the parameter of random access configuration comprises a preamble format and/or a basic cyclic shift value of the random access configuration and/or the like.

35 23. A second communication device (20) comprising a control unit (201) arranged to determine a desired random access reception power from a first communication

device such that the second communication device is enabled to detect a random access request from the first communication device **characterised in that** the control unit (201) is further arranged to determine data based on the desired random access reception power and a parameter of random access configuration, and a transmitting arrangement (205) configured to transmit the data over a radio channel to the first communication device.

24. A second communication device (20) according to claim 23, wherein the control unit (201) is further arranged to determine a signalled random access reception power based on the desired random access reception power and the parameter of random access configuration stored on a memory unit (207), and to determine a pointer value based on the determined signalled random access reception power from a table of signalled random access reception power and the transmitted data comprises the pointer value.

25. A second communication device (20) according to claim 24, wherein the control unit (201) is further arranged to calculate the signalled random access reception power by using the desired random access reception power and an offset in the calculation, the offset being related to the parameter of random access configuration.

26. A second communication device (20) according to claim 23, wherein the transmitted data comprises a pointer value and the control unit (201) is arranged to determine data by determining a pointer value in a table of desired random access reception power, the pointer value is arranged to be determined based on the determined desired random access reception power and the parameter of random access configuration.

27. A second communication device (20) according to claim 26, wherein the table of desired random access reception power comprises rows and columns, which are defined by pointer values and values of the parameter of random access configuration.

28. A second communication device (20) according to any of the claims 23-27, wherein the parameter of random access configuration comprises a preamble

format and/or a basic cyclic shift value of the random access configuration and/or the like.