

5 **SYSTEM AND METHOD FOR MANAGING MOBILE-TERMINATED (MT)
 CALLS IN IMS NETWORK ENVIRONMENT USING ALTERNATIVE
 SIGNALING**

PRIORITY UNDER 35 U.S.C. §119(e) & 37 C.F.R. §1.78

This nonprovisional patent application claims priority based upon the following prior U.S. provisional patent application(s): (i) "SYSTEM AND METHODS FOR MANAGING MT CALL USING ALTERNATIVE SIGNALLING," Application No.: 60/941,322, filed June 1, 2007, in the name(s) of Adrian Buckley and Jan John-Luc Bakker; (ii) "SYSTEM AND METHODS FOR MANAGING MT CALL USING ALTERNATIVE SIGNALLING," Application No.: 60/942,949, filed June 8, 2007, in the name(s) of Adrian Buckley and Jan John-Luc Bakker; and (iii) "SYSTEM AND METHODS FOR MANAGING MT CALL USING ALTERNATIVE SIGNALLING," Application No.: 60/943,115, filed June 11, 2007, in the name(s) of Adrian Buckley and Jan John-Luc Bakker, which is (are) hereby incorporated by reference.

20 REFERENCE TO RELATED APPLICATION(S)

This application discloses subject matter that is related to the subject matter of the following U.S. patent application(s): (i) "SYSTEM AND METHOD FOR MANAGING MOBILE-TERMINATED (MT) CALLS IN IMS NETWORK ENVIRONMENT USING ALTERNATIVE SIGNALING" (Docket No. 32351-US-PAT), Application No.:____, filed even date herewith, in the name(s) of Adrian Buckley and Jan John-Luc Bakker; and (ii) "MESSAGE GENERATION SYSTEM AND METHOD FOR MANAGING IMS SIGNALING OVER A CIRCUIT-SWITCHED NETWORK" (Docket No. 32351-2-US-PAT), Application No.: _____, filed even date herewith, in the name(s) of Adrian Buckley and Jan John-Luc Bakker, which is (are) hereby incorporated by reference.

30 This application further discloses subject matter that is related to the subject matter of
the following U.S. patent application(s): (i) Application No. 11/328,875, filed on January 10,
2006 (Docket No. 30683-US-PAT); (ii) Application No. 11/347,874, filed on February 6,
2006 (Docket No. 30809-US-PAT); (iii) Application No. 11/503,465, filed on August 11,
2006 (Docket No. 31258-US-PAT); and (iv) Application No. 11/542,462, filed on October
35 3, 2006 (Docket No. 31348-US-PAT).

FIELD OF THE DISCLOSURE

The present patent disclosure generally relates to call processing in communications networks. More particularly, and not by way of any limitation, the present patent disclosure is directed to a system and method for managing a Mobile-Terminated (MT) call in a network environment including a Circuit-Switched (CS) network and an IP Multimedia Subsystem (IMS) network.

BACKGROUND

Operators may offer services hosted on or through an IMS network to CS-attached devices, which allows for certain IMS-based services (including supplementary services) to be consumed by such devices. Whereas delivery of an MT call originated by a calling party towards a CS-attached device is being contemplated as one of the IMS-based services, various problems arise with respect to managing such an MT call, especially where multiple MT calls may be involved.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the embodiments of the present patent disclosure may be had by reference to the following Detailed Description when taken in conjunction with the accompanying drawings wherein:

FIG. 1 depicts a network environment including Circuit-Switched (CS) network infrastructure and IP Multimedia Subsystem (IMS) infrastructure wherein an embodiment of the present patent disclosure may be practiced;

FIG. 2 depicts a simplified network arrangement wherein a Mobile-Terminated (MT) call is delivered through an IMS network node according to one embodiment;

FIG. 3 depicts a block diagram of a User Equipment (UE) device according one embodiment;

FIG. 4 depicts a block diagram of an IMS network node according one embodiment;

FIG. 5 depicts a reference point architecture associated with an embodiment of an IMS network node for purposes of the present patent disclosure;

FIGS. 6A and 6B depict exemplary message flow diagrams for managing the delivery of an MT call according to one or more embodiments of the present patent disclosure;

FIGS. 7A and 7B depict exemplary flowcharts associated with one or more embodiments operable at an IMS network node;

FIG. 8 depicts an exemplary flowchart associated with an embodiment operable at a UE device;

FIG. 9A-9C depict exemplary reference point architectures for purposes of the present patent disclosure;

5 FIG. 10 depicts an exemplary structure for transporting ICS protocol information according to one embodiment;

FIG. 11A depicts an exemplary data structure for transporting user data information according to one embodiment;

10 FIG. 11B depicts an embodiment of a message generation scheme that includes generating data structures of the type exemplified in FIGS. 10 and 11A for transporting user data information; and

FIG. 12 is a block diagram that depicts additional details of an embodiment of a communications device operable for purposes of the present patent disclosure.

15 DETAILED DESCRIPTION OF THE DRAWINGS

The present patent disclosure is broadly directed to a scheme for managing delivery of an MT call to a CS-attached UE device via an IMS Centralized Services (ICS) capable functionality. In one aspect, an embodiment is directed to a UE device operable in connection with an IMS network. The claimed embodiment comprises one or more of the
20 following: a component configured to receive an alternative signaling (AS) message via a Circuit-Switched (CS) network domain; a component configured to determine that the AS message is for delivery of a Mobile-Terminated (MT) call to be terminated at the UE device; a component configured to store call information received in the AS message, the call information comprising at least an IMS Multimedia Routing Number (IMRN); and a
25 component configured to initiate a Mobile-Originated (MO) call process towards a network node with the IMRN as a destination number, wherein the MO call process is operable to effectuate an access leg with the network node with respect to the MT call.

Another embodiment of the present patent disclosure is directed to an call connection method operable at a UE device, comprising one or more of the following: receiving an AS
30 message via a CS network domain disposed in connection with an IMS network; determining that the AS message is for delivery of an MT call to be terminated at the UE device; storing call information received in the AS message, the call information comprising at least an IMRN; and initiating an MO call process towards a network node with the IMRN

as a destination number, wherein the MO call process is operable to effectuate an access leg with the network node with respect to the MT call.

In a further embodiment, disclosed herein is a computer-accessible medium having a sequence of instructions which, when executed by a processing entity of a UE device, effectuate a call connection process with a network node. The claimed embodiment comprises one or more of the following: instructions for determining that an AS message received via a CS network domain is for delivery of an MT call to be terminated at the UE device through an IMS network; instructions for storing call information received in the AS message, the call information comprising at least an IMRN; and instructions for initiating an MO call process towards a network node with the IMRN as a destination number, wherein the MO call process is operable to effectuate an access leg with the network node with respect to the MT call.

A system and method of the present patent disclosure will now be described with reference to various examples of how the embodiments can best be made and used. Like reference numerals are used throughout the description and several views of the drawings to indicate like or corresponding parts, wherein the various elements are not necessarily drawn to scale. Referring now to the drawings, and more particularly to FIG. 1, an exemplary network environment 100 is depicted wherein an embodiment of the present patent disclosure may be practiced for managing the delivery of an MT call to a UE device that is CS-attached for some reason. As depicted, the network environment 100 includes an access space 104 comprised of a number of access technologies available to one or more UE devices 102-1 through 102-N, of which a particular UE device may be a CS-attached device that is operable to consume one or more IMS Centralized Services (ICS). For purposes of the present disclosure, a UE device may be any tethered or untethered communications device, and may include any personal computer (e.g., desktops, laptops, palmtops, or handheld computing devices) equipped with a suitable wireless modem or a mobile communications device (e.g., cellular phones or data-enabled handheld devices capable of receiving and sending messages, web browsing, et cetera), or any enhanced PDA device or integrated information appliance capable of email, video mail, Internet access, corporate data access, messaging, calendaring and scheduling, information management, and the like. In general, a UE device may be capable of operating in multiple modes in that it can engage in both Circuit-Switched (CS) as well as Packet-Switched (PS) communications, and can transition from one mode of communications to another mode of communications without

loss of continuity. Furthermore, those skilled in the art will recognize that a wireless UE device may sometimes be treated as a combination of a separate mobile equipment (ME) device and an associated removable memory module. Accordingly, for purposes of the present disclosure, the terms “wireless device” and “UE device”, which are broadly
5 synonymous, are each treated as representative of both ME devices alone as well as the combinations of ME devices with removable memory modules as applicable.

The access space 104 may be comprised of both CS and PS network domains, which may involve wireless technologies, wireline technologies, broadband access technologies, etc. For example, reference numeral 106 refers to wireless technologies such as Global
10 System for Mobile Communications (GSM) networks and Code Division Multiple Access (CDMA) networks, although it is envisaged that the teachings hereof may be extended to any 3rd Generation Partnership Project (3GPP)-compliant cellular network (e.g., 3GPP or 3GPP2) as well. Reference numeral 108 refers to broadband access networks including wireless local area networks or WLANs, Wi-MAX networks as well as fixed networks such
15 as DSL, cable broadband, etc. Thus, for purposes of the present disclosure, the access technologies may comprise radio access technologies selected from IEEE 802.11a technology, IEEE 802.11b technology, IEEE 802.11g technology, IEEE 802.11n technology, GSM/EDGE Radio Access Network (GERAN) technology (both CS and PS domains), and Universal Mobile Telecommunications System (UMTS) technology, and
20 Evolution – Data Optimized (EVDO) technology, and so on. Additionally, also exemplified as part of the access space 104 is the conventional wireline PSTN infrastructure 110 illustrated in FIG. 1. It should be realized that regardless of the access network technologies or communication modes, an ICS-capable UE device that is CS-attached may simply be referred to as an ICS UE device for purposes of the present disclosure.

25 An IMS core network 112 may be coupled to one or more of the various access networks set forth above, including any CS-based networks. As is well known, the IMS standard defined by the 3GPP body is designed to allow service providers manage a variety of services that can be delivered via IP over any network type, wherein IP is used to transport both bearer traffic and Session Initiation Protocol (SIP)-based signaling traffic.
30 Broadly, IMS is a framework for managing the applications (i.e., services) and networks (i.e., access) that is capable of providing multimedia services. IMS defines an “application server” as a network element that delivers services subscribers use, e.g., voice call continuity (VCC), Push-To-Talk (PTT), etc. IMS manages applications by defining common control

components that each application server (AS) is required to have, e.g., subscriber profiles, IMS mobility, network access, authentication, service authorization, charging and billing, inter-operator functions, and interoperation with the legacy phone network.

It should be understood that whereas IMS is defined by the 3GPP standards body that
5 mainly addresses GSM networks, another group, 3GPP2, is involved in defining a closely analogous architecture referred to as Multimedia Domain (MMD). MMD is basically an IMS for CDMA networks, and since MMD and IMS are roughly equivalent, the term "IMS" may be used in this present patent disclosure to refer collectively to both IMS and MMD where applicable. In addition, fixed network standards for NGN (Next Generation
10 Networks) that are based on and/or reuse IMS are also being developed by bodies such as ETSI TISPAN, Cablelabs and the ITU-T. NGN and IMS are roughly equivalent, and accordingly the term "IMS" may also be used in this present patent disclosure to refer collectively to both IMS and NGN where applicable.

Continuing to refer to FIG. 1, reference numerals 114-1 to 114-N refer to a plurality
15 of AS nodes operable to support various services, e.g., VCC, PTT, etc., as alluded to hereinabove. In addition, another network element 130, broadly defined as an "ICS network function" or "ICS node" for purposes of the present disclosure, is associated with the IMS network 112 for effectuating the functionality with respect to managing an MT call originated by a calling party (not shown) towards an ICS UE device. In one arrangement,
20 the ICS network node 130 may be embodied as an IMS CS Control Function (ICCF) that may be associated with the ICS UE device's home IMS core network. Functionalities such as call continuity control function (CCCF) and network domain selection (NeDS) may also be associated therewith. In general, the CCCF is operable as a new IMS application server element that resides in the home IMS network and tracks all call sessions and related mobile
25 voice-over-IP (VoIP) bearer traffic, including call handover/routing between CS and IMS domains. The NeDS portion is responsible for performing, *inter alia*, registration/de-registration management between the IMS and CS networks (e.g., GSM, CDMA, etc.). Despite being potentially separate functions, it is possible to integrate both the CCCF and NeDS functionalities into a single IMS-compatible network element (not explicitly shown in
30 FIG. 1). For purposes of managing MT call delivery, however, the ICS network function 130 includes a CS Access Adaptation Function (CAAF) 116 as well as a SIP User Agent (UA) 118. Also, a suitable session control function (SCF) 120 may be provided as part of the ICS node 130 with respect to applicable radio access technology, e.g., gsmSCF.

Additional IMS functionalities such as the following may also be operably associated with the ICS node 130 in some form: Domain Transfer Function (DTF) (also referred to as Functional Entity FE-A), CS Adaptation Function (CSAF) (also referred to as FE-B), CAMEL Service (also referred to as FE-C), and Domain Selection Function (DSF) (also referred to as FE-D). Accordingly, for purposes of the present disclosure, the term "network node" with reference to an IMS core network may comprise one or more of the foregoing functionalities in addition to the ICS functionality, in any suitable architecture, implementation, integration, or the like, as well as additional service logic described in detail hereinbelow.

Furthermore, although not shown in FIG. 1, a master user database, referred to as a Home Subscriber Server or HSS, may be provided as part of the home IMS network 112, for supporting the various IMS network entities that actually manage calls or sessions such as the ICS node 130. In general, the HSS database may contain user profiles (i.e., subscription-related information), including various user and device identifies such as International Mobile Subscriber Identity (IMSI), Temporal Mobile Subscriber Identity (TMSI), International Mobile Equipment Identity (IMEI), Mobile Subscriber ISDN Number (MSISDN), Universally Unique Identifier (UUID), as well as additional IMS-specific identities such as IM Multimedia Private Identity (IMPI) and IP Multimedia Public Identity (IMPU) that are implemented as Tel-Uniform Resource Identifiers (URIs) or SIP-URIs. Whereas the IMPI is unique to a particular user in a 3GPP system (i.e., (I)SIM) or could be unique to a particular UE device in another technology, it is possible to have multiple Public Identities (i.e., IMPUs) per IMPI. Further, the IMPU can also be shared with IMPI such that two or more devices can be reached with the same identity (e.g., a single phone number for an entire family).

Additionally, appropriate database structures (e.g., DB 122), timer mechanisms (e.g., timer 124) and suitable logic 126 may be provided in association with the ICS node 130 for purposes of configuring and managing a pool of IP Multimedia Routing Numbers (IMRNs) from which a select IMRN may be dynamically allocated for purposes of managing the delivery of an MT call to an ICS UE device, as will be set forth in detail below.

FIG. 2 depicts a simplified network arrangement 200 that is an analogous view of the network environment 100 described above, wherein an MT call originated by a calling party 204 is delivered through an IMS network node according to one embodiment. An ICS UE 202 is exemplary of the various UE devices described in the foregoing sections with respect

to FIG. 1, wherein ICS UE 202 is attached to a CS network (CSN) 208 for any number of reasons. For purposes of the present disclosure, an embodiment of the ICS UE device 202 is a UE device that is capable of receiving telephony and other services offered by the IMS core while the voice bearer is established via a CSN. It may be realized that a UE device
5 may be CS-attached in spite of the capability of the UE device (e.g., a mobile communications device or MCD) to be able to regularly communicate pursuant to both CS and PS communications. Hence, such a device might not be able to receive, or otherwise communicate, pursuant to a PS-based service. In some instances, the UE device may, in fact, not be PS-capable. Or, the subscription pursuant to which the UE device operates may
10 not permit receiving a PS-based service. Or, even if the UE device is PS-capable, a serving PS network (PSN) might not support the particular media (e.g., speech) that is to be communicated pursuant to the communication service. Additionally, even if the UE device is PS-capable, the user's preference might be to utilize CS network connections, e.g., the user may prefer not to connect to an available PSN when the user is roaming. Or, operator,
15 or other, policy might prohibit PS-based access to the UE device.

Irrespective of the reason(s) as to why the ICS UE device 202 is CS-attached, it is desirous of consuming an IMS-based service such as, e.g., an ICS service, that is mediated over the IMS network 112. An ICS network function (ICS-NF) 206 is exemplary of the ICS node 130 shown in FIG. 1 that may embody the functionality of an ICCF element operable
20 to effectuate an ICS service, which in the exemplary embodiment is the delivery of an MT-call originated by the calling party 204. A suitable network 210 is operably disposed between the calling party 204 and the IMS network 112 for effectuating a remote leg connection with respect to the MT call service.

As set forth previously, the ICS network node 206 includes appropriate logic to
25 generate and manage a pool of dynamically allocable IMRNs for purposes of effectuating MT call delivery to ICS UE devices. In addition, the ICS network node 206 is operable with a suitable alternative signaling message application such as an Unstructured Supplementary Service Data (USSD) messaging application or a Short Messaging Service (SMS) application that may be used for transporting an assigned IMRN to the called party, i.e., ICS
30 UE device 202, via a CS domain. In one embodiment, the alternative messaging application may be co-located with the ICS node 206. In another embodiment, the functionality of the alternative messaging application may be embodied as a separate entity operably associated with the ICS node 206. Accordingly, a network node for purposes of the present disclosure

may also include an enhanced MSC or an ICS-capable MSC having the foregoing functionalities.

Additionally, a Back-to-Back User Agent (B2BUA) functionality may also be provided in conjunction with the ICS node 206 for setting up and bridging appropriate remote and access legs of an MT call. In general, if it is determined that an incoming call via a remote leg from a calling party such as the party 204 is an MT call to be delivered to the ICS UE 202 that is attached to the CS domain, appropriate logic associated with the ICS node 206 is operable to effectuate a specialized call treatment process that allows establishment of an access leg to the ICS UE 202. Upon receiving suitable signaling messages with respect to the incoming MT call on the remote leg, the ICS node 206 stores relevant call parameters and dynamically allocates a routable number such as an IMRN (and other related information) that may be correlated with the received session setup request, which is then provided to the ICS UE 202 via a suitable alternative messaging scheme (e.g., USSD or SMS). As will be seen in further detail below, the ICS UE 202 then establishes a Mobile-Originated (MO) call via CS signaling to the ICS node 206 to set up the access leg.

Based on the foregoing, one skilled in the art will recognize that the functionality of the ICS UE 202 may include appropriate components that facilitate reception of call setup information via alternative signaling from the ICS node 206, processing of the received call setup information, and generation of appropriate responses and/requests to the ICS node 206. FIG. 3 depicts a block diagram of a UE device such as, e.g., ICS UE 202, according to one embodiment. One or more processing entities 302 are provided for overall control of the various processes executable on the device. One or more timer mechanisms 304 may also be provided for effectuating timing control with respect to certain time-based functions. For efficient transfer of information, suitable message encode/decode blocks 310, dictionaries 308 and message parsers 306 may be provided. It will be recognized that functionalities such as message encode/decode blocks, dictionaries and message parsers on the device side may be optional, and are generally dependent on the corresponding functionalities on the network side.

Similarly, the functionality of the ICS-NF node 206 may also include appropriate components that facilitate generation of suitable alternative signaling messages to the ICS UE device 202, reception and processing of the call setup information received from the ICS UE device 202, and generation of appropriate responses and/requests to the ICS UE device 202 as well as the remote party, i.e., calling party 204. FIG. 4 depicts a block diagram of an

IMS network node, e.g., ICS-NF node 206, according one embodiment. One or more processing entities 402 are provided for overall control of the various processes executed by the ICS node 206 regardless of its architecture. A suitable transmit/receive (Tx/Rx) block 422 is operable to send or receive various messages over access and remotes legs of an MT call as will be set forth in detail below. A local storage module 420 may be provided for storing appropriate call information relating to the management of MT call delivery. An IMRN generator 406, IMRN mapping/logic 410 and one or more timer mechanisms 404 associated therewith may also be provided with respect the generation of IMRNs and their assignment/allocation, selection and management. A suitable ICS message application (e.g., USSD or SMS application) 418 may be co-located with a B2BUA functionality 414 for effectuating the MT call delivery process as outlined hereinabove. In addition, appropriate message encode/decode blocks 408, dictionaries 412 and message parsers 416 may be provided for purposes of efficient transfer of information.

FIG. 5 depicts a reference point architecture 500 associated with an embodiment of an IMS network node, e.g., ICE node 206, for purposes of the present patent disclosure. As pointed out previously, the ICE node 206 embodies an ICCF that supports functionality necessary for provisioning IMS services for calls originated or terminated over CS access networks. In a typical implementation, such a network functionality belongs to the IMS home network and is comprised of two functions: a Remote CS Access Adaptation Function (R-CAAF) 506 and a Remote User Agent (RUA) 504. Functionally, RUA 504 may be comprised of the B2BUA functionality 414 described above, and combines a CS call established between an ICE UE and the User Agent to set up a voice bearer as well as an IMS CS Control Channel (ICCC) established between the RUA and the UE, either directly or via the CAAF. It enables the completion of the call leg towards the ICE UE (i.e., the access leg, also referred to as the "UE leg"); and presents the session through a Call Session Control Function (CSCF) node, such as a Serving CSCF (S-CSCF) toward the other party, e.g., the calling party, via the remote leg (also referred to as the "RUA leg"). Thus, it can be seen that the UE leg and the RUA leg segments may be combined to form the B2BUA functionality at RUA 504. In one implementation, RUA 504 may be realized as an IMS Application Server (AS) element with an ISC interface to an S-CSCF 502. In this mode, it is invoked as the very first SIP AS in the originating calls and the last one in terminating calls, i.e., closest to the access. This approach for physical realization of RUA 504 may be referred to as the Application Server approach.

In another implementation, RUA 504 may be provided with a Gm interface to CSCF 502 operating as a Proxy CSCF or P-CSCF. In this mode, the RUA acts as an IMS UE remotely controlled from the ICS UE device, i.e., an ICS user connected via CS access and the RUA is perceived from the IMS point of view as an IMS user with bi-directional speech capabilities. This approach for physical realization of RUA 504 may be referred to as the IMS Adaptor approach.

Continuing to refer to FIG. 5, the CAAF is an adaptation function for the service control signaling between a CS network and the IMS. The CAAF is operable to convey the service control signaling information received from the ICS UE over CS domain access signaling to the RUA and vice versa. The RUA uses the information received from the CAAF for initiation and control of SIP sessions. In one implementation, the functionality of a CAAF may be segregated between the ICS node 206 and the ICS UE device 202. In such a scenario, R-CAAF 506 resides in conjunction with RUA 504 as part of the ICCF, whereas a Local CAAF component 508 may be provided in the ICS UE device 202 for enabling an ICCF with CS access signaling.

FIGS. 6A and 6B depict exemplary message flow diagrams for managing the delivery of an MT call according to one or more embodiments of the present patent disclosure. In particular, message flow diagram 600A shown in FIG. 6A exemplifies the use of USSD transport for facilitating session terminations to a UE device, e.g., ICS UE 202. Pursuant to receiving appropriate signaling messages with respect to an incoming MT call 610 from a calling party (not shown), an S-CSCF node 608 is operable to generate a SIP INVITE method request or message 612 towards an ICCF instance at an IMS network node, e.g., ICS-NF 206. In one embodiment, the ICCF instance may be bound to the target ICS UE device 202 of the call, and is operable to store the SIP request/response header field values or header field value fragments such as URI parameters received in the SIP INVITE method request 612 such as but not limited to TO, FROM, CONTACT, PRIVACY INDICATION, an identifier such as a Globally Routable User Agent Uniform Resource Identifier (GRUU), a Request Uniform Resource Identifier (R-URI), SDP, etc. Against this information, an IMRN such as, e.g., an E.164 number, is assigned (i.e., a mapping relationship or correlation record may be established between the IMRN and the received call information). In one embodiment, the IMRN may be dynamically allocated. In another embodiment, the IMRN may be assigned from a range or set of numbers, e.g., sequentially. Regardless of how an IMRN is generated and/or assigned, if the assigned IMRN is returned

back from the ICE UE device 202, the ICS-NF 206 includes the functionality/logic operable to deduce the stored information and the corresponding remote call leg based on examining the mapping relationship.

Responsive to the SIP INVITE method request message 612, the ICS-NF node 206
5 initiates an ICS Incoming Call Request using one or more USSD messages 614 that include but not limited to the following: (i) an indication (e.g., a flag, etc.) to identify that USSD messaging 614 is for an ICS application; (ii) an indication (e.g., a flag, etc.) to identify that the message is for an MT call; (iii) A-Party Number or ID (e.g., SIP URI or Tel URI), if allowed, or an indication that A-Party ID is withheld; (iv) B-Party Number or ID, e.g., SIP
10 URI or Tel URI; (v) GRUU; (vi) the Called Party's ID so that the B-Party knows which Public User ID it was called on, and so on, which may collectively be referred to as "call information." As illustrated in FIG. 6A, the USSD messaging 614 is directed to an HSS 604 that can identify a Mobile Switching Center (602) serving the ICS UE device 202. Although not explicitly shown in this FIG., a timer may be started at the ICS-NF node 206 to monitor
15 the "staleness" or "timeliness" of the assigned IMRN that is sent out via USSD messaging 614. Accordingly, the timer is operable to keep track of the time elapsed between the transmission of USSD messaging 614 and the IMRN's reception at ICS-NF 206. The elapsed time may be compared against a threshold for determining whether the received IMRN is stale. Or, the timer may be programmed to time out after an expiration time, which
20 may be preconfigured. In one embodiment, an IMRN received after the expiration time may be considered stale or invalid, and any MO call received at the ICS node 206 with that IMRN may be rejected.

In response to receiving USSD messaging 614, HSS 604 generates one or more USSD messages 616 towards MSC 602 (which in some cases may be Visited MSC or
25 VMSC) associated with the ICS UE device 202. In one embodiment, MSC 602 may optionally page the ICS UE device 202. Regardless of such functionality, MSC 602 is operable to locate the UE device and forward one or more USSD messages 618 containing the various pieces of call information to the ICS UE device 202. In an optional arrangement, message flow 600A may include optional USSD Acknowledge (ACK) messages 620 that
30 may be transmitted back to ICS-NF 206. Whether or not such ACK messaging is utilized, the ICS UE device 202 includes functionality to originate an MO voice call in the CS domain using the received IMRN according to any known or heretofore unknown procedures. Further, an application timer mechanism (not shown) may be initiated at the

ICS UE device 202 to time the process of the MO call. For instance, the timer may be set for a certain time period, and when the timer expires, the call process may be attempted for a certain number of times (e.g., a maximum of 5 times). In one implementation, the ICS UE device 202 is operable to generate the MO call in accordance with the procedures set forth in 3GPP TS 23.018 and 3GPP TS 23.008 documentation in order to establish an access leg via the CS domain to ICS-NF 206. Accordingly, a call setup message 622 using the IMRN as the destination number is generated by the ICS UE device 202 towards MSC 602. In one implementation, the MO call is processed in the CS network domain according to CS origination procedures set forth in 3GPP TS 23.206, Clause 6.2.2. However, the associated CAMEL triggers may be deactivated due to the CAMEL deactivation trigger information being provided in the Mobile Application Part (MAP) Insert Subscriber Data. In response to the call setup message 622, MSC 602 generates an ISDN User Part (ISUP) Initial Address Message (IAM) 624 towards a Media Gateway Controller Function (MGCF) 606 that is in turn operable to transmit a SIP INVITE method request or message 626 towards the ICS node 206. Those skilled in the art will recognize that there may be additional intermediary network entities involved in mediating the message flow between MGCF 606 and the ICS node 206, with additional/optional parameters. For instance, MGCF 606 may initiate a SIP INVITE method request towards an Interrogating CSCF (I-CSCF) in the home IMS network associated with the ICS UE device 202, which I-CSCF may then route the SIP INVITE method request to the ICS node 206 using one of the standard procedures set forth in 3GPP TS 23.228 documentation. The SIP INVITE method request 626 may also contain a P-Network-Access-Info Header field indicating that the SIP INVITE method request has been generated from the CS domain. Moreover, the SIP INVITE method request contains an indication that the bearer path is to be set over the CS domain. Further, although direct routing to the ICS node 206 is illustrated in FIG. 6A, routing via an S-CSCF may also be implemented in certain embodiments. Additionally, where a Public Service Identity (PSI) is utilized (e.g., one that matches the IMRN), the applicable ISC and Ma reference points are supported by the ICS node 206.

Responsive to receiving the SIP INVITE method request 626, the IMRN-based timer may be stopped and the ICS node 206 is operable to analyze the received IMRN for further processing. Upon determining that the received IMRN is valid (i.e., the IMRN is not timed out based on a time-to-live or life time parameter), the ICS node 206 cross-references or otherwise correlates the IMRN with the stored information so that it can identify the

appropriate remote leg with respect to completing the incoming call from the ICS UE device 202. Thereafter, the access and remote call legs are bridged using the B2BUA functionality. The IMRN may then be released for immediate use or returned to a quarantine pool for a period of time after which it may be reused again at some suitable point. These processes are exemplified in block 628. The ICS node 206 returns a SIP 200 (OK) response message 630 to S-CSCF 608, which is propagated eventually to the calling party that initiated the MT call. Likewise, a SIP 200 (OK) response message 632 is transmitted on the access leg towards MGCF 606, which then generates an ISUP Address Complete Message (ACM) 634 towards the ICS UE device 202. It should be noted that the SIP 200 (OK) response messages 630 and 632 may be generated in parallel or in any sequential order. Thereafter, an end-to-end bearer path 636 for the transmission of media is established between the ICS UE device 202 and the calling party (not shown).

Referring now to FIG. 6B, message flow diagram 600B shown therein exemplifies the use of SMS transport for facilitating session terminations to ICS UE 202. It will be recognized that the message flow relative to the SMS transport is substantially similar to the USSD message flow described in detail hereinabove. Accordingly, only certain highlights are set forth below with respect to the message flow 600B. As before, S-CSCF node 608 is operable to generate a SIP INVITE method request message 612 towards an ICCF instance at an IMS network node, e.g., ICS-NF 206, pursuant to receiving appropriate signaling messages with respect to an incoming MT call 610 from a calling party (not shown), wherein SIP request header field values or header field fragments such as URI parameters, e.g., values for TO, FROM, CONTACT, PRIVACY INDICATION, GRUU, R-URI, SDP, etc., are transported. Against this information, an IMRN may be assigned (i.e., a mapping relationship or correlation record may be established between the IMRN and the received call information), which may be generated and managed in accordance with one or more procedures set forth above. Further, similar to the USSD-based message flow in FIG. 6A, the ICS-NF node 206 includes the functionality/logic operable to deduce the stored information and the corresponding remote call leg based on examining the IMRN when it is returned back.

Responsive to the SIP INVITE method request message 612, the ICS-NF node 206 initiates an ICS Incoming Call Request using one or more SMS messages 652 that include the various pieces of call information as described previously. SMS messaging 652 is directed to HSS 604 that can identify a Short Message Server Center (SMSC) 650 associated

with ICS UE 202. Again, appropriate timer mechanisms may be implemented at the ICS node 206 to monitor and determine if an assigned IMRN is valid or not upon its return. HSS 604 is operable to propagate the SMS messages 654 to SMSC 650 which then provides suitable SMS messaging 656 along with the call information contained therein to ICS UE 202. Those skilled in the art will recognize that when SMS is used to announce incoming calls to a UE device, a separate mailbox may be necessary which must not become full since a full SMS mailbox can prevent signaling of calls using SMS. In one embodiment, optional SMS Acknowledgement (ACK) messaging 658 may be propagated from ICS UE 202 towards the ICS node 206. Thereafter, the ICS UE device 202 may initiate an MO voice call in the CS domain using the received IMRN according to the methodologies set forth previously, with applicable modifications, if any. Accordingly, appropriate call setup messaging 622 using the IMRN as the destination number is generated by the ICS UE device 202 towards MSC 602 serving the ICS UE device 202. Although there may be other network elements in addition to the elements shown, the messaging flow thereafter remains basically the same as that of the USSD-based flow shown in FIG. 6A, *mutatis mutandis*, in order to effectuate the bearer path 636 between ICE UE 200 and the calling party.

Those skilled in the art will recognize that the foregoing signaling flow scenarios may be implemented regardless of whether the ICS UE device 202 is attached to an MSC node that is enhanced for ICS or not. In either implementation, the incoming session may be delivered over the I1 reference point and the media bearer path is established via the CS network. Furthermore, although the USSD and SMS messages are particularly exemplified for purposes of providing an alternative signaling mechanism, supplementary messages such as additional CS domain-based Facility messages may also be utilized for purposes of the present patent disclosure.

FIGS. 7A and 7B depict exemplary flowcharts associated with one or more embodiments of the present patent disclosure in accordance with one or more parts of the message flow diagrams described above. Reference numeral 700A in FIG. 7A refers to a scheme of operations that take place at the network side in one embodiment. A signaling message pursuant to an MT call is received at a CSCF node, wherein the MT call generated by a calling party towards an ICS UE device that is CS-attached (block 702). A SIP request message (e.g., a SIP INVITE method request) is generated towards an ICCF embodied in an ICS node (block 704) which anchors the MT call and assigns an IMRN against the call information received via the SIP request (block 706). One or more alternative signaling

messages (e.g., USSD or SMS messages) are generated towards the ICS UE device, wherein the alternative signaling messages are operable to contain the assigned IMRN and are encoded with applicable call information relative to the incoming MT call on the remote leg. Appropriate timers may be initiated to monitor the elapsed time against the assigned IMRN.

5 These operations are set forth in block 708. Upon receiving the assigned IMRN back from the ICS UE device pursuant to a MO call procedure initiated the ICS UE device to establish an access leg (block 710), the ICS node is operable to analyze the received IMRN to ensure its validity; and if valid, correlate it against the stored information that corresponds to the remote leg of the incoming MT call (block 712). Thereafter, the access and remote legs are

10 bridged in order to establish an end-to-end bearer path between the ICS UE device and the calling party (block 714).

Reference numeral 700B in FIG. 7B refers to another embodiment that sets forth the operations at the network side regardless of whether the functionality of the CSCF and ICCF entities are integrated into a single IMS network node. At block 750, a message relating to

15 an MT call is received, wherein the message can be a SIP INVITE method request, as described above. Appropriate logic operating at the IMS network node is operable to determine that the MT call is to be delivered to a UE device over a CS domain. Call information received via the signaling message is stored and associated with an IMRN in a mapping relationship (block 752). The IMRN can be dynamically generated, or selected

20 from a pool of numbers, or otherwise provisioned. One or more alternative signaling (AS) messages (e.g., USSD or SMS messages) are transmitted to the UE device, wherein at least one of the AS messages includes the IMRN and an indication that the AS messaging is for delivery of the MT call (block 754). Thereafter, the IMRN is received back from the UE device pursuant to an MO call terminating at the IMS network node, wherein the IMRN is

25 used as a destination number (block 756). Upon verifying that the IMRN is valid, the service logic at the network node is operable to initiate an access leg with the UE device and bridge the access leg with a remote leg associated with the calling party for establishing an end-to-end path for the MT call between the calling party and the UE device (block 758).

FIG. 8 refers to a scheme of operations 800 that take place at an ICS-capable UE

30 device. Upon receiving one or more AS messages (i.e., USSD or SMS messages) at the CS-attached ICS UE device (block 802), a determination is made if the received alternative signaling messages relate to an ICS application (block 804). If so, another determination may be made as to whether the ICS application relates to the delivery of an MT call

originated by a calling party. If so, the call information received via the alternative signaling mechanism, including an IMRN, may be stored at the ICS UE device. The call information may also include a token or flag (or other indicator) to identify that a call be made over a CS domain for completing the MT call. These operations are set forth in block 806. As alluded to previously, optional acknowledgement messaging towards the network may be effectuated by the ICS UE device, in addition to initiating a suitable application timer for timing the call process. Thereafter, an MO call procedure is performed by the UE device using the IMRN as the destination number (i.e., the B-Party number) towards the network via a CS path (block 810). Upon receiving an Address Complete Message (ACM) from the network (block 810), the ICS UE device engages in a call session carried via an end-to-end bearer path established with the calling party (block 812).

To manage a pool of dynamically allocable IMRNs, the network node (e.g., ICS-NF 206) may be configured in a number of ways with respect to the use of E.164 numbers as IMRNs. For example, a particular E.164 number may be provided as a "starting address" number of an IMRN range or set. Another E.164 number may operate as a range/set delimiter with respect to the IMRN range or set. To allow flexibility, it may be desirable to provide for different pools of IMRNs to be configured from different number ranges. Further, additional time-based parameters may be provisioned such as, for example, (i) life time an IMRN can live for and (ii) quarantine time of an IMRN, that is, the duration for which an IMRN cannot be reused after it has been released back to the IMRN pool. In addition, the functional behavior of the ICS node functionality involves the following: if the ICS node receives a SIP INVITE method request that contains a Request URI (R-URI) for a B-Party number that has ICS services (e.g., the number associated with the ICS UE device), appropriate service logic at the ICS node is operable to determine via, for example, Domain Selection functionality and other mechanisms such as presence, HSS-mediated methodologies, etc., the domain that the ICS UE device is in and how the device registered in that domain. As described previously, the ICS node is operable to assign an IMRN to the received GRUU via the SIP INVITE method request. A number of mapping relations may be achieved between the IMRN and other information elements of the received call information in any combination: e.g., $\text{IMRN} \Rightarrow \{\text{GRUU}; \text{P-Asserted-Identity(ies)}; \text{P-Called-Party-ID}; \text{B-number}; \text{A-number} + \text{Privacy ID, etc.}\}$. Upon receipt of a SIP INVITE method request from an MGCF with the map-assigned IMRN as the R-URI on the access leg,

appropriate timer mechanisms are operable to determine validity of the IMRN, enforce a quarantine procedure, etc.

From the perspective of the device side, the functionality of an ICS-capable UE device includes appropriate logic to determine if a received USSD or SMS message or messages is/are with respect to an ICS application. In one embodiment, such determination
5 may be effectuated by analyzing the contents of the received message to determine if there is a flag or other indicator associated therewith. Likewise, additional flags or other indicators may be employed to indicate that the received messaging is for an MT call. After effectuating an MO call based on suitable CS origination procedures, the UE device may
10 receive an alerting message. The UE device may include service logic that facilitates, upon receipt of the alerting message, displaying of the A-Party identity if it has been received and the B-Party address that was used to address the UE device with respect to the MT call.

FIG. 9A-9C depict exemplary reference point architectures associated with an IMS environment for purposes of the present patent disclosure. Reference numeral 900A in FIG.
15 9A refers to an implementation where an Application Server approach is represented. The ICCF/ICS node 206 is realized as an IMS Application Server with an IMS Session Control (ISC) interface to the S-CSCF for both I1-cs and I1-ps. An A/Iu reference point interface is provided between ICS UE device 202 and VMSC 602, which in turn uses an ISUP interface with MGCF 606. An Mj reference point interface is provided between MGCF 606 and
20 CSCF 608, which interfaces with HSS 604 via a Cx reference point interface. The ICS node 206 also interfaces with HSS 604 via an Sh reference point interface and with another Application Server such as AS 114-N via a Ut reference point interface. An Ma reference point interface is also disposed between CSCF 608 and the ICS node 206. A Gm reference point interface is provided between ICS UE device 202 and CSCF 608. Further, the CAAF
25 of the ICS node 206 presents a MAP/gsmSCF-HLR interface towards HSS 604 for effectuating appropriate alternative signaling.

FIG. 9B depicts an IMS adaptor model 900B wherein the ICCF/ICS node 206 is provided with an Mw reference point towards CSCF 608 and the ISC for I1-cs only. The reference point architecture 900C depicted in FIG. 9C is representative of an IMS adaptor
30 approach for both I1-cs and I1-ps.

Upon receipt of the USSD or SMS messages, the ICS UE device is operable to apply special call processing that may include decoding the contents of the received messages and setting up a call towards the decoded IMRN as the destination number. In one exemplary

implementation, such a call setup may proceed only after receiving consent from the user operating the ICS UE device. The requirement of the necessary special call processing may be signaled by a suitable code point provided in the coding of the USSD or SMS messages from the ICS network node towards the UE device. In one implementation, any reserved
 5 codings may be assumed by the receiving entity to be the GSM 7-bit default alphabet (the same as code point [00001111]). The octet may be used according to a coding group that is indicated in bits [7:4]. The following Tables 1A through 1F illustrate an exemplary coding scheme:

10

Table 1A

Coding Group Bits 7..4	Use of bits 3..0
0000	Language using the GSM 7 bit default alphabet Bits 3..0 indicate the language: 0000 German 0001 English 0010 Italian 0011 French 0100 Spanish 0101 Dutch 0110 Swedish 0111 Danish 1000 Portuguese 1001 Finnish 1010 Norwegian 1011 Greek 1100 Turkish 1101 Hungarian 1110 Polish 1111 Language unspecified

Table 1B

Coding Group Bits 7..4	Use of bits 3..0
0001	0000 GSM 7 bit default alphabet; message preceded by language indication. The first 3 characters of the message are a two-character representation of the language encoded according to ISO 639, followed by a CR character. The CR character is then followed by 90 characters of text.
	0001 UCS2; message preceded by language indication The message starts with a two GSM 7-bit default alphabet character representation of the language encoded according to ISO 639. This is padded to the octet boundary with two bits set to 0 and then followed by 40 characters of UCS2-encoded message. An MS not supporting UCS2 coding will present the two character language identifier followed by improperly interpreted user data.
	0010..1111 Reserved

Table 1C

5

Coding Group Bits 7..4	Use of bits 3..0
0010..	0000 Czech 0001 Hebrew 0010 Arabic 0011 Russian 0100 Icelandic
	0101..1111 Reserved for other languages using the GSM 7 bit default alphabet, with unspecified handling at the MS
0011	0000..1111 Reserved for other languages using the GSM 7 bit default alphabet, with unspecified handling at the MS

Table 1D

Coding Group Bits 7..4	Use of bits 3..0																														
01xx	General Data Coding indication Bits 5..0 indicate the following: Bit 5, if set to 0, indicates the text is uncompressed Bit 5, if set to 1, indicates the text is compressed using the compression algorithm defined in 3GPP TS 23.042 Bit 4, if set to 0, indicates that bits 1 to 0 are reserved and have no message class meaning Bit 4, if set to 1, indicates that bits 1 to 0 have a message class meaning: <table><tr><td>Bit 1</td><td>Bit 0</td><td>Message Class:</td></tr><tr><td>0</td><td>0</td><td>Class 0</td></tr><tr><td>0</td><td>1</td><td>Class 1 Default meaning: ME-specific.</td></tr><tr><td>1</td><td>0</td><td>Class 2 (U)SIM specific message.</td></tr><tr><td>1</td><td>1</td><td>Class 3 Default meaning: TE-specific (see 3GPP TS 27.005)</td></tr></table> Bits 3 and 2 indicate the character set being used, as follows: <table><tr><td>Bit 3</td><td>Bit 2</td><td>Character set:</td></tr><tr><td>0</td><td>0</td><td>GSM 7 bit default alphabet</td></tr><tr><td>0</td><td>1</td><td>8 bit data</td></tr><tr><td>1</td><td>0</td><td>UCS2 (16 bit)</td></tr><tr><td>1</td><td>1</td><td>Reserved</td></tr></table>	Bit 1	Bit 0	Message Class:	0	0	Class 0	0	1	Class 1 Default meaning: ME-specific.	1	0	Class 2 (U)SIM specific message.	1	1	Class 3 Default meaning: TE-specific (see 3GPP TS 27.005)	Bit 3	Bit 2	Character set:	0	0	GSM 7 bit default alphabet	0	1	8 bit data	1	0	UCS2 (16 bit)	1	1	Reserved
Bit 1	Bit 0	Message Class:																													
0	0	Class 0																													
0	1	Class 1 Default meaning: ME-specific.																													
1	0	Class 2 (U)SIM specific message.																													
1	1	Class 3 Default meaning: TE-specific (see 3GPP TS 27.005)																													
Bit 3	Bit 2	Character set:																													
0	0	GSM 7 bit default alphabet																													
0	1	8 bit data																													
1	0	UCS2 (16 bit)																													
1	1	Reserved																													
1000	Reserved coding groups																														

Table 1E

Coding Group Bits 7..4	Use of bits 3..0																														
1001	Message with User Data Header (UDH) structure: <table><tr><td>Bit 1</td><td>Bit 0</td><td>Message Class:</td></tr><tr><td>0</td><td>0</td><td>Class 0</td></tr><tr><td>0</td><td>1</td><td>Class 1 Default meaning: ME-specific.</td></tr><tr><td>1</td><td>0</td><td>Class 2 (U)SIM specific message.</td></tr><tr><td>1</td><td>1</td><td>Class 3 Default meaning: TE-specific (see 3GPP TS 27.005)</td></tr></table> Bits 3 and 2 indicate the alphabet being used, as follows: <table><tr><td>Bit 3</td><td>Bit 2</td><td>Alphabet:</td></tr><tr><td>0</td><td>0</td><td>GSM 7 bit default alphabet</td></tr><tr><td>0</td><td>1</td><td>8 bit data</td></tr><tr><td>1</td><td>0</td><td>USC2 (16 bit)</td></tr><tr><td>1</td><td>1</td><td>Reserved</td></tr></table>	Bit 1	Bit 0	Message Class:	0	0	Class 0	0	1	Class 1 Default meaning: ME-specific.	1	0	Class 2 (U)SIM specific message.	1	1	Class 3 Default meaning: TE-specific (see 3GPP TS 27.005)	Bit 3	Bit 2	Alphabet:	0	0	GSM 7 bit default alphabet	0	1	8 bit data	1	0	USC2 (16 bit)	1	1	Reserved
Bit 1	Bit 0	Message Class:																													
0	0	Class 0																													
0	1	Class 1 Default meaning: ME-specific.																													
1	0	Class 2 (U)SIM specific message.																													
1	1	Class 3 Default meaning: TE-specific (see 3GPP TS 27.005)																													
Bit 3	Bit 2	Alphabet:																													
0	0	GSM 7 bit default alphabet																													
0	1	8 bit data																													
1	0	USC2 (16 bit)																													
1	1	Reserved																													
1010..1100	Reserved coding groups																														
1101	Defined for IMS Centralized Services																														
	<table><tr><td>Bit 1</td><td>Bit 0</td><td>Message Class:</td></tr><tr><td>0</td><td>0</td><td>Reserved</td></tr><tr><td>0</td><td>1</td><td>Class 1 Default meaning: ME-specific.</td></tr><tr><td>1</td><td>0</td><td>Reserved</td></tr><tr><td>1</td><td>1</td><td>Reserved</td></tr></table> Bits 3 and 2 indicate the alphabet being used, as follows: <table><tr><td>Bit 3</td><td>Bit 2</td><td>Alphabet:</td></tr><tr><td>0</td><td>0</td><td>Reserved</td></tr><tr><td>0</td><td>1</td><td>8 bit data</td></tr><tr><td>1</td><td>0</td><td>Reserved</td></tr><tr><td>1</td><td>1</td><td>Reserved</td></tr></table>	Bit 1	Bit 0	Message Class:	0	0	Reserved	0	1	Class 1 Default meaning: ME-specific.	1	0	Reserved	1	1	Reserved	Bit 3	Bit 2	Alphabet:	0	0	Reserved	0	1	8 bit data	1	0	Reserved	1	1	Reserved
Bit 1	Bit 0	Message Class:																													
0	0	Reserved																													
0	1	Class 1 Default meaning: ME-specific.																													
1	0	Reserved																													
1	1	Reserved																													
Bit 3	Bit 2	Alphabet:																													
0	0	Reserved																													
0	1	8 bit data																													
1	0	Reserved																													
1	1	Reserved																													

Table 1F

Coding Group Bits 7..4	Use of bits 3..0
1110	Defined by the WAP Forum
1111	Data coding / message handling Bit 3 is reserved, set to 0. Bit 2 Message coding: 0 GSM 7 bit default alphabet 1 8 bit data Bit 1 Bit 0 Message Class: 0 0 No message class. 0 1 Class 1 user defined. 1 0 Class 2 user defined. 1 1 Class 3 default meaning: TE specific (see 3GPP TS 27.005)

The foregoing codings may also be used for USSD and Man-Machine Interface (MMI)/display purposes. In an exemplary implementation, specific coding values applicable to USSD for Mobile-Originated USSD messages and Mobile-Terminated USSD messages may be provided in accordance with 3GPP TS 24.090 documentation. In such an implementation, USSD messages using the default alphabet may be coded with the GSM 7-bit default alphabet provided in Clause 6.2.1 of the documentation, wherein the messages may then include up to 182 user characters, by way of an example.

Applicable IMS CS Control Protocol (ICCP) contents may be included in a suitable alternative signaling message application such as USSD or SMS messages, possibly with appropriate encoding and compression for efficient data transfer. In one embodiment, the user-user protocol contents may be structured like the non-imperative part of a standard Layer-3 (L3) message and may comprise a variable number of information elements (IEs) of type 1, 2, 3, and 4. Different formats, e.g., Tag-Value (TV) and Tag-Length-Value (TLV) formats (sometimes also referred to as Type-Variable or Type-Length-Variable formats, respectively), etc., and the categories of IEs, e.g., types 1, 2, 3, and 4, may be provided in accordance with 3GPP TS 24.007 documentation. Within the ICCP contents, the IEs may occur in an arbitrary order, and may only be included once, wherein each IE may comprise one or more octets. FIG. 10 depicts an exemplary structure 1000 for transporting ICS protocol information according to one embodiment, wherein a plurality of IEs 1000-1

through 1000-K are provided. In the exemplary embodiment, each IE is shown to comprise a number of octets, e.g., two octets, although other arrangements are also possible. Further, the data structure 1000 may be designed so as to accommodate any number of USSD/SMS messages that may be concatenated or otherwise manipulated.

5 In certain embodiments, ICS requests can span multiple USSD/SMS requests/messages in a single transaction. FIG. 11A depicts an exemplary data structure 1100 for transporting user data information according to one embodiment. A plurality of User Data Items (UDIs), e.g., UDI 1102, may be provided with respect to the user data. The total number of UDIs may be preconfigured, e.g., 128 UDIs. If the most significant bit is set
10 in the UDI, the UDI uses a consecutive eight bits (i.e., an octet). Otherwise, the UDI uses consecutive four bits (half an octet). The remaining three or seven bits are encoded in a big-endian order, e.g., with the most significant bit (MSB) first. For example, the integer value 0x0A would be encoded with one octet [0x8A]. The integer value 0x06 would be encoded in four consecutive bits: [0x06]. Each UDI may comprise a number of unique Information
15 Element Identifiers (IEIs) 1104-a through 1104-n. For example, UDI 1102 may include up to 256 IEIs. Depending on the IEI, an Information Element Data Length (IEDL) and/or an Information Element Data (IED) may be provided for each IEI. As exemplified in FIG. 11A, IEIa 1104-a includes IEDLa 1106-a that indicates the length of the actual user data in octets, e.g., IEDa 1108-a. Likewise, IEIn 1104-n is exemplified with IDELn 1106-n with
20 respect to IEDn 1108-n. The data type of the IEDL variable can be an 8-bit, unsigned integer (u_int8) or a 32-bit unsigned integer, encoded in multi-byte integer format (mb_u_int32). A multi-byte integer may comprise a series of octets where the most significant bit is the continuation flag and the remaining seven bits are a scalar value. The continuation flag is operable to indicate that an octet is not the end of the multi-byte
25 sequence. A single integer value may be encoded into a sequence of N octets. The first N-1 octets have a continuation flag that may be set to a particular binary value, e.g., binary 1. Likewise, the final octet in the series may be provided with a continuation flag that has a binary value of 0. The remaining seven bits in each octet may be encoded in a big-endian order, i.e., with the MSB first. The octets may also be arranged in a big-endian order, e.g.,
30 the most significant seven bits are transmitted first. In the situation where the initial octet has fewer than seven bits of value, all unused bits may be set to zero. By way of example, the integer value 0xA0 may be encoded with the two-byte sequence [0x81]:[0x20]. The

integer value 0x60 may be encoded with the one-byte sequence [0x60]. The type of the IED may be indicated by the corresponding IEI.

FIG. 11B depicts an embodiment of a message generation scheme 1150 that includes generating the data structures of FIG. 11A for transporting user data information, for example, between a UE device and an IMS-centric network node over a CS network, with respect to IMS message signaling. As set forth in this patent application, the IMS message signaling may pertain to delivering an MT call, although other IMS services may also use the message generation scheme. Accordingly, the scheme 1150 may be embodied as a method, system or a computer-accessible medium operable with respect to the user data information at a UE device or the network node. Furthermore, the UE device and the network node may be considered as a pair of entities, e.g., a first entity and a second entity, or vice versa, for purposes of generating and transmitting the messages from one entity to the other. In general, a number of UDIs may be configured or pre-configured at a first entity based on the amount of the user data information, wherein each UDI is operable to contain a plurality of IEIs (block 1152). For a select IEI, an IEDL structure is provided that is operable to indicate a length of data associated with the select IEI, wherein the data comprises at least a portion of the user data information (block 1154). As alluded to previously, depending on the IEI type, there may be some IEIs for which an IEDL is not necessary. One or more alternative signaling (AS) messages are generated for transmission to the other entity, i.e., the second entity, which could be the UE device or the network node, wherein the AS messages include one or more of the UDIs (block 1156). In relation to the ICS-NF node of 206 illustrated in FIG. 4, the foregoing scheme may be embodied or otherwise executed based on functionalities such as processor 402, ICS message application 418, message encode/decode block 408, dictionary 412, storage 420, among others.

A list of defined IEIs in the context of managing an MT-call, i.e., response and request encoding codes, may be provided as set forth in Tables 2A through 2K below, wherein a tabular structure can be thought of as being further separated in request/response IEIs and associated IEIs.

Table 2A

IEI	Value	IEDL present	IED encoding
MT call setup	0x01	No	N.A.
Tel URI	0x02	No	See Tables 3A-3D Below
SIP(S) URI	0x03	Yes	See 3GPP TS 23.042
A party withheld	0x04	No	N.A.
100 (Trying)	N.A.	N.A.	N.A.
1xx response	0x05	Yes	See 3GPP TS 23.042
180 (Ringing)	N.A.	N.A.	N.A.
181 (Call Is Being Forwarded)	N.A.	N.A.	N.A.
182 (Queued)	0x06	Yes	See 3GPP TS 23.042
183 (Session Progress)	0x07	Yes	See 3GPP TS 23.042
2xx response	0x08	Yes	See 3GPP TS 23.042
200 (OK)	0x09	No	N.A.
202 (Accepted)	0x0a	No	N.A.
3xx response	0x0b	No	N.A.

Table 2B

5

IEI	Value	IEDL present	IED encoding
300 (Multiple Choices)	0x0c	No	N.A.
301 (Moved Permanently)	0x0d	No	N.A.
302 (Moved Temporarily)	0x0e	No	N.A.
305 (Use Proxy)	N.A.	N.A.	N.A.
380 (Alternative Service)	0x0f	No	N.A.
4xx response	0x10	Yes	See 3GPP TS 23.042
400 (Bad Request)	0x11	No	N.A.
401 (Unauthorized)	N.A.	N.A.	N.A.
402 (Payment Required)	N.A.	N.A.	N.A.
403 (Forbidden)	N.A.	N.A.	N.A.
404 (Not Found)	N.A.	N.A.	N.A.
405 (Method Not Allowed)	0x12	Yes	See 3GPP TS 23.042
406 (Not Acceptable)	N.A.	N.A.	N.A.

Table 2C

IEI	Value	IEDL present	IED encoding
407 (Proxy Authentication Required)	N.A.	N.A.	N.A.
408 (Request Timeout)	N.A.	N.A.	N.A.
410 (Gone)	N.A.	N.A.	N.A.
412 (Conditional Request Failed)	N.A.	N.A.	N.A.
413 (Request Entity Too Large)	0x13	No	N.A.
414 (Request-URI Too Large)	0x14	No	N.A.
415 (Unsupported Media Type)	N.A.	N.A.	N.A.
416 (Unsupported URI Scheme)	0x15	No	N.A.
420 (Bad Extension)	0x16	No	N.A.
421 (Extension Required)	0x17	No	N.A.
422 (Session Interval Too Small)	0x18	No	N.A.
423 (Interval Too Brief)	0x19	No	N.A.

Table 2D

5

IEI	Value	IEDL present	IED encoding
424 (Bad Location Information)	N.A.	N.A.	N.A.
429 (Provide Referrer Identity)	N.A.	N.A.	N.A.
430 (Flow Failed)	N.A.	N.A.	N.A.
433 (Anonymity Disallowed)	0x1a	No	N.A.
480 (Temporarily Unavailable)	0x1b	No	N.A.
481 (Call/Transaction Does Not Exist)	0x1c	No	N.A.
482 (Loop Detected)	N.A.	N.A.	N.A.
483 (Too Many Hops)	N.A.	N.A.	N.A.
484 (Address Incomplete)	N.A.	N.A.	N.A.
485 (Ambiguous)	N.A.	N.A.	N.A.
486 (Busy Here)	0x1d	No	N.A.

Table 2E

IEI	Value	IEDL present	IED encoding
487 (Request Terminated)	N.A.	N.A.	N.A.
488 (Not Acceptable Here)	N.A.	N.A.	N.A.
489 (Bad Event)	0x1f	No	N.A.
491 (Request Pending)	N.A.	N.A.	N.A.
493 (Undecipherable)	0x1f	No	N.A.
494 (Security Agreement Required)	N.A.	N.A.	N.A.
5xx response	0x20	Yes	See 3GPP TS 23.042
500 (Internal Server Error)	N.A.	N.A.	N.A.
501 (Not Implemented)	N.A.	N.A.	N.A.
502 (Bad Gateway)	N.A.	N.A.	N.A.
503 (Service Unavailable)	N.A.	N.A.	N.A.
504 (Server Time-out)	N.A.	N.A.	N.A.
505 (Version not supported)	N.A.	N.A.	N.A.

Table 2F

5

IEI	Value	IEDL present	IED encoding
513 (Message Too Large)	0x21	No	N.A.
580 (Precondition Failure)	N.A.	N.A.	N.A.
6xx response	0x20	Yes	See 3GPP TS 23.042
600 (Busy Everywhere)	0x21	No	N.A.
603 (Decline)	0x22	No	N.A.
604 (Does Not Exist Anywhere)	N.A.	N.A.	N.A.
606 (Not Acceptable)	N.A.	N.A.	N.A.
Accept	N.A.	N.A.	N.A.
Accept-Contact	N.A.	N.A.	N.A.
Accept-Encoding	N.A.	N.A.	N.A.
Accept-Language	0x23	Yes	See 3GPP TS 23.042
Alert-Info	0x24	Yes	See 3GPP TS 23.042

Table 2G

IEI	Value	IEDL present	IED encoding
Allow	0x25	Yes	See 3GPP TS 23.042
Allow-Events	0x26	Yes	See 3GPP TS 23.042
Authorization	N.A.	N.A.	N.A.
Call-ID	0x27	Yes	See 3GPP TS 23.042
Call-Info	0x28	Yes	See 3GPP TS 23.042
Contact	0x29	Yes	See 3GPP TS 23.042
Content-Disposition	0x2a	Yes	See 3GPP TS 23.042
Content-Encoding	0x2b	Yes	See 3GPP TS 23.042
Content-Language	0x2c	Yes	See 3GPP TS 23.042
Content-Length	N.A.	N.A.	N.A.
Content-Type	0x2d	Yes	See 3GPP TS 23.042
Cseq	0x2e	Yes	See 3GPP TS 23.042
Date	0x2f	Yes	See 3GPP TS 23.042

Table 2H

5

IEI	Value	IEDL present	IED encoding
Expires	0x30	Yes	See 3GPP TS 23.042
From	0x31	Yes	See 3GPP TS 23.042
Geolocation	0x32	Yes	See 3GPP TS 23.042
History-Info	0x33	Yes	See 3GPP TS 23.042
In-Reply-To	0x34	Yes	See 3GPP TS 23.042
Join	0x35	Yes	See 3GPP TS 23.042
Max-Forwards	N.A.	N.A.	N.A.
MIME-Version	N.A.	N.A.	N.A.
Min-SE	N.A.	N.A.	N.A.
Organization	0x36	Yes	See 3GPP TS 23.042
P-Access-Network-Info	N.A.	N.A.	N.A.
P-Asserted-Identity	N.A.	N.A.	N.A.

Table 2I

IEI	Value	IEDL present	IED encoding
P-Called-Party-ID	N.A.	N.A.	N.A.
P-Charging-Function-Addresses	N.A.	N.A.	N.A.
P-Charging-Vector	N.A.	N.A.	N.A.
P-Media-Authorization	N.A.	N.A.	N.A.
P-Preferred-Identity	N.A.	N.A.	N.A.
P-Profile-Key	N.A.	N.A.	N.A.
P-User-Database	N.A.	N.A.	N.A.
P-Visited-Network-ID	N.A.	N.A.	N.A.
Priority	0x37	Yes	See 3GPP TS 23.042
Privacy	0x38	Yes	See 3GPP TS 23.042
Proxy-Authorization	N.A.	N.A.	N.A.
Proxy-Require	N.A.	N.A.	N.A.
Reason	0x39	Yes	See 3GPP TS 23.042
Record-Route	N.A.	N.A.	N.A.
Referred-By	0x40	Yes	See 3GPP TS 23.042

Table 2J

5

IEI	Value	IEDL present	IED encoding
Reject-Contact	0x41	Yes	See 3GPP TS 23.042
Replaces	0x42	Yes	See 3GPP TS 23.042
Reply-To	0x43	Yes	See 3GPP TS 23.042
Request-Disposition	N.A.	N.A.	N.A.
Require	N.A.	N.A.	N.A.
Route	N.A.	N.A.	N.A.
Security-Client	N.A.	N.A.	N.A.
Security-Verify	N.A.	N.A.	N.A.
Session-Expires	N.A.	N.A.	N.A.
Subject	0x44	Yes	See 3GPP TS 23.042
Supported	0x45	Yes	See 3GPP TS 23.042
Timestamp	0x46	Yes	See 3GPP TS 23.042
To	0x47	Yes	See 3GPP TS 23.042

Table 2K

IEI	Value	IEDL present	IED encoding
User-Agent	N.A.	N.A.	N.A.
Via	N.A.	N.A.	N.A.
Server	0x48	Yes	See 3GPP TS 23.042
Warning	N.A.	N.A.	N.A.
Rseq	0x49	no	mb_u_int32
Authentication-Info	N.A.	N.A.	N.A.
Error-Info	0x4a	Yes	See 3GPP TS 23.042
Proxy-Authenticate	N.A.	N.A.	N.A.
WWW-Authenticate	N.A.	N.A.	N.A.
Retry-After	0x4b	Yes	See 3GPP TS 23.042
Unsupported	0x4c	Yes	See 3GPP TS 23.042
Security-Server	N.A.	N.A.	N.A.
Reason-Phrase	0x4d	Yes	See 3GPP TS 23.042

Those skilled in the art will recognize that some IEIs may be followed by other IEIs, which can be either permissive or mandatory (e.g., IEI “182 (Queued)” may be followed by IEI “Reason-Phrase”). Accordingly, as alluded to previously, an appropriate encoder/decoder mechanism may be provided at the transmitter and recipient entities, which can be either a serving ICS node or a served ICS UE device. In conjunction, a suitable parser may also be provided at either or both entities. In one implementation, the functionality of a parser involves sequentially reading the USSD/SMS payload as set forth below:

- I. Read a request/response IEI.
- II. Find its associated IEIs if there are more UDIs. If there are no more UDIs, the parser may exit and any unexpected IEIs may be ignored. Applicable procedures of 3GPP TS 24.229 documentation may be used in conjunction with the Tables set forth above for possible headers encoded as associated IEIs.
- III. Upon reading another response/request IEI, the parser may operate iteratively to proceed to Step (II) above.

By way of example, the coding of a Tel URI as an E.164 number may be provided in a variety of implementations, as set forth in the Tables 3A through 3D below.

Table 3A

8	7	6	5	4	3	2	1	
E.164 Information Element – X Party ID								octet 1
Length of called party BCD number contents								octet 2
1 ext	type of number			Numbering plan identification				octet 2
Number digit 2				Number digit 1				octet 3*
Number digit 4				Number digit 3				octet 4*
etc.								:
								:

5

Table 3B

Type of number (octet 3)	
Bits	
7 6 5	
0 0 0	unknown
0 0 1	international number
0 1 0	national number
0 1 1	network specific number
1 0 0	dedicated access, short code
1 0 1	reserved
1 1 0	reserved
1 1 1	reserved for extension

Table 3C

Numbering plan identification (octet 3)	
Number plan (applies for type of number = 000, 001, 010 and 100)	
Bits	
4 3 2 1	
0 0 0 0	unknown
0 0 0 1	ISDN/telephony numbering plan (Rec. E.164/E.163)
0 0 1 1	data numbering plan (Recommendation X.121)
0 1 0 0	telex numbering plan (Recommendation F.69)
1 0 0 0	national numbering plan
1 0 0 1	private numbering plan
1 1 1 1	reserved for extension
All other values are reserved.	

10

Table 3D

Number digits (octets 4, etc.)	
Bits	Number digit value
4 3 2 1 or 8 7 6 5	
0 0 0 0	0
0 0 0 1	1
0 0 1 0	2
0 0 1 1	3
0 1 0 0	4
0 1 0 1	5
0 1 1 0	6
0 1 1 1	7
1 0 0 0	8
1 0 0 1	9
1 0 1 0	*
1 0 1 1	#
1 1 0 0	a
1 1 0 1	b
1 1 1 0	c
1 1 1 1	used as an endmark in the case of an odd number of number digits

By way of further example, the coding of a SIP URI and the payload (e.g., USSD or SMS) may be provided as follows. In one embodiment, the SIP URI or the payload may be compressed using one or more standard compression algorithms in accordance with 3GPP TS 23.042 documentation. For optimal and efficient transmission and/or compression, compatible dictionaries may be provided at the both ends, as alluded to previously. A dictionary may be embodied as a list of key words or phrases of up to certain length (e.g., 255 characters) that are known to both the coder and decoder. The input stream may be matched against entries provided in the dictionary and matching characters in the stream may be replaced with a reference to the dictionary entry. Operationally, such dictionaries may be provisioned by a network operator and may include matches for frequently occurring strings (or strings that occur a certain number of times) such as, e.g., "sip:", "sips:" and the domain fragment of a URI, as well as other frequently occurring strings or string fragments.

FIG. 12 depicts a block diagram of an embodiment of a communications device operable as an ICS UE device, e.g., UE 202, for purposes of the present patent disclosure. It will be recognized by those skilled in the art upon reference hereto that although an

embodiment of UE 202 may comprise an arrangement similar to one shown in FIG. 12, there can be a number of variations and modifications, in hardware, software or firmware, with respect to the various modules depicted. Accordingly, the arrangement of FIG. 12 should be taken as illustrative rather than limiting with respect to the embodiments of the present patent disclosure. A microprocessor 1202 providing for the overall control of an embodiment of UE 202 is operably coupled to a communication subsystem 1204 that may be capable of multi-mode communications (e.g., CS domain, IP domain such as IMS, et cetera). The communication subsystem 1204 generally includes one or more receivers 1208 and one or more transmitters 1214 as well as associated components such as one or more local oscillator (LO) modules 1210 and a processing module such as a digital signal processor (DSP) 1212. As will be apparent to those skilled in the field of communications, the particular design of the communication module 1204 may be dependent upon the communications networks with which the mobile device is intended to operate (e.g., a CDMA network, a GSM network, WLAN, et cetera). Regardless of the particular design, however, signals received by antenna 1206 through appropriate access infrastructure 1205 (e.g., cellular base station towers, WLAN hot spots, etc.) are provided to receiver 1208, which may perform such common receiver functions as signal amplification, frequency down conversion, filtering, channel selection, analog-to-digital (A/D) conversion, and the like. Similarly, signals to be transmitted are processed, including modulation and encoding, for example, by DSP 1212, and provided to transmitter 1214 for digital-to-analog (D/A) conversion, frequency up conversion, filtering, amplification and transmission over the air-radio interface via antenna 1216.

Microprocessor 1202 may also interface with further device subsystems such as auxiliary input/output (I/O) 1218, serial port 1220, display 1222, keyboard/keypad 1224, speaker 1226, microphone 1228, random access memory (RAM) 1230, a short-range communications subsystem 1232, and any other device subsystems, e.g., timer mechanisms, generally labeled as reference numeral 1233. To control access, an interface 1234 may also be provided in communication with the microprocessor 1202 with respect to a removable storage module (Universal/Subscriber Identity Module (U/SIM) or Removable User Identity Module (RUIM)). In one implementation, U/SIM or RUIM interface 1234 may be operable with a U/SIM or RUIM card having a number of key configurations 1244 and other information 1246 such as R-URIs as well as identification and subscriber-related data.

Operating system software and applicable service logic software may be embodied in a persistent storage module (i.e., non-volatile storage) such as Flash memory 1235. In one implementation, Flash memory 1235 may be segregated into different areas, e.g., storage area for computer programs 1236 (e.g., service processing logic), as well as data storage regions such as device state 1237, address book 1239, other personal information manager (PIM) data 1241, and other data storage areas generally labeled as reference numeral 1243. A transport stack 1245 may be provided to effectuate one or more appropriate radio-packet transport protocols. In addition, an ICS service logic module 1248 is provided for effectuating reception/generation of ICCP-based alternative signaling (i.e., USSD/SMS) as well as mechanisms to effectuate MO call procedures based on received IMRNs from an ICS network node, etc., as set forth hereinabove.

It should be appreciated that the various operations, components and processes set forth in the present patent disclosure, operable either at the ICS UE device, the ICS network node, or at other network locations, may be accomplished via a number of means, including software (e.g., program code or sequence of instructions), firmware, hardware, or in any combination, usually in association with a processing system. Where the processes are embodied in software, such software may comprise program instructions that form a computer program product, instructions on computer-accessible media, uploadable service application software, or software downloadable from a remote station, and the like. Further, where the processes, data structures, or both, are stored in computer-accessible storage, such storage may include semiconductor memory, internal and external computer storage media and encompasses, but not limited to, nonvolatile media, volatile media, and transmission media. Nonvolatile media may include CD-ROMs, magnetic tapes, PROMs, Flash memory, or optical media. Volatile media may include dynamic memory, caches, RAMs, etc. Transmission media may include carrier waves or other signal-bearing media. As used herein, the phrase "computer-accessible medium" encompasses "computer-readable medium" as well as "computer-executable medium."

It is believed that the operation and construction of the embodiments of the present patent application will be apparent from the Detailed Description set forth above. While the exemplary embodiments shown and described may have been characterized as being preferred, it should be readily understood that various changes and modifications could be made therein without departing from the scope of the present disclosure as set forth in the following claims.

WHAT IS CLAIMED IS:

- 1 1. A User Equipment (UE) device operable in connection with an Internet Protocol (IP)
2 Multimedia Subsystem (IMS) network, comprising:
3 a component configured to receive an alternative signaling (AS) message via a
4 Circuit-Switched (CS) network domain;
5 a component configured to determine that said AS message is for delivery of a
6 Mobile-Terminated (MT) call to be terminated at said UE device;
7 a component configured to store call information received in said AS message, said
8 call information comprising at least an IMS Multimedia Routing Number (IMRN); and
9 a component configured to initiate a Mobile-Originated (MO) call process towards a
10 network node with said IMRN as a destination number, wherein said MO call process is
11 operable to effectuate an access leg with said network node with respect to said MT call.
- 1 2. The UE device operable in connection with an IMS network as recited in
2 claim 1, wherein said AS message comprises at least one of at least one Unstructured
3 Supplementary Service Data (USSD) message and at least one Short Messaging Service
4 (SMS) message.
- 1 3. The UE device operable in connection with an IMS network as recited in
2 claim 1, further comprising a component configured to decode said call information encoded
3 in said AS message.
- 1 4. The UE device operable in connection with an IMS network as recited in
2 claim 34, wherein said component configured to decode said call information comprises a
3 dictionary mechanism.
- 1 5. The UE device operable in connection with an IMS network as recited in
2 claim 4, wherein said dictionary mechanism comprises a component configured to match a
3 character string that occurs a predetermined number of times.
- 1 6. The UE device operable in connection with an IMS network as recited in
2 claim 5, wherein said character string comprises at least one of a "sip:" and "sips:".

1 7. The UE device operable in connection with an IMS network as recited in
2 claim 4, wherein said dictionary mechanism comprises a component configured to match a
3 domain fragment of a Uniform Resource Identifier (URI).

1 8. The UE device operable in connection with an IMS network as recited in
2 claim 1, further comprising an application timer mechanism for timing said MO call process.

1 9. The UE device operable in connection with an IMS network as recited in
2 claim 1, wherein said call information comprises information relating to at least one of an A-
3 Party ID and a B-Party ID with respect to said MT call.

1 10. The UE device operable in connection with an IMS network as recited in
2 claim 910, wherein at least one of said A-Party ID and said B-Party ID is encoded as at least
3 one of a SIP URI, a Tel URI, and an E.164 number.

1 11. The UE device operable in connection with an IMS network as recited in
2 claim 1, further comprising a component configured to parse data provided in said AS
3 message.

1 12. The UE device operable in connection with an IMS network as recited in
2 claim 1, wherein said IMRN comprises an E.164 number.

1 13. The UE device operable in connection with an IMS network as recited in
2 claim 1, further comprising a component configured to determine that said AS message is
3 for an IMS Centralized Services (ICS) application.

1 14. A call connection method for a User Equipment (UE) device, comprising:
2 receiving an alternative signaling (AS) message via a Circuit-Switched (CS) network
3 domain disposed in connection with an Internet Protocol (IP) Multimedia Subsystem (IMS)
4 network;
5 determining that said AS message is for delivery of a Mobile-Terminated (MT) call
6 to be terminated at said UE device;
7 storing call information received in said AS message, said call information
8 comprising at least an IMS Multimedia Routing Number (IMRN); and
9 initiating a Mobile-Originated (MO) call process towards a network node with said
10 IMRN as a destination number, wherein said MO call process is operable to effectuate an
11 access leg with said network node with respect to said MT call.

1 15. The call connection method as recited in claim 14, wherein said AS message
2 comprises at least one of at least one Unstructured Supplementary Service Data (USSD)
3 message and at least one Short Messaging Service (SMS) message.

1 16. The call connection method as recited in claim 14, further comprising
2 decoding said call information encoded in said AS message.

1 17. The call connection method as recited in claim 16, wherein said decoding
2 comprises applying a dictionary mechanism.

1 18. The call connection method as recited in claim 17, wherein said dictionary
2 mechanism comprises matching a character string that occurs a predetermined number of
3 times.

1 19. The call connection method as recited in claim 18, wherein said character
2 string comprises at least one of a "sip:" and "sips:".

1 20. The call connection method as recited in claim 17, wherein said dictionary
2 mechanism comprises matching a domain fragment of a Uniform Resource Identifier (URI).

1 21. The call connection method as recited in claim 141, further comprising
2 initiating an application timer mechanism for timing said MO call process.

1 22. The call connection method as recited in claim 14, wherein said call
2 information comprises information relating to at least one of an A-Party ID and a B-Party ID
3 with respect to said MT call.

1 23. The call connection method as recited in claim 1426, wherein at least one of
2 said A-Party ID and said B-Party ID is encoded as at least one of a SIP URI, a Tel URI, and
3 an E.164 number.

1 24. The call connection method as recited in claim 14, further comprising parsing
2 data provided in said AS message.

1 25. The call connection method as recited in claim 14, wherein said IMRN
2 comprises an E.164 number.

1 26. The call connection method as recited in claim 14, further comprising
2 determining that said AS message is for an IMS Centralized Services (ICS) application.

1 27. A computer-accessible medium having a sequence of instructions which,
2 when executed by a processing entity of a User Equipment (UE) device, effectuate a call
3 connection process with a network node, said medium comprising:
4 instructions for determining that an alternative signaling (AS) message received via a
5 Circuit-Switched (CS) network domain is for delivery of a Mobile-Terminated (MT) call to
6 be terminated at said UE device through an Internet Protocol (IP) Multimedia Subsystem
7 (IMS) network;
8 instructions for storing call information received in said AS message, said call
9 information comprising at least an IMS Multimedia Routing Number (IMRN); and
10 instructions for initiating a Mobile-Originated (MO) call process towards said
11 network node with said IMRN as a destination number, wherein said MO call process is
12 operable to effectuate an access leg with said network node with respect to said MT call.