Claims:

1. A conveyor dishwasher (1), in particular commercial conveyor dishwasher, having:

at least one wash zone (10, 11.1, 11.2, 11.3);

at least one final rinse zone (13.1) which is arranged downstream of the at least one wash zone (10, 11.1, 11.2, 11.3), and having a conveyor apparatus (2) for conveying washware through the at least one wash zone (10, 11.1, 11.2, 11. 3) and the at least one final rinse zone (13.1), with the final rinse liquid which is sprayed onto the washware to be treated in the at least one final rinse zone (13.1) having a metered disinfection chemical; and

at least one additional final rinse zone (13.2) which is arranged downstream of the at least one final rinse zone (13.1) as seen in the conveying direction (T) being provided for only ever spraying fresh water onto the washware to be treated;

wherein the at least one additional final rinse zone (13.2) has an associated collection device (22.2) for collecting liquid which is sprayed in the at least one additional final rinse zone (13.2); and in that a liquid transfer system is provided, it being possible to supply the liquid which is collected in the collection device (22.2) directly to the at least one wash zone (10, 11.1, 11.2, 11.3) by means of said liquid transfer system, or it being possible to supply the liquid which is collected in the collection device (22.2) directly to a wastewater outlet of the conveyor dishwasher (1) by means of said liquid transfer system and wherein the washing and/or rinsing temperatures in the conveyor dishwasher (1) are below 60°C, and preferably below 55°C.

2. The conveyor dishwasher (1) as claimed in claim 1, with the liquid transfer system having a bypass line (6) which is or can be connected at one end to the collection device (22.2) which is associated with the at least one additional final rinse zone (13.2) and at the other end to the at least one wash zone (10, 11.1, 11.2, 11.3), and in particular to a wash tank (20, 21.1, 21.2, 21.3) which is associated with the at least one wash zone (10, 11.1, 11.2, 11.3);

with the liquid transfer system having at least one pump (38a) with which the liquid which is collected in the collection device (22.2) which is associated with the at least one additional final rinse zone (13.2) can be supplied to the at least one wash

zone (10, 11.1, 11.2, 11.3), and in particular to the wash tank (20, 21.1, 21;2, 21.3) which is associated with the at least one wash zone (10, 11.1, 11.2, 11.3), via the bypass line (6);

it being possible to actuate the at least one pump (38a) by means of a control device (50) in such a way that the liquid which is collected in the collection device (22.2) which is associated with the at least one additional final rinse zone (13.2) is supplied continuously or at pre-specified or pre-specifiable times or events to the at least one wash zone (10, 11.1, 11.2, 11.3), and in particular to the wash tank (20, 21.1, 21.2, 21.3) which is associated with the at least one wash zone (10, 11. 1, 11. 2, 11. 3), via the bypass line (6).

3. The conveyor dishwasher as claimed in any one of the preceding claims, with the liquid transfer system having an outlet line (35) which is or can be connected at one end to the collection device (22.2) which is associated with the at least one additional final rinse zone (13.2) and at the other end to a wastewater outlet of the conveyor dishwasher (1).

4. The conveyor dishwasher (1) as claimed in claim 3, it being possible for the outlet line (35) to be connected to the wastewater outlet of the conveyor dishwasher (1) via a valve, it being possible for the valve to be actuated by means of a control device (50) in such a way that the liquid which is collected in the collection device (22.2) which is associated with the at least one additional final rinse zone (13.2) is supplied continuously or at pre-specified or pre-specifiable times or events to the wastewater outlet of the conveyor dishwasher (1) via the outlet line (35)

5. The conveyor dishwasher (1) as claimed in any one of the preceding claims, with the at least one final rinse zone (13.1) having an associated collection device (22.1), which is formed separately from the collection device (22.2) which is associated with the at least one additional final rinse zone (13.2), for collecting the liquid which is sprayed in the at least one final rinse zone (13.1), and with the at least one pre-rinse zone (12) being provided, upstream of the at least one final rinse zone (13.1) and downstream of the at least one wash zone (10, 11.1, 11.2, 11.3) as seen in the conveying direction (T), for spraying the liquid which is collected in the collection device (22.1) which is associated with the at least one final rinse zone

(13.1) onto the washware to be treated.

6. The conveyor dishwasher (1) as claimed in any one of claims 1 to 4, with a metering device being provided for metering a disinfection chemical into the liquid which is to be sprayed in the at least one final rinse zone (13.1) in such a way that the liquid contains a predefinable or predefined minimum concentration of disinfection chemicals which depends on the type of metered disinfection chemical.

7. The conveyor dishwasher (1) as claimed in claim 5, with a metering device also being provided for metering a disinfection chemical into the liquid which is sprayed in the at least one final rinse zone and which is to be sprayed in the at least one pre-rinse zone (12) and/or for metering a disinfection chemical into the liquid which is to be sprayed in the at least one final rinse zone (13.1) in such a way that the liquid which is sprayed in the at least one final rinse zone (13.1) and the liquid which is sprayed in the at least one pre-rinse zone (12) have a pre-definable or predefined minimum concentration of disinfection chemicals which depends on the type of metered disinfection chemical.

8. The conveyor dishwasher (1) as claimed in claim 6 or claim 7, with the disinfection chemical containing chlorine dioxide, sodium hypochlorite, ozone, iodine and/or ammonium.

9. The conveyor dishwasher (1) as claimed in any one of the preceding claims, with the liquid which is sprayed in the at least one additional final rinse zone (13.2) being at a temperature which is equal to or greater than the temperature of the liquid which is sprayed in the at least one final rinse zone (13.1).

10. The conveyor dishwasher (1) as claimed in any one of the preceding claims, with the liquid which is sprayed in the at least one additional final rinse zone (13.2) being, in particular demineralized, fresh water.

11. The conveyor dishwasher (1) as claimed in any one of the preceding claims, with a sensor device (51) being provided for detecting the type of washware to be treated in the conveyor dishwasher (1), and with a control device (50) also being

provided, said control device being designed to connect or disconnect the at least one additional final rinse zone (13.1) as a function of the type of washware detected.

12. A method for operating a conveyor dishwasher (1), in particular a commercial conveyor dishwasher, as claimed in any one of the preceding claims, in which method the washware to be cleaned is conveyed through at least one wash zone (10, 11.1, 11.2, 11.3) and at least one final rinse zone (13.1) with the aid of a conveyor apparatus (2), with the at least one final rinse zone (13.1) being arranged downstream of the at least one wash zone (10, 11 . 1, 11.2, 11.3) as seen in the conveying direction (T) of the washware which is conveyed using the conveyor apparatus (2), and with final rinse liquid being sprayed onto the washware to be treated in the at least one final rinse zone (13.1), with a disinfection chemical being added in a metered manner to the final rinse liquid which is sprayed in the at least one final rinse zone (13.1), and with the washware which is treated in the at least one final rinse zone (13.1) then being conveyed through at least one additional final rinse zone (13.2) in which only fresh water is ever sprayed onto the washware, preferably as a function of the type of washware to be treated, wherein the liquid which is spayed in the at least one additional final rinse zone (13.2) is collected by a collection device (22.2) which is associated with the at least one additional final rinse zone (13.2); and the liquid which is collected in the collection device (22 . 2) is supplied directly to the at least one wash zone (10, 11.1, 11. 2, 11. 3) or to a wastewater outlet of the conveyor dishwasher (1) and the washing and/or rinsing temperatures in the conveyor dishwasher (1) are below 60°C, and preferably below 55°C.

Claims:

1. A conveyor dishwasher (1), in particular commercial conveyor dishwasher, having:

at least one wash zone (10, 11.1, 11.2, 11.3);

at least one final rinse zone (13.1) which is arranged downstream of the at least one wash zone (10, 11.1, 11.2, 11.3), and having a conveyor apparatus (2) for conveying washware through the at least one wash zone (10, 11.1, 11.2, 11. 3) and the at least one final rinse zone (13.1), with the final rinse liquid which is sprayed onto the washware to be treated in the at least one final rinse zone (13.1) having a metered disinfection chemical; and

at least one additional final rinse zone (13.2) which is arranged downstream of the at least one final rinse zone (13.1) as seen in the conveying direction (T) being provided for only ever spraying demineralized, fresh water onto the washware to be treated;

wherein the at least one additional final rinse zone (13.2) has an associated collection device (22.2) for collecting liquid which is sprayed in the at least one additional final rinse zone (13.2); and in that a liquid transfer system is provided, it being possible to supply the liquid which is collected in the collection device (22.2) directly to the at least one wash zone (10, 11.1, 11.2, 11.3) by means of said liquid transfer system, or it being possible to supply the liquid which is collected in the collection device (22.2) directly to a wastewater outlet of the conveyor dishwasher (1) by means of said liquid transfer system and wherein the washing and/or rinsing temperatures in the conveyor dishwasher (1) are below 60°C, and preferably below 55°C.

2. The conveyor dishwasher (1) as claimed in claim 1, with the liquid transfer system having a bypass line (6) which is or can be connected at one end to the collection device (22.2) which is associated with the at least one additional final rinse zone (13.2) and at the other end to the at least one wash zone (10, 11.1, 11.2, 11.3), and in particular to a wash tank (20, 21.1, 21.2, 21.3) which is associated with the at least one wash zone (10, 11.1, 11.2, 11.3);

with the liquid transfer system having at least one pump (38a) with which the liquid which is collected in the collection device (22.2) which is associated with the at

least one additional final rinse zone (13.2) can be supplied to the at least one wash zone (10, 11.1, 11.2, 11.3), and in particular to the wash tank (20, 21.1, 21;2, 21.3) which is associated with the at least one wash zone (10, 11.1, 11.2, 11.3), via the bypass line (6);

it being possible to actuate the at least one pump (38a) by means of a control device (50) in such a way that the liquid which is collected in the collection device (22.2) which is associated with the at least one additional final rinse zone (13.2) is supplied continuously or at pre-specified or pre-specifiable times or events to the at least one wash zone (10, 11.1, 11.2, 11.3), and in particular to the wash tank (20, 21.1, 21.2, 21.3) which is associated with the at least one wash zone (10, 11. 1, 11. 2, 11. 3), via the bypass line (6).

3. The conveyor dishwasher as claimed in any one of the preceding claims, with the liquid transfer system having an outlet line (35) which is or can be connected at one end to the collection device (22.2) which is associated with the at least one additional final rinse zone (13.2) and at the other end to a wastewater outlet of the conveyor dishwasher (1).

4. The conveyor dishwasher (1) as claimed in claim 3, it being possible for the outlet line (35) to be connected to the wastewater outlet of the conveyor dishwasher (1) via a valve, it being possible for the valve to be actuated by means of a control device (50) in such a way that the liquid which is collected in the collection device (22.2) which is associated with the at least one additional final rinse zone (13.2) is supplied continuously or at pre-specified or pre-specifiable times or events to the wastewater outlet of the conveyor dishwasher (1) via the outlet line (35)

5. The conveyor dishwasher (1) as claimed in any one of the preceding claims, with the at least one final rinse zone (13.1) having an associated collection device (22.1), which is formed separately from the collection device (22.2) which is associated with the at least one additional final rinse zone (13.2), for collecting the liquid which is sprayed in the at least one final rinse zone (13.1), and with the at least one pre-rinse zone (12) being provided, upstream of the at least one final rinse zone (13.1) and downstream of the at least one wash zone (10, 11.1, 11.2, 11.3) as seen in the conveying direction (T), for spraying the liquid which is collected in the

collection device (22.1) which is associated with the at least one final rinse zone (13.1) onto the washware to be treated.

6. The conveyor dishwasher (1) as claimed in any one of claims 1 to 4, with a metering device being provided for metering a disinfection chemical into the liquid which is to be sprayed in the at least one final rinse zone (13.1) in such a way that the liquid contains a predefinable or predefined minimum concentration of disinfection chemicals which depends on the type of metered disinfection chemical.

7. The conveyor dishwasher (1) as claimed in claim 5, with a metering device also being provided for metering a disinfection chemical into the liquid which is sprayed in the at least one final rinse zone and which is to be sprayed in the at least one pre-rinse zone (12) and/or for metering a disinfection chemical into the liquid which is to be sprayed in the at least one final rinse zone (13.1) in such a way that the liquid which is sprayed in the at least one final rinse zone (13.1) and the liquid which is sprayed in the at least one pre-rinse zone (12) have a pre-definable or predefined minimum concentration of disinfection chemicals which depends on the type of metered disinfection chemical.

8. The conveyor dishwasher (1) as claimed in claim 6 or claim 7, with the disinfection chemical containing chlorine dioxide, sodium hypochlorite, ozone, iodine and/or ammonium.

9. The conveyor dishwasher (1) as claimed in any one of the preceding claims, with the liquid which is sprayed in the at least one additional final rinse zone (13.2) being at a temperature which is equal to or greater than the temperature of the liquid which is sprayed in the at least one final rinse zone (13.1).

10. The conveyor dishwasher (1) as claimed in any one of the preceding claims, with a sensor device (51) being provided for detecting the type of washware to be treated in the conveyor dishwasher (1), and with a control device (50) also being provided, said control device being designed to connect or disconnect the at least one additional final rinse zone (13.1) as a function of the type of washware detected.

11. A method for operating a conveyor dishwasher (1), in particular a commercial conveyor dishwasher, as claimed in any one of the preceding claims, in which method the washware to be cleaned is conveyed through at least one wash zone (10, 11.1, 11.2, 11.3) and at least one final rinse zone (13.1) with the aid of a conveyor apparatus (2), with the at least one final rinse zone (13.1) being arranged downstream of the at least one wash zone (10, 11 . 1, 11.2, 11.3) as seen in the conveying direction (T) of the washware which is conveyed using the conveyor apparatus (2), and with final rinse liquid being sprayed onto the washware to be treated in the at least one final rinse zone (13.1), with a disinfection chemical being added in a metered manner to the final rinse liquid which is sprayed in the at least one final rinse zone (13.1), and with the washware which is treated in the at least one final rinse zone (13.1) then being conveyed through at least one additional final rinse zone (13.2) in which only fresh water is ever sprayed onto the washware, preferably as a function of the type of washware to be treated, wherein the liquid which is spayed in the at least one additional final rinse zone (13.2) is collected by a collection device (22.2) which is associated with the at least one additional final rinse zone (13.2); and the liquid which is collected in the collection device (22 . 2) is supplied directly to the at least one wash zone (10, 11.1, 11. 2, 11. 3) or to a wastewater outlet of the conveyor dishwasher (1) and the washing and/or rinsing temperatures in the conveyor dishwasher (1) are below 60°C, and preferably below 55°C.