

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
15 June 2006 (15.06.2006)

PCT

(10) International Publication Number
WO 2006/062309 A1

(51) International Patent Classification:
E21B 1/30 (2006.01)

(21) International Application Number:
PCT/KR2005/004075

(22) International Filing Date:
1 December 2005 (01.12.2005)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:
10-2004-0102256 7 December 2004 (07.12.2004) KR
10-2005-0029503 8 April 2005 (08.04.2005) KR
10-2005-0111836 22 November 2005 (22.11.2005) KR

(71) Applicant and

(72) Inventor: **LIM, Byung-duk** [KR/KR]; Seoho Apt. 105-1104 Songcheon-dong 1ga, Deokjin-ku, Jeonju-si, Jeollabuk-do 561-301 (KR).


(74) Agent: **AJU INTERNATIONAL LAW & PATENT GROUP**; 12th Floor, Poonglim Building, 823-1, Yeoksam-dong, Gangnam-gu, Seoul 135-784 (KR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT,

[Continued on next page]

(54) Title: A GROUND DRILLING HAMMER AND THE DRIVING METHOD



(57) Abstract: Disclosed herein is a pneumatic operated hammer for rock drilling, the hammer comprising a cylindrical casing, a back head mounted at an upper portion of the casing, a check valve for opening/closing a compressed air passageway in the casing, a guide for supporting the check valve, a piston adapted to ascend and descend with compressed air in the casing, and a button bit for performing a drilling work through the striking of the piston. The piston is extended to a certain length to conform to the work condition of the pneumatic hammer to thereby prevent a water back-flow phenomenon in which underground water, etc., is introduced into the drilling equipment during the drilling work, compressed air passageways and variable compressed air chambers are formed between the piston and the casing so that when the piston ascends by the compressed air, it abruptly ascends at a load-free state, and the piston has axial portions with a reference diameter and different outer diameters so that it is possible to manufacture a hammer bit having a plurality of variable compressed air chambers formed between the casing the piston to fit for the work capacity. The piston ascended in a load-free state strikes the button bit with its rapid and strong striking force produced by the compressed air supplied from the variable chambers while abruptly descending to thereby perform the drilling work.



RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*