



The present invention relates to an apparatus for forming a rim on a tubular body.

The invention has been developed primarily for use in the formation of rims on tubular containers, and will
5 be described hereinafter with reference to this application. However, it will be appreciated that the invention is not limited to this particular field of use, and may be used to form a rim on any kind of tube.

It is often desirable to form rims on tubular
10 containers to facilitate the subsequent attachment of bases, lids, caps, and the like. Sometimes, no additional attachment is required, and a rim is provided simply to protect or dress the marginal edge of the container.

15 Various techniques are known for forming rims on tubular containers. For example, it is known to mould plastic rims, and then subsequently to secure the rims to the containers in a separate attachment operation. However, this is unsatisfactory, particularly in high
20 rate production applications, because of the relatively large number of process steps involved.

It is also known to mould plastic rims directly onto the tubes. However, this typically involves the use of relatively complex and expensive die assemblies and
25 relatively high powered rams and clamps to resist the jacking forces generated by the injection of molten plastic into the die cavities. Such devices therefore tend to be excessively sophisticated and expensive.



It is an object of the present invention to provide an apparatus which overcomes or substantially ameliorates at least some of these deficiencies of the prior art.

Accordingly, the invention as presently contemplated provides an apparatus for forming a rim on a tube, said apparatus comprising a die block, a locking plate supported in fixed spaced apart relationship with respect to the die block, an inner core block extending intermediate the die block and the locking plate, a pair of complementary outer core blocks slidably disposed around the inner core block intermediate the die block and the locking plate such that the die block and core blocks together in a closed position form a die cavity, a pair of wedge blocks respectively disposed intermediate the outer core blocks and the locking plate, and clamping means operable selectively and progressively to move the outer core blocks together into the closed position thereby clamping the tube against the inner core block such that an exposed end of the tube extends into the die cavity, the clamping means being further operable to drive the wedge blocks between the locking plate and the respective core blocks to wedge the core blocks against the die block in the closed position, the apparatus further including injection means to inject hot thermoplastic material into the die cavity thereby forming a peripheral rim thermoplastically bonded to the exposed end of the tube.

Preferably, resilient compression elements are



disposed intermediate the outer core blocks and the respective wedge blocks and the clamping means are operable directly on the wedge blocks.

Preferably also, the core blocks are connected to
5 the respective wedge blocks by shoulder screws which accommodate the relative lost motion of the core blocks during the wedging phase and limit the maximum excursion of the wedge blocks away from the core blocks. In a release phase, it is preferred that the clamping means
10 first release and retract the wedge blocks, which in turn drag the respective core blocks open by means of the shoulder screws following expansion of the resilient compression elements.

Preferably, the end of the tube remote from the die
15 cavity incorporates a base, and the apparatus further includes a passage to direct pressurised air into the tube through the inner core block upon opening of the die to eject the tubular container.

An inner sleeve associated with the inner core
20 block is preferably provided to support and locate the remote end of the tube.

In the preferred embodiment, the clamping means comprises two hydraulic actuators respectively disposed on opposite sides of the apparatus.

25 In this embodiment, the thermoplastic material is injected through a nozzle disposed on the inner periphery of the die cavity such that the plastic tends to provide an outwardly directed injection pressure on the exposed



end of the tube. The outer core blocks preferably define an inwardly depending shoulder to provide radial support for the exposed end of the tube to resist deformation under the outwardly directed injection pressure.

5 A preferred embodiment of the invention will now be described, by way of example only, with reference to the accompanying drawings in which:-

Figure 1 is a cross sectional side elevation of a rim forming apparatus according to the invention;

10 Figure 2 is a front view of the apparatus shown in Figure 1 with the locking plate removed and one core block retracted for clarity;

Figure 3 is an enlarged sectional view of the die cavity and injection nozzle;

15 Figure 4 is a cross sectional side elevation showing a tubular container having a base at one end, and a rim formed at the other end in accordance with the invention; and

Figure 5 is a cross sectional side elevation
20 similar to Figure 4 showing a tubular body with a rim formed on both ends.

Referring to the drawings, wherein corresponding features are denoted by corresponding reference numerals, the invention provides an apparatus 1 for forming a rim 2
25 on a tubular container 3. The apparatus comprises a die block 4 defining a substantially flat operative surface 5. A locking plate 6 is supported in fixed spaced apart relationship with respect to the die block 4 by a series



of spaced apart high tensile bolts 8. The locking plate 6 defines an operative surface 9 substantially parallel to the opposing surface 5 of the die block. An inner core block 12 extends fixedly from the die block 4 toward the locking plate. A pair of complementary outer core blocks 15 are slidably disposed around the inner core block 12 intermediate the die block 4 and locking plate 6. The outer core blocks 15 are adapted to slide across the operative surface 5 of the die block and together form complementary halves of an outer die corresponding generally in cross sectional configuration to the tube, which in the preferred embodiment is round in section. The die block 4, inner core block 12, and outer core blocks 15 together in a closed position form a die cavity 18, as best seen in Figures 1 and 3.

A pair of wedge blocks 20 are respectively disposed outwardly of the outer core blocks 15 and extend intermediate the core blocks and the locking plate 6. Each wedge block incorporates an inclined surface 21 disposed to engage a correspondingly inclined mating surface 23 on the respective core block.

The apparatus further includes a symmetrically operating clamping assembly 30 comprising two opposed hydraulically actuatable clamping cylinders 31 and 32. The clamping cylinders 31 and 32 incorporate actuating rods 33 bolted directly to the wedge blocks with bolts 34 to transfer the clamping forces directly to the wedge blocks. A resilient compression element 35 is disposed



intermediate each outer core block 15 and the respective wedge block 20. The core blocks are connected to the respective wedge blocks by shoulder screws 38 (as best seen in Figure 2) which accommodate a predetermined
5 degree of relative displacement. This arrangement provides a degree of "lost motion", but limits the maximum relative excursion between these components, as described in more detail below.

As best seen in Figure 3, injection means in the
10 form of an injection screw and barrel assembly (not shown) are disposed to inject hot thermoplastic material into annular passage 40 in the die block, through nozzle 41, and into the die cavity 18.

An inner cylindrical boss 50 incorporating an
15 ejector sleeve extends coaxially from the inner core block 12 to support and locate the end of the tube remote from the die block.

Turning now to describe the operation of the apparatus, the clamping cylinders 31 and 32 are initially
20 retracted to separate the outer core blocks 15 and open the die, as shown in Figure 2. A tube is then placed over the boss 50 and the inner core block 12. In the present case, the tube is preformed with a base 51 and the boss 50 is specifically sized to locate the base so
25 that the exposed end of the tube is located in predetermined relationship with respect to the die block.

With the tube in place, the clamping assembly 30 is



actuated. Initial relative movement of the actuating rods 33 acting on the wedge blocks 20 is transferred to the outer core blocks 15 by the intermediate compression elements 35. In this initial die closing phase, the inclined surfaces 21 of the wedge blocks and the correspondingly inclined mating surfaces 23 of the core blocks are marginally separated by the compression elements. Similarly, during this phase a clearance space is maintained between the operative surface 9 of the locking plate and the wedge blocks so that no wedging action occurs. In this way, the outer core blocks 15 are progressively moved together across the die block and into the closed position, ultimately clamping the tube firmly against the inner core block 12 such that the exposed end of the tube extends into the die cavity. The amount by which the tube extends into the cavity is determined by the locating boss 50 and is preferably of the order of several millimetres. This action substantially closes and seals the die cavity.

With the die closed, further displacement of the clamping cylinder drives the wedge blocks toward the respective core blocks 15 by compression of the intermediate resilient elements 35. This relative "lost motion" is accommodated by shoulder screws 38, as best seen in Figure 2. During this locking phase, the wedge blocks are driven between the locking plate and the core blocks, to secure the core blocks against the die block 4.



With the die segments closed and locked, hot thermoplastic material is injected under pressure into passage 40, through nozzle 41 and into the die cavity 18 thereby forming a peripheral rim thermoplastically bonded to the exposed end of the tube. During this injection phase, it will be appreciated that the jacking forces on the outer core blocks generated by the injection of pressurised plastic into the void are effectively resisted by the wedge blocks and locking plate, with only a small force component being reacted by the clamping cylinder. It should also be noted that the plastic is injected at the inner periphery of the die cavity to provide an outwardly directed injection pressure on the exposed end of the tube. The outer core blocks 15 define an inwardly depending shoulder 60 to prevent deformation of the marginal edge of the tube under the injection pressure of the molten plastic.

Once the rim has been formed, the clamping cylinders begin to withdraw. Since the actuating rods 33 of the clamping cylinders act directly on the wedge blocks via bolts 34, the initial withdrawal releases the wedge blocks from locking engagement between the core blocks and locking plate which in turn permits the intermediate compression elements 35 to expand. Further retraction of the clamping cylinder and wedge blocks drags open the core blocks, once the interconnecting shoulder screws 38 abut their respective end stops.

With the die again in the open position as shown in



Figure 2, pressurised air is directed into the container through air central ejection passage 55, thereby ejecting the container from the apparatus. The cycle can then be repeated.

5 Once the rim is formed, the tube and rim may be heated and reformed into varying cross sectional profiles such as square, triangular or the like if required, without the need for different die shapes.


10 It will be appreciated that this method and apparatus enables the formation of a rim on a tube without the need for a moving platen. Moreover, because most of the jacking forces are reacted by the wedge blocks and only a small component transferred to the clamping assembly, a relatively small clamping
15 actuator can be used. These advantages combine to produce an apparatus which is considerably simpler, cheaper, more compact, and more efficient than comparable prior art devices.

20 Although the invention has been described with reference to a specific example, it will be appreciated by those skilled in the art that the invention may be embodied in many other forms.



Claims: -

1. Apparatus for forming a rim (2) on a tube (3), the apparatus comprising a die block (4), a locking plate (6) supported in fixed spaced apart relationship with respect to the die block (4), an inner core block (12) extending intermediate the die block (4) and the locking plate (6), complementary outer core blocks (15) slidably disposed around the inner core block (12) intermediate the die block (4) and the locking plate (6) such that the die block (4) and core blocks (12, 15) together in a closed position form a die cavity (18), wedge blocks (20) respectively disposed intermediate the outer core blocks (15) and the locking plate (6), and clamping means (30) operable selectively and progressively to move the outer core block (15) together into the closed position, thereby clamping the tube (3) against the inner core block (12) such that an exposed end of the tube (3) extends into the die cavity (18), the clamping means (30) being further operable to drive the wedge blocks (20) between the locking plate (6) and the respective outer core blocks (15) to wedge the outer core blocks (15) against the die block (4) in the closed position, the apparatus further including injection means to inject hot thermoplastic material into the die cavity (18), thereby forming a peripheral rim (2) thermoplastically bonded to the exposed end of the tube (3)



2. Apparatus according to claim 1, further including resilient compression elements (35) disposed intermediate the outer core blocks (15) and the respective wedge blocks (20).

3. Apparatus according to claim 1 or 2, wherein the clamping means (30) are operable directly on the wedge blocks (20).

4. Apparatus according to any preceding claim, wherein the outer core blocks (15) are connected to the respective wedge blocks (20) by connecting elements (38) which accommodate a degree of relative displacement of the wedge blocks (20) toward the core blocks (15) and limit the maximum relative displacement of the wedge blocks (20) away from the core blocks (15).

5. Apparatus according to claim 4, wherein the clamping means (30) are operable in a release phase firstly to release and retract the wedge blocks (20) and subsequently to retract the respective outer core blocks (15) by means of the connecting elements (38) at the point of maximum relative displacement.

6. Apparatus according to any preceding claim, for use with a tube (3) which incorporates a preformed base (51) remote from the die cavity (18), wherein the apparatus further includes a passage (55) to direct pressurised gas into the tube (3) through the inner core block (12) upon opening of the die to eject the tube (3) from the apparatus.



7. Apparatus according to any preceding claim, further including an inner sleeve (50) associated with the inner core block (12) to locate the remote end of the tube (3).

8. Apparatus according to any preceding claim, wherein the clamping means (30) comprises mutually opposed hydraulic actuators (31,32) disposed on opposite sides of the die and operable on the respective wedge blocks (20).

9. Apparatus according to any preceding claim, wherein the thermoplastic material is injectable through a nozzle (41) disposed on an inner periphery of the die cavity (18) such that the thermoplastic material tends to provide an outwardly directed injection pressure on the exposed end of the tube (3).

10. Apparatus according to claim 9, wherein the outer core blocks (15) together define an inwardly depending peripheral shoulder (60) to provide radial support for the exposed end of the tube (3) and thereby to resist deformation of the tube under the outwardly directed injection pressure.

11. Apparatus according to any preceding claim, wherein each wedge block (20) incorporates an inclined wedging surface (23) disposed to engage a correspondingly inclined mating surface (21) on the respective core block (15).



12. Apparatus according to claim 11, wherein the said inclined surfaces (21,23) are disposed such that the majority of jacking forces acting on the outer core blocks (15) by the injection of the thermoplastic material into the die cavity (18) are reacted by the locking plate (6), whereby only a relatively smaller force component is reacted by the clamping means (30).

13. Apparatus according to claim 2 or any claim dependent thereon, wherein the resilient compression elements (35) are disposed initially to drive the wedge blocks (20) out of clamping engagement with the respective outer core blocks (15) immediately upon release of the clamping means (30).

14. Apparatus according to any preceding claim, wherein the die block (4) and locking plate (6) define respective mutually opposing substantially parallel guide surfaces (5,9) along which the outer core blocks (15) and wedge blocks (20) respectively slide in response to operation of the clamping means (30).



SET OF TWO DIES FOR A CRIMPING TOOL
ABSTRACT

An apparatus (1) for forming a rim (2) on a tube (3). The apparatus (1) comprises a die block (4), a locking plate (6) supported in fixed spaced apart relationship with respect to the die block (4), an inner core block (12) extending intermediate the die block (4) and the locking plate (6), and a pair of complementary outer core blocks (15) slidably disposed around the inner core block (12) intermediate the die block (4) and the locking plate (6) such that the die block (4) and core blocks (12,15) together in a closed position form a die cavity (18). A pair of wedge blocks (20) are respectively disposed intermediate the outer core blocks (15) and the locking plate (6), and clamping means (30) are operable selectively and progressively to move the outer core blocks (15) together into the closed position, thereby clamping the tube against the inner core block (12) such that an exposed end of the tube extends into the die cavity (18). The clamping means (30) are further operable to drive the wedge blocks (20) between the locking plate (6) and the respective core blocks to wedge the core blocks against the die block (4) in the closed position. The apparatus (1) also includes injection means to inject hot thermoplastic material into the die cavity (18) thereby forming a peripheral rim thermoplastically bonded to the exposed end of the tube.




FIG 1






FIG 3

This Sheet Has Been Replaced



4/5




FIG 4



5/5




FIG 5

Rtmp copy

REPLACEMENT SHEET

09 OCT 1996

1

SET OF TWO DIES FOR A CRIMPING TOOL

The present invention relates to an apparatus for forming a rim on a tubular body.

The invention has been developed primarily for use in the formation of rims on tubular containers, and will be described hereinafter with reference to this application. However, it will be appreciated that the invention is not limited to this particular field of use, and may be used to form a rim on any kind of tube.

It is often desirable to form rims on tubular containers to facilitate the subsequent attachment of bases, lids, caps, and the like. Sometimes, no additional attachment is required, and a rim is provided simply to protect or dress the marginal edge of the container.

Various techniques are known for forming rims on tubular containers. For example, it is known to mould plastic rims, and then subsequently to secure the rims to the containers in a separate attachment operation. However, this is unsatisfactory, particularly in high rate production applications, because of the relatively large number of process steps involved.

It is also known to mould plastic rims directly onto the tubes. However, this typically involves the use of relatively complex and expensive die assemblies and relatively high powered rams and clamps to resist the jacking forces generated by the injection of molten plastic into the die cavities. Such devices therefore tend to be excessively sophisticated and expensive.

This Sheet Has Been Replaced



0000

09 OCT 1996

It is an object of the present invention to provide an apparatus which overcomes or substantially ameliorates at least some of these deficiencies of the prior art.

Accordingly, the invention as presently contemplated provides an apparatus for forming a rim on a tube, said apparatus comprising a die block, a locking plate supported in fixed spaced apart relationship with respect to the die block, an inner core block extending intermediate the die block and the locking plate, a pair of complementary outer core blocks slidably disposed around the inner core block intermediate the die block and the locking plate such that the die block and core blocks together in a closed position form a die cavity, a pair of wedge blocks respectively disposed intermediate the outer core blocks and the locking plate, and clamping means operable selectively and progressively to move the outer core blocks together into the closed position thereby clamping the tube against the inner core block such that an exposed end of the tube extends into the die cavity, the clamping means being further operable to drive the wedge blocks between the locking plate and the respective core blocks to wedge the core blocks against the die block in the closed position, the apparatus further including injection means to inject hot thermoplastic material into the die cavity thereby forming a peripheral rim thermoplastically bonded to the exposed end of the tube.

Preferably, resilient compression elements are



09 OCT 1996

disposed intermediate the outer core blocks and the respective wedge blocks and the clamping means are operable directly on the wedge blocks.

Preferably also, the core blocks are connected to the respective wedge blocks by shoulder screws which accommodate the relative lost motion of the core blocks during the wedging phase and limit the maximum excursion of the wedge blocks away from the core blocks. In a release phase, it is preferred that the clamping means first release and retract the wedge blocks, which in turn drag the respective core blocks open by means of the shoulder screws following expansion of the resilient compression elements.

Preferably, the end of the tube remote from the die cavity incorporates a base, and the apparatus further includes a passage to direct pressurised air into the tube through the inner core block upon opening of the die to eject the tubular container.

An inner sleeve associated with the inner core block is preferably provided to support and locate the remote end of the tube.

In the preferred embodiment, the clamping means comprises two hydraulic actuators respectively disposed on opposite sides of the apparatus.

In this embodiment, the thermoplastic material is injected through a nozzle disposed on the inner periphery of the die cavity such that the plastic tends to provide an outwardly directed injection pressure on the exposed



09 OCT 1996

end of the tube. The outer core blocks preferably define an inwardly depending shoulder to provide radial support for the exposed end of the tube to resist deformation under the outwardly directed injection pressure.

A preferred embodiment of the invention will now be described, by way of example only, with reference to the accompanying drawings in which:-

Figure 1 is a cross sectional side elevation of a rim forming apparatus according to the invention;

Figure 2 is a front view of the apparatus shown in Figure 1 with the locking plate removed and one core block retracted for clarity;

Figure 3 is an enlarged sectional view of the die cavity and injection nozzle;

Figure 4 is a cross sectional side elevation showing a tubular container having a base at one end, and a rim formed at the other end in accordance with the invention; and

Figure 5 is a cross sectional side elevation similar to Figure 4 showing a tubular body with a rim formed on both ends.


Referring to the drawings, wherein corresponding features are denoted by corresponding reference numerals, the invention provides an apparatus 1 for forming a rim 2 on a tubular container 3. The apparatus comprises a die block 4 defining a substantially flat operative surface 5. A locking plate 6 is supported in fixed spaced apart relationship with respect to the die block 4 by a series



This Sheet Has Been Replaced




5



of spaced apart high tensile bolts 8. The locking plate 6 defines an operative surface 9 substantially parallel to the opposing surface 5 of the die block. An inner core block 12 extends fixedly from the die block 4 toward the locking plate. A pair of complementary outer core blocks 15 are slidably disposed around the inner core block 12 intermediate the die block 4 and locking plate 6. The outer core blocks 15 are adapted to slide across the operative surface 5 of the die block and together form complementary halves of an outer die corresponding generally in cross sectional configuration to the tube, which in the preferred embodiment is round in section. The die block 4, inner core block 12, and outer core blocks 15 together in a closed position form a die cavity 18, as best seen in Figures 1 and 3.

A pair of wedge blocks 20 are respectively disposed outwardly of the outer core blocks 15 and extend intermediate the core blocks and the locking plate 6. Each wedge block incorporates an inclined surface 21 disposed to engage a correspondingly inclined mating surface 23 on the respective core block.

The apparatus further includes a symmetrically operating clamping assembly 30 comprising two opposed hydraulically actuable clamping cylinders 31 and 32. The clamping cylinders 31 and 32 incorporate actuating rods 33 bolted directly to the wedge blocks with bolts 34 to transfer the clamping forces directly to the wedge blocks. A resilient compression element 35 is disposed



intermediate each outer core block 15 and the respective wedge block 20. The core blocks are connected to the respective wedge blocks by shoulder screws 38 (as best seen in Figure 2) which accommodate a predetermined degree of relative displacement. This arrangement provides a degree of "lost motion", but limits the maximum relative excursion between these components, as described in more detail below.

As best seen in Figure 3, injection means in the form of an injection screw and barrel assembly (not shown) are disposed to inject hot thermoplastic material into annular passage 40 in the die block, through nozzle 41, and into the die cavity 18.

An inner cylindrical boss 50 incorporating an ejector sleeve extends coaxially from the inner core block 12 to support and locate the end of the tube remote from the die block.

Turning now to describe the operation of the apparatus, the clamping cylinders 31 and 32 are initially retracted to separate the outer core blocks 15 and open the die, as shown in Figure 2. A tube is then placed over the boss 50 and the inner core block 12. In the present case, the tube is preformed with a base 51 and the boss 50 is specifically sized to locate the base so that the exposed end of the tube is located in predetermined relationship with respect to the die block.

With the tube in place, the clamping assembly 30 is

This Sheet Has Been Replaced



09 OCT 1996

actuated. Initial relative movement of the actuating rods 33 acting on the wedge blocks 20 is transferred to the outer core blocks 15 by the intermediate compression elements 35. In this initial die closing phase, the inclined surfaces 21 of the wedge blocks and the correspondingly inclined mating surfaces 23 of the core blocks are marginally separated by the compression elements. Similarly, during this phase a clearance space is maintained between the operative surface 9 of the locking plate and the wedge blocks so that no wedging action occurs. In this way, the outer core blocks 15 are progressively moved together across the die block and into the closed position, ultimately clamping the tube firmly against the inner core block 12 such that the exposed end of the tube extends into the die cavity. The amount by which the tube extends into the cavity is determined by the locating boss 50 and is preferably of the order of several millimetres. This action substantially closes and seals the die cavity.

With the die closed, further displacement of the clamping cylinder drives the wedge blocks toward the respective core blocks 15 by compression of the intermediate resilient elements 35. This relative "lost motion" is accommodated by shoulder screws 38, as best seen in Figure 2. During this locking phase, the wedge blocks are driven between the locking plate and the core blocks, to secure the core blocks against the die block

4.

This Sheet Has Been Replaced



04 OCT 1996

With the die segments closed and locked, hot thermoplastic material is injected under pressure into passage 40, through nozzle 41 and into the die cavity 18 thereby forming a peripheral rim thermoplastically bonded to the exposed end of the tube. During this injection phase, it will be appreciated that the jacking forces on the outer core blocks generated by the injection of pressurised plastic into the void are effectively resisted by the wedge blocks and locking plate, with only a small force component being reacted by the clamping cylinder. It should also be noted that the plastic is injected at the inner periphery of the die cavity to provide an outwardly directed injection pressure on the exposed end of the tube. The outer core blocks 15 define an inwardly depending shoulder 60 to prevent deformation of the marginal edge of the tube under the injection pressure of the molten plastic.

Once the rim has been formed, the clamping cylinders begin to withdraw. Since the actuating rods 33 of the clamping cylinders act directly on the wedge blocks via bolts 34, the initial withdrawal releases the wedge blocks from locking engagement between the core blocks and locking plate which in turn permits the intermediate compression elements 35 to expand. Further retraction of the clamping cylinder and wedge blocks drags open the core blocks, once the interconnecting shoulder screws 38 abut their respective end stops.

With the die again in the open position as shown in



09 OCT 1996

Figure 2, pressurised air is directed into the container through air central ejection passage 55, thereby ejecting the container from the apparatus. The cycle can then be repeated.

Once the rim is formed, the tube and rim may be heated and reformed into varying cross sectional profiles such as square, triangular or the like if required, without the need for different die shapes.

It will be appreciated that this method and apparatus enables the formation of a rim on a tube without the need for a moving platen. Moreover, because most of the jacking forces are reacted by the wedge blocks and only a small component transferred to the clamping assembly, a relatively small clamping actuator can be used. These advantages combine to produce an apparatus which is considerably simpler, cheaper, more compact, and more efficient than comparable prior art devices.

Although the invention has been described with reference to a specific example, it will be appreciated by those skilled in the art that the invention may be embodied in many other forms.





REPLACEMENT SHEET

09 OCT 1996

10

Claims: -

1. Apparatus for forming a rim (2) on a tube (3), the apparatus comprising a die block (4), a locking plate (6) supported in fixed spaced apart relationship with respect to the die block (4), an inner core block (12) extending intermediate the die block (4) and the locking plate (6), complementary outer core blocks (15) slidably disposed around the inner core block (12) intermediate the die block (4) and the locking plate (6) such that the die block (4) and core blocks (12, 15) together in a closed position form a die cavity (18), wedge blocks (20) respectively disposed intermediate the outer core blocks (15) and the locking plate (6), and clamping means (30) operable selectively and progressively to move the outer core block (15) together into the closed position, thereby clamping the tube (3) against the inner core block (12) such that an exposed end of the tube (3) extends into the die cavity (18), the clamping means (30) being further operable to drive the wedge blocks (20) between the locking plate (6) and the respective outer core blocks (15) to wedge the outer core blocks (15) against the die block (4) in the closed position, the apparatus further including injection means to inject hot thermoplastic material into the die cavity (18), thereby forming a peripheral rim (2) thermoplastically bonded to the exposed end of the tube (3).

This Sheet Has Been Replaced





REPLACEMENT SHEET

09 OCT 1996

11

2. Apparatus according to claim 1, further including resilient compression elements (35) disposed intermediate the outer core blocks (15) and the respective wedge blocks (20).

3. Apparatus according to claim 1 or 2, wherein the clamping means (30) are operable directly on the wedge blocks (20).

4. Apparatus according to any preceding claim, wherein the outer core blocks (15) are connected to the respective wedge blocks (20) by connecting elements (38) which accommodate a degree of relative displacement of the wedge blocks (20) toward the core blocks (15) and limit the maximum relative displacement of the wedge blocks (20) away from the core blocks (15).

5. Apparatus according to claim 4, wherein the clamping means (30) are operable in a release phase firstly to release and retract the wedge blocks (20) and subsequently to retract the respective outer core blocks (15) by means of the connecting elements (38) at the point of maximum relative displacement.

6. Apparatus according to any preceding claim, for use with a tube (3) which incorporates a preformed base (51) remote from the die cavity (18), wherein the apparatus further includes a passage (55) to direct pressurised gas into the tube (3) through the inner core block (12) upon opening of the die to eject the tube (3) from the apparatus.

This Sheet Has Been Replaced





* C L M S *

REPLACEMENT SHEET

09 OCT 1996

7. Apparatus according to any preceding claim, further including an inner sleeve (50) associated with the inner core block (12) to locate the remote end of the tube (3).

8. Apparatus according to any preceding claim, wherein the clamping means (30) comprises mutually opposed hydraulic actuators (31, 32) disposed on opposite sides of the die and operable on the respective wedge blocks (20).

9. Apparatus according to any preceding claim, wherein the thermoplastic material is injectable through a nozzle (41) disposed on an inner periphery of the die cavity (18) such that the thermoplastic material tends to provide an outwardly directed injection pressure on the exposed end of the tube (3).

10. Apparatus according to claim 9, wherein the outer core blocks (15) together define an inwardly depending peripheral shoulder (60) to provide radial support for the exposed end of the tube (3) and thereby to resist deformation of the tube under the outwardly directed injection pressure.

11. Apparatus according to any preceding claim, wherein each wedge block (20) incorporates an inclined wedging surface (23) disposed to engage a correspondingly inclined mating surface (21) on the respective core block (15).






12. Apparatus according to claim 11, wherein the said inclined surfaces (21,23) are disposed such that the majority of jacking forces acting on the outer core blocks (15) by the injection of the thermoplastic material into the die cavity (18) are reacted by the locking plate (6), whereby only a relatively smaller force component is reacted by the clamping means (30).

13. Apparatus according to claim 2 or any claim dependent thereon, wherein the resilient compression elements (35) are disposed initially to drive the wedge blocks (20) out of clamping engagement with the respective outer core blocks (15) immediately upon release of the clamping means (30).

14. Apparatus according to any preceding claim, wherein the die block (4) and locking plate (6) define respective mutually opposing substantially parallel guide surfaces (5,9) along which the outer core blocks (15) and wedge blocks (20) respectively slide in response to operation of the clamping means (30).



This Sheet Has Been Replaced



09 OCT 1996

SET OF TWO DIES FOR A CRIMPING TOOL

ABSTRACT

An apparatus (1) for forming a rim (2) on a tube (3). The apparatus (1) comprises a die block (4), a locking plate (6) supported in fixed spaced apart relationship with respect to the die block (4), an inner core block (12) extending intermediate the die block (4) and the locking plate (6), and a pair of complementary outer core blocks (15) slidably disposed around the inner core block (12) intermediate the die block (4) and the locking plate (6) such that the die block (4) and core blocks (12,15) together in a closed position form a die cavity (18). A pair of wedge blocks (20) are respectively disposed intermediate the outer core blocks (15) and the locking plate (6), and clamping means (30) are operable selectively and progressively to move the outer core blocks (15) together into the closed position thereby clamping the tube against the inner core block (12) such that an exposed end of the tube extends into the die cavity (18). The clamping means (30) are further operable to drive the wedge blocks (20) between the locking plate (6) and the respective core blocks to wedge the core blocks against the die block (4) in the closed position. The apparatus (1) also includes injection means to inject hot thermoplastic material into the die cavity (18) thereby forming a peripheral rim thermoplastically bonded to the exposed end of the ~~tube~~.

Figure 1

This Sheet Has Been Replaced



09 OCT 1996

1/5





FIG 1

09 OCT 1996


09 OCT 1996



246

09 OCT 1996

3/5



REPLACEMENT SHEET

09 OCT 1996

4/5




FIG 4

REPLACEMENT SHEET

09 OCT 1996

5/5




FIG 5

8-150005P

REPLACEMENT SHEET

10 FEB 1998

SET OF TWO DIES FOR A CRIMPING TOOL

The present invention relates to an apparatus for forming a rim on a tubular body.

The invention has been developed primarily for use in the formation of rims on tubular containers, and will be described hereinafter with reference to this application.

5 However, it will be appreciated that the invention is not limited to this particular field of use, and may be used to form a rim on any kind of tube.

It is often desirable to form rims on tubular containers to facilitate the subsequent attachment of bases, lids, caps, and the like. Sometimes, no additional attachment is required, and a rim is provided simply to protect or dress the marginal edge of the
10 container.

Various techniques are known for forming rims on tubular containers. For example, it is known to mould plastic rims, and then subsequently to secure the rims to the containers in a separate attachment operation. However, this is unsatisfactory, particularly in high rate production applications, because of the relatively large number of
15 process steps involved.

It is also known to mould plastic rims directly onto the tubes. However, this typically involves the use of relatively complex and expensive die assemblies and relatively high powered rams and clamps to resist the jacking forces generated by the injection of molten plastic into the die cavities. Such devices therefore tend to be
20 excessively sophisticated and expensive.

GB-A-2190323 discloses apparatus for moulding a container mouth section onto one end of a tube. The apparatus comprising a die block, a plate resiliently supported above the die block, an inner core block extending intermediate the die block and the plate, and complementary outer core blocks slidably disposed around the inner block

10 FEB 1998

- 2 -

intermediate the die block and the plate. Wedge blocks are respectively disposed
intermediate the outer core blocks and the plate. Clamping means are progressively
operable to move the outer core blocks together into the closed position, thereby clamping
the tube against the inner core block such that an exposed end of the tube extends into the
5 die cavity formed by the closed outer core blocks and the inner core block. The apparatus
further includes means to inject hot thermoplastic material into the die cavity, thereby
forming a container mouth bonded to the end of the tube.

GB-A-2 171 048 discloses apparatus for forming a rim on a tube, in accordance
with the pre-characterising part of claim 1.

10 It is an object of the present invention to provide an apparatus which overcomes or
substantially ameliorates at least some of the deficiencies of the prior art.

According to the present invention as set forth in claim 1, a locking plate is
supported in fixed space apart relationship with respect to the die block, clamping means
being operable to drive the wedges of wedge blocks between the locking plate and
15 respective outer core blocks to wedge the outer core blocks against the die block in the
closed position such that the die block and core blocks together in the closed position
form the die cavity.

Preferably, resilient compression elements are disposed intermediate the outer core
blocks and the respective wedge blocks and the clamping means are operable directly on
20 the wedge blocks.

Preferably also, the core blocks are connected to the respective wedge blocks by
shoulder screws which accommodate the relative lost motion of the core blocks during the
wedging phase and limit the maximum excursion of the wedge blocks away from the core
blocks. In a release phase, it is preferred that the clamping means first release and retract

10 FEB 1998

- 3 -

the wedge blocks, which in turn drag the respective core blocks open by means of the shoulder screws following expansion of the resilient compression elements.

Preferably, the end of the tube remote from the die cavity incorporates a base, and the apparatus further includes a passage to direct pressurised air into the tube through the
5 inner core block upon opening of the die to eject the tubular container.

An inner sleeve associated with the inner core block is preferably provided to support and locate the remote end of the tube.

In the preferred embodiment, the clamping means comprises two hydraulic actuators respectively disposed on opposite sides of the apparatus.

10 In this embodiment, the thermoplastic material is injected through a nozzle disposed on the inner periphery of the die cavity such that the plastic tends to provide an outwardly directed injection pressure on the exposed end of the tube. The outer core blocks preferably define an inwardly depending shoulder to provide radial support for the exposed end of the tube to resist deformation under the outwardly directed injection
15 pressure.

A preferred embodiment of the invention will now be described, by way of example only, with reference to the accompanying drawings in which:-

Figure 1 is a cross sectional side elevation of a rim forming apparatus according to the invention;

20 Figure 2 is a front view of the apparatus shown in Figure 1 with the locking plate removed and one core block retracted for clarity;

Figure 3 is an enlarged sectional view of the die cavity and injection nozzle;

Figure 4 is a cross sectional side elevation showing a tubular container having a base at one end, and a rim formed at the other end in accordance with the invention; and

10 FEB 1998

- 4 -

Figure 5 is a cross sectional side elevation similar to Figure 4 showing a tubular body with a rim formed on both ends.

Referring to the drawings, wherein corresponding features are denoted by corresponding reference numerals, the invention provides an apparatus 1 for forming a rim 2 on a tubular container 3. The apparatus comprises a die block 4 defining a substantially flat operative surface 5. A locking plate 6 is supported in fixed spaced apart relationship with respect to the die block 4 by a series of spaced apart high tensile bolts 8. The locking plate 6 defines an operative surface 9 substantially parallel to the opposing surface 5 of the die block. An inner core block 12 extends fixedly from the die block 4 toward the locking plate. A pair of complementary outer core blocks 15 are slidably disposed around the inner core block 12 intermediate the die block 4 and locking plate 6. The outer core blocks 15 are adapted to slide across the operative surface 5 of the die block and together form complementary halves of an outer die corresponding generally in cross sectional configuration to the tube, which in the preferred embodiment is round in section. The die block 4, inner core block 12, and outer core blocks 15 together in a closed position form a die cavity 18, as best seen in Figures 1 and 3.

A pair of wedge blocks 20 are respectively disposed outwardly of the outer core blocks 15 and extend intermediate the core blocks and the locking plate 6. Each wedge block incorporates an inclined surface 21 disposed to engage a correspondingly inclined mating surface 23 on the respective core block.

The apparatus further includes a symmetrically operating clamping assembly 30 comprising two opposed hydraulically actuable clamping cylinders 31 and 32. The clamping cylinders 31 and 32 incorporate actuating rods 33 bolted directly to the wedge blocks with bolts 34 to transfer the clamping forces directly to the wedge blocks. A

10 FEB 1998

- 5 -


resilient compression element 35 is disposed intermediate each outer core block 15 and the respective wedge block 20. The core blocks are connected to the respective wedge blocks by shoulder screws 38 (as best seen in Figure 2) which accommodate a predetermined degree of relative displacement. This arrangement provides a degree of "lost motion", but limits the maximum relative excursion between these components, as described in more detail below.

As best seen in Figure 3, injection means in the form of an injection screw and barrel assembly (not shown) are disposed to inject hot thermoplastic material into annular passage 40 in the die block, through nozzle 41, and into the die cavity 18.

10 An inner cylindrical boss 50 incorporating an ejector sleeve extends coaxially from the inner core block 12 to support and locate the end of the tube remote from the die block.

Turning now to describe the operation of the apparatus, the clamping cylinders 31 and 32 are initially retracted to separate the outer core blocks 15 and open the die, as shown in Figure 2. A tube is then placed over the boss 50 and the inner core block 12. In the present case, the tube is preformed with a base 51 and the boss 50 is specifically sized to locate the base so that the exposed end of the tube is located in predetermined relationship with respect to the die block.

With the tube in place, the clamping assembly 30 is actuated. Initial relative movement of the actuating rods 33 acting on the wedge blocks 20 is transferred to the outer core blocks 15 by the intermediate compression elements 35. In this initial die closing phase, the inclined surfaces 21 of the wedge blocks and the correspondingly inclined mating surfaces 23 of the core blocks are marginally separated by the compression elements. Similarly, during this phase a clearance space is maintained



between the operative surface 9 of the locking plate and the wedge blocks so that no wedging action occurs. In this way, the outer core blocks 15 are progressively moved together across the die block and into the closed position, ultimately clamping the tube firmly against the inner core block 12 such that the exposed end of the tube extends into the die cavity. The amount by which the tube extends into the cavity is determined by the
5 locating boss 50 and is preferably of the order of several millimetres. This action substantially closes and seals the die cavity.

With the die closed, further displacement of the clamping cylinder drives the wedge blocks toward the respective core blocks 15 by compression of the intermediate
10 resilient elements 35. This relative "lost motion" is accommodated by shoulder screws 38, as best seen in Figure 2. During this locking phase, the wedge blocks are driven between the locking plate and the core blocks, to secure the core blocks against the die block 4.

With the die segments closed and locked, hot thermoplastic material is injected
15 under pressure into passage 40, through nozzle 41 and into the die cavity 18 thereby forming a peripheral rim thermoplastically bonded to the exposed end of the tube. During this injection phase, it will be appreciated that the jacking forces on the outer core blocks generated by the injection of pressurised plastic into the void are effectively resisted by the wedge blocks and locking plate, with only a small force component being reacted by
20 the clamping cylinder. It should also be noted that the plastic is injected at the inner periphery of the die cavity to provide an outwardly directed injection pressure on the exposed end of the tube. The outer core blocks 15 define an inwardly depending shoulder 60 to prevent deformation of the marginal edge of the tube under the injection pressure of the molten plastic.


Once the rim has been formed, the clamping cylinders begin to withdraw. Since the actuating rods 33 of the clamping cylinders act directly on the wedge blocks via bolts 34, the initial withdrawal releases the wedge blocks from locking engagement between the core blocks and locking plate which in turn permits the intermediate compression elements 35 to expand. Further retraction of the clamping cylinder and wedge blocks drags open the core blocks, once the interconnecting shoulder screws 38 abut their respective end stops.

With the die again in the open position as shown in Figure 2, pressurised air is directed into the container through air central ejection passage 55, thereby ejecting the container from the apparatus. The cycle can then be repeated.

Once the rim is formed, the tube and rim may be heated and reformed into varying cross sectional profiles such as square, triangular or the like if required, without the need for different die shapes.

It will be appreciated that this method and apparatus enables the formation of a rim on a tube without the need for a moving platen. Moreover, because most of the jacking forces are reacted by the wedge blocks and only a small component transferred to the clamping assembly, a relatively small clamping actuator can be used. These advantages combine to produce an apparatus which is considerably simpler, cheaper, more compact, and more efficient than comparable prior art devices.

Although the invention has been described with reference to a specific example, it will be appreciated by those skilled in the art that the invention may be embodied in many other forms.



10 FEB 1998



Claims:-

1. Apparatus for forming a rim (2) on a tube (3), the apparatus comprising a die block (4), a plate (6), an inner core block (12) extending intermediate the die block (4) and the plate (6), and injection means to inject hot thermoplastic material into a die cavity (18), thereby forming a peripheral rim (2) thermoplastically bonded to the exposed end of the tube (3), characterised in that the plate (6) is a locking plate supported in fixed space apart relationship with respect to the die block (4), complementary outer core blocks (15) are slidably disposed around the inner core block (12) intermediate the die block (4) and the plate (6), wedge blocks (20) are respectively disposed intermediate the outer core blocks (15) and the plate (6), and clamping means (30) are operable selectively and progressively to move the outer core blocks (15) together into a closed position thereby clamping the tube (3) against the inner core block (12) such that an exposed end of the tube (2) extends into the die cavity (18), which is delimited by the core blocks (12,15), the clamping means (30) being further operable to drive the wedges of the wedge blocks (20) between the locking plate (6) and the respective outer core blocks (15) to wedge the outer core blocks against the die block (4) in the closed position such that the die block (4) and core blocks (12,15) together in the closed position form the die cavity (18).
2. Apparatus according to claim 1, further including resilient compression elements (35) disposed intermediate the outer core blocks (15) and the respective wedge blocks (20).
3. Apparatus according to claim 1 or 2, wherein the clamping means (30) are operable directly on the wedge blocks (20).
4. Apparatus according to any preceding claim, wherein the outer core blocks (15) are connected to the respective wedge blocks (20) by connecting elements (38) which



accommodate a degree of relative displacement of the wedge blocks (20) toward the core blocks (15) and limit the maximum relative displacement of the wedge blocks (20) away from the core blocks (15).

5. Apparatus according to claim 4, wherein the clamping means (30) are operable in
5 a release phase firstly to release and retract the wedge blocks (20) and subsequently to retract the respective outer core blocks (15) by means of the connecting elements (38) at the point of maximum relative displacement.


6. Apparatus according to any preceding claim, for use with a tube (3) which incorporates a preformed base (51) remote from the die cavity (18), wherein the apparatus
10 further includes a passage (55) to direct pressurised gas into the tube (3) through the inner core block (12) upon opening of the die to eject the tube (3) from the apparatus.

7. Apparatus according to any preceding claim, further including an inner sleeve (50) associated with the inner core block (12) to locate the remote end of the tube (3).

8. Apparatus according to any preceding claim, wherein the clamping means (30)
15 comprises mutually opposed hydraulic actuators (31,32) disposed on opposite sides of the die and operable on the respective wedge blocks (20).

9. Apparatus according to any preceding claim, wherein the thermoplastic material is injectable through a nozzle (41) disposed on an inner periphery of the die cavity (18) such that the thermoplastic material tends to provide an outwardly directed injection pressure
20 on the exposed end of the tube (3).

10. Apparatus according to claim 9, wherein the outer core blocks (15) together define an inwardly depending peripheral shoulder (60) to provide radial support for the exposed end of the tube (3) and thereby to resist deformation of the tube under the outwardly directed injection pressure.





11. Apparatus according to any preceding claim, wherein each wedge block (20) incorporates an inclined wedging surface (23) disposed to engage a correspondingly inclined mating surface (21) on the respective core block (15).

12. Apparatus according to claim 11, wherein the said inclined surfaces (21,23) are disposed such that the majority of jacking forces acting on the outer core blocks (15) by the injection of the thermoplastic material into the die cavity (18) are reacted by the locking plate (6), whereby only a relatively smaller force component is reacted by the clamping means (30).

13. Apparatus according to claim 2 or any claim dependent thereon, wherein the resilient compression elements (35) are disposed initially to drive the wedge blocks (20) out of clamping engagement with the respective outer core blocks (15) immediately upon release of the clamping means (30):

14. Apparatus according to any preceding claim, wherein the die block (4) and locking plate (6) define respective mutually opposing substantially parallel guide surfaces (5,9) along which the outer core blocks (15) and wedge blocks (20) respectively slide in response to operation of the clamping means (30).

REPLACEMENT SHEET

10 FEB 1998

SET OF TWO DIES FOR A CRIMPING TOOL

ABSTRACT

An apparatus (1) for forming a rim (2) on a tube (3). The apparatus (1) comprises a die block (4), a locking plate (6) supported in fixed spaced apart relationship with respect to the die block (4), an inner core block (12) extending intermediate the die block (4) and the locking plate (6), and a pair of complementary outer core blocks (15) slidably disposed around the inner core block (12) intermediate the die block (4) and the locking plate (6) such that the die block (4) and core blocks (12,15) together in a closed position form a die cavity (18). A pair of wedge blocks (20) are respectively disposed intermediate the outer core blocks (15) and the locking plate (6), and clamping means (30) are operable selectively and progressively to move the outer core blocks (15) together into the closed position thereby clamping the tube against the inner core block (12) such that an exposed end of the tube extends into the die cavity (18). The clamping means (30) are further operable to drive the wedge blocks (20) between the locking plate (6) and the respective core blocks to wedge the core blocks against the die block (4) in the closed position. The apparatus (1) also includes injection means to inject hot thermoplastic material into the die cavity (18) thereby forming a peripheral rim thermoplastically bonded to the exposed end of the tube

Figure 1

REPLACEMENT

11 FEB 1998