



- (51) **International Patent Classification:** Not classified
- (21) **International Application Number:**
PCT/GB2012/050066
- (22) **International Filing Date:**
13 January 2012 (13.01.2012)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
1100543.6 13 January 2011 (13.01.2011) GB
- (71) **Applicant (for all designated States except US):** **DOWN-HOLE PRODUCTS LIMITED** [GB/GB]; Badentoy Road, Badentoy Park, Portlethen, Aberdeen, AB12 4YA (GB).
- (72) **Inventors; and**
- (75) **Inventors/Applicants (for US only):** **KIRK, Andrew** [GB/GB]; Braikley Farm House, Methlick, Aberdeenshire, AB41 7HB (GB). **KIRK, Ian** [GB/GB]; Lindsos, 131 North Deeside Road, Aberdeen, AB13 0JF (GB).
- (74) **Agent:** **MURGITROYD & COMPANY**; Scotland House, 165-169 Scotland Street, Glasgow, Strathclyde G5 8PL (GB).


(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) **Title:** CENTRALISER



(57) **Abstract:** A centraliser is disclosed for an oil, gas or water well, the centraliser having a body, and the body having a bore with an axis, the bore being configured to receive a tubular to be centraliser, the body having at least one resilient device configured to extend radially from the axis of the bore, wherein the body has at least one collar member extending radially inwards from the centraliser body adjacent to an end of the body. The collar can be formed separately from the body and attached subsequently, so that the body and the resilient device can optionally be formed in a single stamping or forming step from a single sheet of resilient material. The collars (typically at each end) are typically fixed co-axially in the bore so as to be resistant to axial movement of the collar member within the bore relative to the body of the centraliser, and can be retained in the body by radially extending a lip formed by forcing material at the ends of the body radially inwards into the bore to retain the collar. The body is typically adapted to receive within the bore at least one anchoring device for connection to the tubular, and the anchoring device is configured to engage the collar member within the bore of the body so that relative movement of the centraliser and the tubular is restricted once the anchoring device is fixed to the tubular and the anchoring device engages the collar member. A method of centralising a tubular in a borehole for an oil, gas or water well, and a method of making a centraliser for centralising a tubular in an oil, gas or water well are also disclosed.