

SEALED DERRICK STRUCTURE FOR POLAR VESSELS

CROSS-REFERENCE(S) TO RELATED APPLICATION

This application claims priority of Korean Utility Model Registration No. 20-
5 2010-0011352, filed on November 4, 2010, in the Korean Intellectual Property Office,
which is hereby incorporated by reference in its entirety.

BACKGROUND OF THE INVENTION

10 **Field of the Invention**

The present invention relates to an enclosed derrick structure of an arctic ship, and more particularly, to an enclosed derrick structure of an arctic ship, which provides an installation space for an exhaust unit at an upper portion of an enclosed derrick.

15 **Description of the Related Art**

Due to the rapid international industrialization and industrial development, the use of the earth's resources, such as oil, is gradually increasing. Accordingly, stable production and supply of oil is emerging as a very important worldwide issue.

For this reason, much attention has recently been paid to development of small
20 marginal fields or deep-sea oil fields, which have been ignored because of their low economic feasibility. Therefore, with the development of offshore drilling techniques, drill ships equipped with drilling equipment suitable for development of such oil fields have been developed.

In a conventional offshore drilling, rig ships or fixed type platforms have been
25 mainly used, which can be moved only by tugboats and are anchored at a position on the sea using a mooring gear to conduct an oil drilling operation. In recent years, however, so-called drill ships have been developed and used for offshore drilling. The drill ships are provided with advanced drilling equipments and have structures similar to typical

ships such that they can make a voyage using their own power. Since drill ships have to frequently move in order for development of small marginal fields, they are constructed to make a voyage using their own power, without assistance of tugboats.

5 Meanwhile, a moonpool is formed at the center of a rig ship, a fixed type platform or a drill ship, such that a riser or a drill pipe is vertically movable through the moonpool. In addition, a derrick in which a variety of drilling equipments are integrated is installed on a deck.

SUMMARY OF THE INVENTION

10 Embodiments of the present invention are directed to an enclosed derrick structure of an arctic ship, in which an upper portion of an enclosed derrick is gradually widened upwardly, thereby facilitating equipment installation and maintenance of a crown block platform.

15 Meanwhile, in order for drilling of natural resources in extremely cold regions such as arctic regions, arctic rig ships, fixed type arctic platforms, and arctic ships such as arctic drill ships have been built. Such arctic ships may be constructed to have an enclosed area in almost all zones in order to prevent freezing in extremely low temperature environments and ensure the smooth operation of equipments and crews' safety.

20 In particular, a derrick and a moonpool of an arctic ship are enclosed in order to protect internal equipments and workers. A ventilating system may be installed in the enclosed derrick and the enclosed moonpool in order for protection and ventilation of the inner spaces thereof. In particular, in order to meet a rule and regulation in an extremely low temperature region, it is preferable that the ventilating system supplies
25 heated air to the derrick and the moonpool, and exhausts cooled air to the exterior through an upper portion of the derrick. In this case, a crown block section is formed at the upper portion of the derrick, and a crown block is installed inside the crown block section. The crown block section may be formed in a conical shape which becomes

narrower upwardly. A plurality of exhaust fans may be installed inside the crown block section.

However, due to the structural shape of the conical crown block section that becomes narrower upwardly, such an enclosed derrick is weak to accessibility. Thus, it is difficult to install and maintain the exhaust fan, and the inner spaces of the enclosed derrick and the enclosed moonpool may not be effectively protected. Moreover, smooth ventilation may not be maintained.

According to an aspect of the present invention, a drill ship includes: an enclosed derrick; a crown block section disposed at an upper portion of the enclosed derrick such that a crown block is installed and an installation workspace is formed thereinside; an exhaust unit installed in the installation workspace to communicate with the exterior; a drill floor on which the enclosed derrick is disposed; an enclosed moonpool coupled to communicate with a lower portion of the enclosed derrick; and a supply unit disposed at the outside of the drill floor to supply outside air to the enclosed moonpool.

The width of the crown block section may be gradually widened upwardly, and the width of the installation workspace may be gradually widened upwardly.

A pair of inclined planes may be symmetrically formed on both sides of the crown block, such that a lower circumference of the crown block is formed to be narrower than an upper circumference thereof.

A pair of inclined planes may be symmetrically formed on both sides of the crown block section, such that a lower circumference of the crown block section is formed to be wider than an upper circumference thereof.

A crown block platform for installation of the crown block may be formed on the bottom of the crown block section.

The exhaust unit may include: an exhaust port provided in a side of the crown block to communicate with the exterior; an exhaust fan coupled to an inner side of the exhaust port; and a first open/close valve installed at a downstream side of the exhaust fan to selectively allow the exhaust of inside air.

The supply unit may include: an inlet port into which the outside air flows; a heater installed adjacent to the inlet port; a supply fan coupled to the inlet port to supply
5 the outside air; and a second open/close valve installed at a downstream side of the supply fan to selectively allow the inflow of the outside air.

The enclosed derrick structure may further include a supply pipe coupled from the second open/close valve to the enclosed moonpool, such that the outside air from the supply fan is supplied to the enclosed moonpool.

10 According to another embodiment of the present invention, an enclosed derrick structure of an arctic ship is characterized in that an exhaust unit is installed at an upper inner side of an enclosed derrick.

An installation workspace whose width is gradually widened upwardly may be formed at an upper portion of the enclosed derrick, and a crown block may be installed
15 in the installation workspace. A crown block platform for installation and maintenance of the exhaust unit may be disposed at an upper portion of the enclosed derrick.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view illustrating an enclosed derrick structure of an arctic
20 ship according to an embodiment of the present invention.

FIG. 2 is a cross-sectional view illustrating the enclosed derrick structure of the arctic ship and a ventilating system installed therein according to the embodiment of the present invention.

<Reference Numerals>

25	10: enclosed derrick	15: enclosed moonpool
	20: crown block section	21: inclined plane
	25: crown block platform	30: exhaust unit
	31: exhaust port	32: exhaust fan

33: first open/close valve	40: supply unit
41: inlet port	42: supply fan
43: heater	44: second open/close valve
50: installation workspace	

5

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

Exemplary embodiments of the present invention will be described below in detail with reference to the accompanying drawings.

FIGS. 1 and 2 illustrate an enclosed derrick structure of an arctic ship according to an embodiment of the present invention.

As illustrated in FIGS. 1 and 2, the enclosed derrick structure according to the embodiment of the present invention includes an enclosed derrick 10 installed in an arctic ship, and an enclosed moonpool 15 coupled to a lower portion of the enclosed derrick 10.

The enclosed derrick 10 and the enclosed moonpool 15 are coupled such that inner spaces 10a and 15b thereof communicate with each other. The enclosed derrick 10 is disposed on a drill floor 11 of the ship, and the enclosed moonpool 15 is disposed under the drill floor 11.

An outer wall of the enclosed derrick 10 is formed in an enclosed structure. The outer wall of the enclosed derrick 10 may be made of a fiberglass reinforced polymer (FRP), a stainless steel sheet (SUS sheet), a zinc alloy structure, or a sandwich panel. Enclosed tunnels 17 and 19 are provided at sides of the enclosed derrick 10. Openings are formed at the ends of the enclosed tunnels 17 and 19, such that equipment such as a riser can be passed therethrough. The enclosed tunnels 17 and 19 are adjacent to riser tensioner rooms 16.

Supply units 40 are installed outside the enclosed derrick 10 to supply outside air from the outside of the enclosed derrick 10 to an inner space 15a of the enclosed moonpool 15 or an inner space 10a of the enclosed derrick 10.

According to an embodiment, the supply unit 40 includes one or more inlet ports 41 installed at the outside of the drill floor 11, one or more supply fans 42 coupled to the inlet ports 41, one or more heaters 43 installed adjacent to the inlet ports 41, and one or more second open/close valves 44 installed at a downstream side of the supply fans 42 to
5 selectively allow the inflow of the outside air.

The inlet port 41 is installed at a roof (13) side of the riser tensioner room 16, and the outside air is introduced through the inlet port 41.

The supply fan 42 is coupled to a lower portion of the inlet port 41 and configured to forcibly blow the outside air to the inner space 15a of the enclosed moonpool 15.
10 The outside air forcibly blown by the supply fan 42 may be supplied through a supply pipe 45 to the inner space 15a of the enclosed moonpool 15 or the lower portion of the inner space 10a of the enclosed derrick 10.

When a temperature is low in an extremely cold region (in particular, below 0°C like a winter season), the heater 43 heats the outside air introduced through the inlet port
15 41. The heated air is supplied to the inner spaces 15a and 10a of the moonpool 15 and the derrick 10 by the supply fan 42. Accordingly, internal equipments, workers, and working conditions can be safely protected and maintained from external extreme environments.

The second open/close valve 44 may be selectively opened or closed to block an
20 air flow in the event of a fire or other emergency or in the repair of the supply fan 42.

Meanwhile, an exhaust unit 30 is installed at an upper portion of the enclosed derrick 10. When the outside air is supplied to the inner space 15a of the moonpool 15 by the supply unit 40, the exhaust unit 30 guides the outside air to flow upwardly from the inner space 15a of the enclosed moonpool 15 to the upper portion of the inner space
25 10a of the enclosed derrick 10.

The upper portion of the enclosed derrick 10 forms a crown block section 20. A crown block (not shown) is installed inside the crown block section 20. The width of the crown block section 20 is gradually widened upwardly, and thus, an installation

workspace 50 is formed inside the crown block section 20. In particular, an inclined plane 21 is provided in at least one side of the crown block section 20, and the exhaust unit 30 is installed on the inclined plane 21. In addition, according to the embodiment of FIGS. 1 and 2, it is preferable that a pair of inclined planes 21 is symmetrically
5 formed on both sides of the crown block section 20, and the exhaust units 30 are installed on the respective inclined planes 21.

The lower portion of the installation workspace 50 communicates with the inner space 10a of the derrick 10. A crown block platform 25 is installed to cross the lower portion of the installation workspace 50. The crown block (not shown) is installed on
10 the crown block platform 25.

As the crown block section 20 whose upper width becomes gradually wider is installed at the upper portion of the enclosed derrick 10, the installation workspace 50 formed inside the crown block section 20 is gradually widened upwardly. Accordingly, the installation workspace 50 provides a space enough to install the exhaust unit 30 on
15 the side of the crown block section 20 by using the crown block platform 25, installed in the installation workspace 50, and to allow a worker to perform a maintenance task on the exhaust unit 30. Hence, the worker can perform the maintenance task effectively and safely.

By installing the exhaust unit 30 at the upper portion of the enclosed derrick 10, an
20 effective air flow is achieved within the enclosed derrick 10 and the enclosed moonpool 15. Therefore, internal equipments, workers, and working conditions can be protected and maintained safely and effectively.

The exhaust unit 30 includes one or more exhaust ports 31 installed in the inclined plane 21, and one or more exhaust fans 32 coupled to the exhaust ports 31. The
25 exhaust fan 32 is installed within the crown block section 20 and is coupled to a first open/close valve 33. The first open/close valve 33 may be selectively opened or closed to block an air flow in the event of a fire or other emergency or in the repair of the exhaust fan 32.

As described above, since the crown block section 20 whose upper width becomes gradually wider is installed at the upper portion of the enclosed derrick 10, the crown block platform 25 can be utilized without additional installation of ducts, and a workspace enough to install the exhaust unit 30 can be provided. Therefore, the worker
5 can easily install the exhaust unit 30 at the upper portion of the enclosed derrick 10 and can more effectively perform the maintenance task on the exhaust unit 30. Moreover, the worker's safety can be improved.

According to the embodiments of the present invention, since outside air is supplied to the enclosed moonpool 15 and is exhausted through the upper portion of the
10 enclosed derrick 10, the air flow from the enclosed moonpool 15 to the upper portion of the enclosed derrick 10 is effectively achieved. Therefore, internal equipments, workers, and working conditions within the enclosed derrick 10 can be safely protected and maintained from external extreme environments.

According to the embodiments of the present invention, since the crown block
15 section 20 whose upper width becomes gradually wider is installed at the upper portion of the enclosed derrick, the exhaust unit can be installed at the upper portion of the enclosed derrick by utilizing the crown block platform. Therefore, the installation costs for additional ducts can be saved, and the worker's safety can be improved.

In addition, the space for the installation of the exhaust fan and the workspace for
20 the maintenance of the exhaust fan can be provided at the upper portion of the enclosed derrick.

While the embodiments of the present invention has been described with reference to the specific embodiments, it will be apparent to those skilled in the art that various changes and modifications may be made without departing from the spirit and scope of
25 the invention as defined in the following claims.

WHAT IS CLAIMED IS:

1. A drill ship, comprising:
an enclosed derrick;
5 a crown block section disposed at an upper portion of the enclosed derrick such that a crown block is installed and an installation workspace is formed thereinside;
an exhaust unit installed in the installation workspace to communicate with the exterior;
a drill floor on which the enclosed derrick is disposed;
an enclosed moonpool coupled to communicate with a lower portion of the enclosed derrick;
10 and
a supply unit disposed at the outside of the drill floor to supply outside air to the enclosed moonpool.
2. The drill ship according to claim 1, wherein the width of the crown block section is
15 gradually widened upwardly, and the width of the installation workspace is gradually widened upwardly.
3. The drill ship according to claim 1, wherein the crown block section has one or more inclined planes on one or more side thereof.
20
4. The drill ship according to claim 2, wherein a pair of inclined planes are symmetrically formed on both sides of the crown block section, such that an upper circumference of the crown block section is formed to be wider than a lower circumference thereof.
- 25 5. The drill ship according to claim 1, wherein a crown block platform for installation of the crown block is formed on the bottom of the crown block section.
6. The drill ship according to claim 1, wherein the exhaust unit comprises:
an exhaust port provided in a side of the crown block to communicate with the

exterior;

an exhaust fan coupled to an inner side of the exhaust port; and

a first open/close valve installed at a downstream side of the exhaust fan to selectively allow the exhaust of inside air.

5

7. The drill ship according to claim 1, wherein the supply unit comprises:

an inlet port into which the outside air flows;

a heater installed adjacent to the inlet port;

a supply fan coupled to the inlet port to supply the outside air; and

10 a second open/close valve installed at a downstream side of the supply fan to selectively allow the inflow of the outside air.

8. The drill ship according to claim 7, further comprising:

a supply pipe coupled from the second open/close valve to the enclosed moonpool, such that the

15 outside air from the supply fan is supplied to the enclosed moonpool.

20