

Description

The invention relates to cathode-ray tubes.

A color television picture tube is a CRT which comprises an evacuated glass envelope including a viewing window which carries a luminescent viewing screen, and a glass neck which houses an electron gun mount assembly for producing one or more electron beams for selectively scanning the viewing screen. Each gun of the mount comprises a cathode and a plurality of electrodes supported as a unit in spaced tandem relation from at least two elongated, longitudinally-oriented support rods, which are usually in the form of glass beads. The beads have extended surfaces closely spaced from and facing the inner surface of the glass neck. The beads usually extend from the region close to the neck stem, where the ambient electric fields are small, to the region of the electrode to which the highest operating potential is applied, where the ambient electric fields are high during the operation of the tube. The spaces between the beads and the neck surfaces are channels in which leakage currents may travel from the stem region up to the region of the highest-potential electrode. These leakage currents are associated with blue glow in the neck glass, with charging of the neck surface, and with arcing or flashover in the neck.

Several expedients have been suggested for blocking or reducing these leakage currents. Coatings on the neck glass are partially effective in preventing arcing, but are burned through when arcing does occur. A metal wire or ribbon in the channel (partially or completely around the mount assembly) is also only partially effective in reducing arcing, because it is often bypassed due to its limited longitudinal extent, because the limited space between the bead and the neck may result in shorting problems, and because there is frequently field emission from the metal structure.

One other expedient, which has been found to be particularly effective, is disclosed in U.S. Pat. No. 4,288,719, issued to K.G. Hernqvist September 8, 1981. That patent discloses a CRT including a beaded electron gun mount assembly in which each glass bead has a rectangularly-shaped electrically-conductive metal coating on the bead surface facing the neck. It has been found, however, that when the electrodes of the electron gun are electrically processed, e.g., by spot-knocking, the electrically-conductive coatings are eroded, producing undesirable particles in the CRT. Spot-knocking is described in U.S. Pat. No. 4,214,798, issued to L.F. Hopen July 29, 1980.

Yet another expedient which has been effective is described in U.S. Pat. No. 4,567,400, issued to S.A. Opresko January 28, 1986. That patent discloses that the electrically-conductive coatings should be positioned opposite a focusing electrode and spaced a prescribed distance away from a gap between the end or anode electrode and the adjacent focusing electrode. Additionally, no portion of the electrically-conductive coatings should be opposite a claw on the focusing electrode. However, the coatings described in the patent adversely affect not only the degree of spot-knocking activity, i.e., the number of induced electrical discharges, but also the region of the electron gun mount assembly in which the discharges take place. In particular, the electrical activity during the spot-knocking process is typically seven times higher for CRT's with the electrically-conductive coatings on the insulating beads than for CRT's without the coatings. This high degree of electrical activity is known to generate bead, stem, and glass-neck particles which may cause blocked apertures in the shadow mask of the tube. In addition, the prior electrically-conducting coatings concentrate the spot-knocking activity in the low voltage region of the mount assembly. Thus, the spot-knocking activity in the high voltage region of the mount (between the anode electrode and the focusing electrode) is reduced, and the subsequent high voltage characteristics, i.e., leakage currents and afterglow, are not optimized.

The CRT according to the present invention has an electron gun mount assembly therein similar in construction to the prior CRT's disclosed in the above-referenced U.S. Pat. Nos. 4,288,719 and 4,567,400. As with the prior structures, the present electron gun mount assembly comprises means for generating at least one electron beam and a plurality of successively spaced-apart electrodes, including a screen grid electrode, a focusing electrode and an anode electrode, secured to one major surface of at least two longitudinally-extending insulating support beads. An opposite major surface of each of the support beads faces outwardly and has thereon an electrically-conducting coating located opposite the focusing electrode. Means are provided for applying suitable voltages to the electrodes to generate electrical activity within said electron gun mount assembly and along the beads thereof. The present structure differs from the prior structures in that the electrically-conducting coating on each of the beads has a longitudinal dimension d and is located in an area of minimum electrical activity along the beads and the center of said coating is longitudinally spaced by a distance of about $1.25 d$ from the end of the focusing electrode adjacent to the screen grid electrode.

In the drawings:

FIG. 1 is a broken-away, side, elevational view of the neck of a preferred CRT according to the invention.

FIG. 2 is a broken-away, front, elevational view along section line 2-2 of the neck of the CRT shown in FIG. 1.

FIG. 3 is a curve showing the relative spot-knocking activity along a portion of the electron gun.

FIGS. 1 and 2 show structural details of the neck of a color television picture tube. The structure of this CRT is conventional, except for the electron gun mount assembly.

The CRT includes an evacuated glass envelope 11 comprising a rectangular faceplate panel (not shown) sealed to a funnel (also not shown) having a neck 13 integrally attached thereto. A glass stem 15 having a plurality of leads or pins 17 therethrough is sealed to and closes the neck 13 at an end thereof. A base 19 is attached to the pins 17 outside the envelope 11. The panel includes a viewing window which carries on its inner surface a luminescent viewing screen comprising phosphor lines extending in the direction of the minor axis thereof, which is the vertical direction under normal viewing conditions.

An in-line, beaded, bipotential, electron gun mount assembly 21, centrally mounted within the neck 13, is designed to generate and project three electron beams along coplanar convergent paths to the viewing screen. The mount assembly comprises two glass support rods or beads 23a and 23b to which the various electrodes are secured and supported, to form a coherent unit in a manner commonly used in the art. These electrodes include three substantially equally transversely spaced coplanar cathodes 25 (one for producing each beam), a control-grid electrode (also referred to as G_1) 27, a screen grid electrode (also referred to as G_2) 29, a focusing electrode (also referred to as G_3) 31, an anode electrode (also referred to as G_4) 33, and a shield cup 35, longitudinally spaced in that order by the beads 23a and 23b. The various electrodes of the mount assembly 21 are electrically connected to the pins 17 either directly or through metal ribbons 37. The mount assembly 21 is held in a predetermined position in the neck 13 on the pins 17 and with snubbers 39, which press on and make contact with an electrically-conducting internal coating 41 on the inside surface of the neck 13. The internal coating 41 extends over the inside surface of the funnel and connects to an anode button (not shown).

Each of the beads 23a and 23b is about 10 mm (millimeters) wide by 50 mm long and carries an electrically-conducting coating 43a and 43b, respectively, on a portion of its surface facing and spaced from the inside surface of the neck 13. In this embodiment, each coating 43a and 43b is a metal resinate such as Hanovia Liquid Bright Platinum No. 5, which is marketed by Englehard Industries, Inc. East Newark, N.J. (U.S.A.). A resinate coating may be produced by any of the known processes, such as painting, screening, spraying or print transfer. The resinate-coated beads are heated to 500°C, in air, to volatilize organic matter and to cure the coating, and then they are cooled to room temperature.

The product is a coating comprising an alloy of platinum and gold that is tightly bonded to the outwardly facing surface of each of the beads 23a and 23b. Each coating 43a and 43b is substantially circular and has a diameter, d , of about 6.4 mm (1/4 inch), which is less than the full width of the bead. Each coating is about 10^{-5} cm (1000 Å) thick except at the edges, where it is tapered to a thickness of about 5×10^{-6} cm (500 Å). Each coating is floating electrically.

The tube may be operated in its normal way by applying operating voltages to the pins 17 and to the internal coating 41 through the anode button. These voltages are, for example, typically less than 100 volts on G_1 , about 600 volts on G_2 , about 8,000 volts on G_3 , and about 30,000 volts on G_4 . Because of the beaded structure as described, the regions between the beads and the neck, which can be called bead channels 47, behave differently than the regions between the neck and the other parts of the mount assembly, which can be called gun channels 49. Arcing (flashover), if present, occurs in the bead channels 47, when the tube is operating and the conducting coatings 43a and 43b are absent. However, with the conductive coatings present, as shown in FIGS. 1 and 2, arcing in these channels is substantially entirely suppressed.

The G_3 or focusing electrode 31 comprises a first substantially rectangular, tub-shaped cup 51 disposed towards the G_4 or anode electrode 33 and a second substantially rectangular, tub-shaped cup 53 disposed towards the G_2 , which cups are joined together at their open ends by means of peripheral flanges 55 which include claws 56 for securing the cups 51 and 53 to the beads 23a and 23b. A first gap 57 having a gap width of about 1.25 ± 0.20 mm (50 ± 8 mils) is formed between the end of the first cup 51 and the G_4 . A second gap 59 extends between the opposite end of the second cup 53 and the G_2 . The second gap 59 has a gap width of about $0.84 \pm .05$ mm (33 ± 2 mils).

The embodiment shown in FIGS. 1 and 2 are distinguished from the embodiments of U.S. Pat. Nos. 4,288,719 and 4,567,400, op. cit., in that the center of the conducting coating 43a and 43b is spaced a predetermined distance of about 1.25 times the longitudinal dimension, d , from the end of the second cup 53 of the focusing electrode 31 adjacent to the second gap 59.

Preferably, the conducting coatings 43a and 43b are circular, so that no pointed corners are available to initiate electrical arcing or to generate particles. It has been determined that a coating diameter of about 6.4 mm (1/4 inch) is ideal, since it is smaller than the width (10 mm) of the support beads 23a and 23b, thus making the conducting coatings 43a and 43b independent of the location of the claws 56. As herein described, the coatings 43a and 43b are centered about 8 mm (0.31 inch) from the end of the second cup 53 adjacent to the second gap 59.

FIG. 3 is a curve showing the relative spot-knocking activity for conducting coatings 43a and 43b located at various positions along the beads 23a and 23b. The beads themselves are not shown; however, the relative locations of the anode electrode G4, focusing electrode G3 and screen grid electrode G2 are shown to scale. The curve has been normalized so that, at the peak of spot-knocking activity, a value of 1 has been assigned. One of the conducting coatings, 43a, is shown superposed on the curve at the area of minimum spot-knocking activity.

The spot-knocking is performed in the manner described in the above-referenced U.S. Pat. No. 4,214,798.

Briefly, the electron gun mount assembly elements comprising a heater, a cathode, a control electrode and a screen electrode are interconnected, and spot-knocking voltages in excess of normal operating voltages are applied between an anode and the interconnected gun elements. A focusing electrode is electrically floating during spot-knocking. The spot-knocking removes from the surfaces of the electrode projections burrs and/or particles which would later be sites for the field emission of electrons, during the normal operation of the CRT.

The size and location of the conducting coatings 43a, 43b strongly influence both the level of spot-knocking activity and its effectiveness. Reduction in the level of spot-knocking activity is advantageous, because a high activity level can damage the tube and create loose particles. The optimum position for the present conducting coatings 43a, 43b, on the beads 23a, 23b, is shown in FIG. 3 as centered around data point 3. The curve suggests that spot-knocking activity can be minimized by locating the conducting coatings 43a, 43b on the outwardly facing major surface of the beads 23a, 23b, over the focusing electrode, G3, so that the coatings are in an area of minimum electrical activity. The experimental data points, comparing relative spot-knocking activity for a conductive coating having a diameter of about 6.4 mm (1/4-inch) as a function of the distance that the center of the coatings is located from the anode electrode, G4, are listed in TABLE I. It should be noted that, in the vicinity of the gap 59 between the G2 and G3 electrodes, i.e., between data points 4 and 5, the electrical activity and the possibility of particle generation and/or electrical damage to the electron gun is greatest. This is in agreement with observations of the spot-knocking results on CRT's made with large area conducting coatings, such as those shown in FIGS. 1 and 2 of U.S. Pat. No. 4,567,400, op. cit.

The spot-knocking activity curve of FIG. 3 was constructed by counting the arcs generated during spot-knocking, visually determining the location of the arcs, and evaluating the post-spot-knocking performance of the processed CRT's.

TABLE I

DATA POINT	DISTANCE FROM G4 (MM)	SPOT-KNOCKING ACTIVITY
1	6.6	0.35
2	11.7	0.32
3	18.0	0.25
4	23.9	0.62
5	30.7	0.34

TABLE II compares the spot-knocking activity of different size conductive coatings (including uncoated support beads 23a and 23b), but with the location of the coating fixed at a distance of 12.7 mm from G4. Sample sizes ranged from 20 to 550 tubes. The "standard" conducting coatings are substantially rectangular in shape and have an area normalized to 1. The present circular conducting coatings have a normalized area of 0.3.

TABLE II

Coating Type	Normalized Area	Normalized Spot-knocking Activity ($\geq 1\mu\text{A}$)	Focus Leakage (@40kV)	Afterglow (@ <40kV)
Standard	1	1	78%	85%
Circular	0.3	0.44	43%	49%
None	0	0.17	--	

While CRT's having electron guns without conducting coatings showed very low spot-knocking activity, it is known from the work disclosed in U.S. 4,288,719, op. cit., that some type of conducting coating is required on the support beads of the electron gun mount assembly to suppress arcing and flashover during normal tube operation. The effectiveness of the present circular conducting coating, compared to the prior standard coating, was confirmed by analyzing the CRT's used to provide the information in TABLE II. The present circular conducting coatings 43a, 43b, provided a lower percentage of CRT's having focus leakage equal to or greater than one microampere at an anode voltage of 40 kilovolts, and a lower percentage of tubes exhibiting afterglow at an anode voltage of less than about 40 kilovolts, than did CRT's using a standard conducting coating of the type similar to that disclosed in the above-referenced U.S. Pat. Nos. 4,288,719 and 4,567,400. Afterglow is electron emission from the G3-G4 region of the electron gun which manifests itself as a visual pattern on the screen, after the CRT is turned off, but before the stored charge can dissipate. The reduced size and novel position of the present conducting coatings 43a, 43b show that, in general, spot-knocking is more effective with the present coating than with the prior conducting coating, and that tube performance, as measured by a decrease in leakage current and afterglow, is significantly improved.

Claims

1. A cathode-ray tube having a glass neck and an electron gun mount assembly in said neck, said mount assembly comprising means for generating at least one electron beam and a plurality of successively spaced-apart electrodes, including a screen grid electrode, a focusing electrode and an anode electrode, secured to one major surface of at least two longitudinally extending insulating support beads, an opposite major surface of each of said beads being outwardly facing and having thereon an electrically-conductive coating located opposite said focusing electrode, and means for applying suitable voltages to said electrodes to generate electrical activity within said electron gun mount assembly and along said beads thereof; characterized by said coating (43a, 43b) on each of said beads (23a, 23b) having a longitudinal dimension, d , and being located in an area of minimum electrical activity along said beads, the center of said coating being longitudinally spaced by a distance of about $1.25d$ from the end of said focusing electrode (31) adjacent to said screen grid electrode (29).
2. The cathode-ray tube defined in claim 1 characterized in that said conductive coating (43a, 43b) has a circular shape.
3. The cathode-ray tube defined in claim 2, characterized in that said dimension, d , of said coating (43a, 43b) is about 6.4mm (1/4 inch).
4. The cathode-ray tube defined in Claim 1, 2 or 3 characterized in that said coating (43a, 43b) is electrically floating.

Patentansprüche

1. Kathodenstrahlröhre mit einem Glashals und einem Elektronenkanonen-Aufbau in dem Hals, wobei der Aufbau ein Mittel zum Erzeugen mindestens eines Elektronenstrahls und eine Mehrzahl von aufeinanderfolgend beabstandeten Elektroden enthält, beinhaltend eine Schirmgitter-Elektrode, eine Fokussier-

**TABLE II**

5	Coating Type	Normalized Area	Normalized Spot-knocking ($\geq 1\mu\text{A}$. @40kV) Activity	Focus Leakage ($\geq 1\mu\text{A}$. @40kV)	Afterglow (@ <40kV)
	Standard	1	1	78%	85%
10	Circular	0.3	0.44	43%	49%
	None	0	0.17	--	

15 While CRT's having electron guns without conducting coatings showed very low spot-knocking activity, it is known from the work disclosed in U.S. 4,288,719, op. cit., that some type of conducting coating is required on the support beads of the electron gun mount assembly to suppress arcing and flashover during normal tube operation. The effectiveness of the present circular conducting coating, compared to the prior standard coating, was confirmed by analyzing the CRT's used to provide the information in TABLE II. The present circular conducting coatings 43a, 43b, provided a lower percentage of CRT's having focus leakage equal to or greater than one microampere at an anode voltage of 40 kilovolts, and a lower percentage of tubes exhibiting afterglow at an anode voltage of less than about 40 kilovolts, than did CRT's using a standard conducting coating of the type similar to that disclosed in the above-referenced U.S. Pat. Nos. 4,288,719 and 4,567,400. Afterglow is electron emission from the G3-G4 region of the electron gun which manifests itself as a visual pattern on the screen, after the CRT is turned off, but before the stored charge can dissipate. The reduced size and novel position of the present conducting coatings 43a, 43b show that, in general, spot-knocking is more effective with the present coating than with the prior conducting coating, and that tube performance, as measured by a decrease in leakage current and afterglow, is significantly improved.

30 Claims

1. A cathode-ray tube having a glass neck and an electron gun mount assembly in said neck, said mount assembly comprising means for generating at least one electron beam and a plurality of successively spaced-apart electrodes, including a screen grid electrode, a focusing electrode and an anode electrode, secured to one major surface of at least two longitudinally extending insulating support beads, an opposite major surface of each of said beads being outwardly facing and having thereon an electrically-conductive coating located opposite said focusing electrode, and means for applying suitable voltages to said electrodes to generate electrical activity within said electron gun mount assembly and along said beads thereof; characterized by said coating (43a, 43b) on each of said beads (23a, 23b) having a longitudinal dimension, d , and being located in an area of minimum electrical activity along said beads, the center of said coating being longitudinally spaced by a distance of about $1.25d$ from the end of said focusing electrode (31) adjacent to said screen grid electrode (29).
2. The cathode-ray tube defined in claim 1 characterized in that said conductive coating (43a, 43b) has a circular shape.
3. The cathode-ray tube defined in claim 2, characterized in that said dimension, d , of said coating (43a, 43b) is about 6.4mm (1/4 inch).
4. The cathode-ray tube defined in Claim 1, 2 or 3 characterized in that said coating (43a, 43b) is electrically floating.

Patentansprüche

1. Kathodenstrahlröhre mit einem Glashals und einem Elektronenkanonen-Aufbau in dem Hals, wobei der Aufbau ein Mittel zum Erzeugen mindestens eines Elektronenstrahls und eine Mehrzahl von aufeinanderfolgend beabstandeten Elektroden enthält, beinhaltend eine Schirmgitter-Elektrode, eine Fokussier-



elektrode und eine Anodenelektrode, die an einer Hauptoberfläche von zumindest zwei sich in Längsrichtung erstreckenden Isolier-Stützperlen angeordnet sind, wobei eine gegenüberliegende Hauptoberfläche jeder der Perlen nach außen gerichtet ist und auf ihr eine elektrisch leitende Schicht gegenüber der Fokussierelektrode angeordnet ist, sowie ein Mittel zum Zuführen geeigneter Spannungen an die Elektroden, um elektrische Aktivität innerhalb des Elektronenkanonen-Aufbaus und längs ihrer Perlen zu erzeugen, dadurch gekennzeichnet, daß die Schicht (43a, 43b) auf jeder der Perlen (23a, 23b) eine Längserstreckung d hat und in einem Bereich minimaler elektrischer Aktivität entlang der Perlen angeordnet ist, wobei die Mitte der Schicht in Längsrichtung einen Abstand von etwa $1,25d$ von dem Ende der Fokussierelektrode (31), benachbart der Schirmgitter-Elektrode (29), hat.

2. Kathodenstrahlröhre nach Anspruch 1, dadurch gekennzeichnet, daß die leitfähige Schicht (43a, 43b) kreisförmig ist.
3. Kathodenstrahlröhre nach Anspruch 2, dadurch gekennzeichnet, daß die Dimension d der Schicht (43a, 43b) etwa 6,4 mm (1/4 inch) ist.
4. Kathodenstrahlröhre nach Anspruch 1, 2 oder 3 dadurch gekennzeichnet, daß die Schicht (43a, 43b) elektrisch nicht angeschlossen ist (electrically "floating").

Revendications

1. Tube à rayons cathodiques comportant un col de verre et un ensemble de montage de canon à électrons dans ledit col, ledit ensemble de montage comprenant un moyen pour générer au moins un faisceau d'électrons et une pluralité d'électrodes disposées à distance l'une de l'autre, incluant une électrode de grille-écran, une électrode de focalisation et une électrode d'anode, fixées à une surface principale d'au moins deux perles de support isolantes s'étendant longitudinalement, une surface principale opposée de chacune desdites perles se trouvant face vers l'extérieur et comportant sur elle un revêtement électriquement conducteur placé à l'opposé de ladite électrode de focalisation, et un moyen pour appliquer des tensions convenables auxdites électrodes pour générer une activité électrique à l'intérieur dudit ensemble de montage du canon à électrons et le long de ses dites perles; caractérisé en ce que ledit revêtement (43a, 43b) sur chacune desdites perles (23a, 23b) présente une dimension longitudinale, d , et est placé dans une zone d'activité électrique minimale le long desdites perles, le centre dudit revêtement étant espacé longitudinalement d'une distance d'environ $1,25 d$ de l'extrémité de ladite électrode de focalisation (31) adjacente à ladite électrode de grille-écran (29).
2. Tube à rayons cathodiques défini selon la revendication 1, caractérisé en ce que ledit revêtement conducteur (43a, 43b) présente une forme circulaire.
3. Tube à rayon cathodique défini selon la revendication 2, caractérisé en ce que ladite dimension, d , dudit revêtement (43a, 43b) est d'environ 6,4 mm (1/4 de pouce).
4. Tube à rayons cathodiques selon la revendication 1 ou 2, caractérisé en ce que ledit revêtement (43a, 43b) est électriquement isolé.