

Appliance for heating meals

The invention relates to a device for heating up meals. The device comprises a housing which can be closed by means of a door and shields the surroundings from electromagnetic waves. One or more functional trays are held in the interior of the housing. There are, in turn, one or more induction coils in a functional tray of this type. Heating can be performed within the alternating electromagnetic fields of the induction coils when articles (for example containers), which are suitable for this purpose and are at least partially composed of materials which can be inductively heated up or substances of this type, are arranged within said fields.

The invention is particularly suitable when pre-prepared meals which are to be consumed have to be heated up quickly and with increased energy efficiency and increased quality. Areas of use particularly predetermined for this are, for example, hospitals and also vehicles, preferably aircraft. However, increased requirements in terms of undesirable electromagnetic fields or waves are placed on the devices in these areas since these fields or waves may have an undesirable effect on electronic devices and this, in turn, may lead to damage to the devices or the vehicles or else to human health or life.

Although this problem can be solved using known solutions, as described in DE 198 18 831 A1 for example, by means of a metallic housing in the majority of cases, the door region remains critical. It is therefore necessary to ensure that no electromagnetic waves can ever escape from the gaps around the door or to be absolutely sure that no such waves are emitted

from open door openings.

Known solutions to this problem also have disadvantages in terms of handling for the operator and meals being
5 selectively heated up in a very largely automated manner.

Localized overheating can be prevented only with difficulty and ineffectively, and so at least the
10 quality of the meals which are heated up may be impaired.

The object of the invention is therefore to propose possible ways in which the operational reliability of
15 devices for inductively heating up meals can be increased.

According to the invention, this object is achieved by a device which has the features of claim 1.

20 Advantageous refinements and developments can be achieved with the features mentioned in the dependent claims.

25 The device according to the invention has a housing which, apart from a door opening which can be closed, is closed and is formed in such a way that electromagnetic waves, which are emitted by induction coils for heating up meals or else by other generating
30 electromagnetic waves for example, are shielded, and it is accordingly possible to prevent them having any effect outside the device. The entire housing or just an inner wall may therefore be composed of a suitable material.

35 In order to prevent electromagnetic waves undesirably escaping into the surroundings through the door region, both when the door is open and when it is closed,

electrical conductors, which are arranged on functional trays which contain induction coils, are provided according to the invention.

5 At least one electrical conductor can be provided on an end face, which points in the direction of the door, of a functional tray. One or each of a plurality of electrical conductors has to be connected to the local potential, housing potential and/or ground potential in
10 order to maintain an equipotential, so that said electrical conductor also forms a shield for electromagnetic waves in conjunction with the shielding housing. The respective potential connection depends substantially on where the device is used.

15

The electrical conductors should be routed over the entire length of an end face of a functional tray. They should also advantageously be routed at least further along the adjoining side faces which are oriented in
20 the direction which is orthogonal to the end face.

The electrical conductors can be fixed to the respective functional tray by interlocking, force-fitting or cohesive bonding, combinations of these
25 types of connection also being possible.

The electrical conductors may be in the form of metal profiles, for example angled or U-profiles, integrated in this region of functional trays, or applied in the
30 form of an electrically conducting coating.

However, it is also possible to fix electrical conductors to the inner face of a door, so that when the door is closed they are positioned in relation to
35 end faces of functional trays and can fulfill their shielding effect.

It is not absolutely necessary to provide a shielding

electrical conductor on each functional tray within a device, but it is instead sufficient for minimum separations to be complied with. The maximum distance between an electrical conductor and the housing or else
5 an adjacent electrical conductor should therefore not be greater than 500 mm, preferably not greater than 300 mm.

The distance should also not be greater than $1/3$,
10 preferably $1/5$, of the antenna separation specified in EURO CAE ED-14 D/RTLA DO-160 (C, D or E), section 21.

This can be readily implemented when a plurality of functional trays are securely installed in a device.

15

It is advantageous for the functional trays to be designed such that they can be removed, particularly to facilitate cleaning of the interior of the device and the functional trays. Functional trays formed in this
20 way can be inserted or removed through the door opening. Therefore, guide and/or supporting rails for the functional trays may be present on the inner wall of the device. The housing then contains connecting elements for each of the individual functional trays,
25 and connecting elements which complement the aforementioned connecting elements, for example corresponding connector strips, are present on the functional trays. The connection can be made when functional trays are inserted, so that the functional
30 trays are electrically connected to a power supply system and also to an electronic control system. A connection of this type can then also be used to maintain the equipotential to the electrical conductor.

35 Interchangeable functional trays of this type which can be inserted one above the other in a plurality of levels within a device also increase the operational flexibility. It is therefore possible to keep some

levels free and accordingly heat up meals contained in tall containers.

5 The functional trays may advantageously be formed in such a way that the one or more induction coil or coils is/are held between planar plate-like elements, which are made from a thermostable material, from above and below so as to be watertight on all sides. This material may be a thermostable plastic, a ceramic or
10 mica, for example. In addition to the temperature resistance, this material should be easy to clean and fulfill the requirements for food hygiene.

At least one planar, flat shielding element may
15 additionally be arranged in the interior of the device. It may be composed of a purely ferritic material or a material which contains ferrites. It is thus possible to achieve direction-specific shielding for electromagnetic waves.

20 An element of this type may be arranged on the floor of the device, for example. However, shielding elements may also be arranged above or below functional trays. It goes without saying that shielding elements should
25 not be arranged directly above a functional tray, at least not when it is to be used. It is possible to arrange said elements directly below functional trays however. It is even possible for a shielding element arranged in this way to be an integral component of a
30 functional tray.

Electrically conducting elements or regions, which can be heated up by the influence of alternating electromagnetic fields and/or by induction coils
35 heating up in a parasitic manner, can also be provided on the surface of functional trays. This heat can be used to heat up towels or baked goods at a somewhat lower temperature or power than meals which are to be

heated up. However, the inner wall of the device can also be heated up by thermal conduction, and this may be advantageous, for example, for catalytic self-cleaning of the interior. Also, bacteria or other germs
5 can therefore be killed when a temperature of 100°C is reached or exceeded.

One or more induction coils can be arranged within a functional tray and electrically connected up in a very
10 wide variety of ways. The induction coils may each have identical electrical and electromagnetic parameters. A plurality of induction coils be connected in series and/or in parallel.

15 Although these preconditions are met, the individual induction coils or else series connections of induction coils are not uniformly electrically loaded when meals are heated up. The respective load is also influenced by the electrical properties of the respective
20 containers which contain the meals. It is also necessary to take into account the fact that not all meals, which in relation to induction coils of a functional tray, have to be heated up to the same temperatures, or even have to be heated up at all.

25 The overheating already mentioned in the introduction should be avoided in particular. Temperature sensors or temperature sensor switching elements may therefore be present in, but also on, functional trays, these
30 temperature sensors or temperature sensor switching elements switching off one, a plurality of or all of the induction coils of a functional tray when predefined maximum temperatures are reached. Examples
35 of electrical or electronic elements which are suitable under these conditions and for this purpose are PTCs or bimetallic switches.

Induction coils can be switched off using sensor

elements by means of an electronic control system. Sensor switching elements can switch off one or more induction coils directly.

- 5 It is advantageous to heat up containers containing meals in conjunction with insert elements, particularly in the case of embodiments of functional trays having a multiplicity of induction coils which can be used in devices with increased operational flexibility.
- 10 Receptacles for containers are then formed in insert elements of this type, so that the containers can be positioned in relation to induction coils at least in two, or even better in three, dimensions. The arrangement of the receptacles can therefore be matched
- 15 to the position of the induction coils, and their shape and dimensions can be matched to the respective containers. They can therefore be positioned in an optimum position of an alternating electromagnetic field of induction coils for heating up meals in a
- 20 uniform, rapid and energy-saving manner.

Receptacles may be arranged on insert elements in such a way that they are not heated up there. This is possible by correspondingly positioning them outside

25 the alternating electromagnetic fields.

Coding elements may be present on insert elements, these coding elements allowing individual recognition of the respective insert element, including its

30 fittings or whether there are covers on insert elements or containers. In this case, the device contains detectors for the coding elements for the individual functional tray levels. After the respective insert element is recognized, meals can be heated up in a

35 locally deliberate manner by corresponding pre-programming for this insert element, for example by switching on specific induction coils and allowing other induction coils to be switched off. It is

therefore possible, for example, to either generate steam or not generate steam in a differentiated manner, with reference still to be made to possible ways of generating steam.

5

For the described purposes, it is also advantageous when the insert elements are inserted into a device in a defined manner and can be positioned in relation to a functional tray. For this purpose, there may be
10 profiled elements on the inner side walls or the side edges of functional trays, into which profiled elements profiles formed on the side edges of insert elements can be inserted. It is therefore possible to achieve a specific lateral separation between or central
15 positioning of insert elements in a very simple manner.

However, if the profiled elements and profiles are not identically formed on the diametrically opposite faces or sides or else are arranged at different distances
20 from the edge or the inner wall, the insert elements can be inserted into the device only in one direction.

The devices according to the invention can also be developed when they can be operated in combination with
25 a refrigeration system. In this way, it is possible to refrigerate meals in the device for specific time periods and then to heat them up later. A refrigeration system may have been integrated in the device with all the necessary components or some such components may
30 have been formed as an additional accessory, in which case a heat exchanger can be arranged within the device for refrigeration purposes and interfaces to an external refrigeration system should be present.

35 There may therefore be one or more supply lines for supplying a cooling medium, preferably cooled air, from the outside.

The cooling medium may advantageously be passed in and through between individual, selected functional trays in a controlled manner.

- 5 The invention will be described in greater detail below by way of example.

In the drawing:

- 10 Figure 1 shows a schematic, perspective illustration of one example of a device according to the invention;

- 15 Figure 2 schematically shows functional trays with electrical conductors for shielding electromagnetic waves;

Figure 3 shows a functional tray with induction coils;

- 20 Figure 4 shows one example of an insert element;

Figure 5 shows one example of a cavity for generating steam;

- 25 Figure 6 shows one example of a cover for insert elements;

Figure 7 shows two further examples of insert elements; and

30

Figure 8 schematically shows a guide for insert elements having profiled elements and profiles.

- 35 Figure 1 schematically shows one example of a device according to the invention. In this case, three functional trays 2 are arranged one above the other and oriented horizontally within the housing 1.

Electrical conductors 3 are provided on the end faces of the functional trays 2 which point in the direction of the door opening, these electrical conductors forming a reliable shield against electromagnetic waves reaching the surroundings of the device in this direction.

In this example, a refrigeration system 17 is also integrated in the device.

10

Detector strips 16 having discretely arranged individual detectors are present on the housing 1 for the functional trays 2 and can be used together with coding elements 23 on insert elements 5 to identify said insert elements.

In this case, a central control system 18 is arranged in an intermediate housing.

20 The functional trays 2 can be removed and inserted into the device again through the door opening.

To this end, the connecting elements which are mentioned in the general part of the description and can be inserted into connecting elements on the inner wall of the housing to produce electrical connections (not illustrated) are present on the end face of the functional trays 2 which parallel to end faces with electrical conductors 3.

30

Figure 2 schematically shows a possible arrangement and design of the electrical conductors 3 on functional trays 2 in the region of the door opening. In this case, the electrical conductors 3 are also routed along part of the side faces of the functional trays 2 and each individual electrical conductor 3 is separately connected to the local potential, housing potential or ground potential. The latter also applies for the

housing 1, including the door frame 1' (illustrated here) on the device.

Figure 3 illustrates one example of the arrangement of
5 induction coils 4 and temperature sensor switching elements 21 on a functional tray.

The induction coils 4' are arranged here in a regular pattern in two parallel rows, for example. The
10 temperature sensor switching elements 21 are arranged between the two rows of induction coils 4. In this case, their arrangement may differ from the illustration. However, the way in which they are arranged should take into account the electrical
15 connection of the induction coils 4 to one another.

Therefore, the series connection of in this case five induction coils or five pairs of induction coils 4, which are connected in series and are each connected in
20 parallel to one another again, can be taken into account.

Figure 4 is a perspective view of one example of an insert element 5. In this case, a total of four
25 receptacles 8 for containers (not illustrated) containing meals to be heated up are present on the insert element 5. The containers can be inserted into these receptacles and positioned in relation to induction coils 4 of a functional tray.

30

A ferromagnet in the form of a coding element 23 is fixed in a predefined position on the shown insert element 5. Its position can be detected by means of the detectors of a detector strip 16 and the insert element
35 5 can thus be individually identified and distinguished from insert elements 5 possibly formed or fitted in a different way. However, coding elements 23 may also be in the form of reflecting elements which allow

identification using discretely arranged optical detectors.

There are two cavities 9 in this insert element 5 and
5 these can be integrated into an insert element 5 or
else can be inserted into correspondingly formed
receptacles. These cavities 9 can be filled with water,
then likewise be heated within an alternating
electromagnetic field of induction coils 4 until steam
10 is formed.

In contrast to the examples which have been shown and
described, steam can also be generated externally
and/or centrally. The steam can then be passed to the
15 interior of the device via one feed line, preferably a
plurality of feed lines, which can be temporarily
closed. Supply lines for each functional tray level are
therefore preferred. In these cases, there may be
couplings on covers 10 for connection to steam feed
20 lines and the steam can be passed in an analogous
manner via channels 11 within an insert element 5
closed by a cover 10.

This steam can at least assist in heating up meals, it
25 being possible to use the steam to increase the quality
of heated-up meals.

A section through a cavity 9 of this type is
schematically illustrated in Figure 5. The example
30 shown has an opening at the top to allow steam to
escape and to fill said cavity with water. The lower
base here is formed from an electrically conducting
material which can be inductively heated, but may also
be correspondingly coated.

35

Such an arrangement and design of cavities 9 and insert
element 5 should be used in conjunction with a cover 10
as far as possible, as shown likewise by way of example

in Figure 6.

Channels 11 are formed on the lower side of the cover 10. The steam emerging from the cavities 9 can be passed through these channels 11, to the meals to be heated up, when the cover 10 with the downwardly pointing, open channels 11 has been fitted on an insert element 5, so that steam can be passed through the channels 11 directly to the meals which are to be heated up and are arranged in containers fixed in receptacles 8.

Insert elements 5 and covers 10 should be formed in such a way that they can be detachably connected to one another, with the intention being to produce a relatively tight seal when the cover 10 is fitted on an insert element 5. To this end, the cover 10 and insert element 5 may be provided with a suitable edge contour.

However, it should also be possible for the two elements to be connected to one another as far as possible in the opposite sense, that is to say for the cover 10 to be fixed to the insert element 5 in an interlocking manner from below.

It is also advantageous when covers 10 with insert elements 5 connected can be stacked one above the other in several layers and slipping within or of one complete stack of this type is at least impeded by the edge and/or surface contours of covers and insert elements 5.

Figure 7 schematically shows a lateral section illustration through two examples of insert elements 5.

In the upper illustration in Figure 7, electrically conducting elements 12, in which eddy currents can be induced for heating purposes, are arranged on the base

of an insert element 5. These elements 12 are arranged within a cavity 9' which is open by means of channels 11' and can be filled with water, so that steam is generated during heating and this steam can be used to
5 heat up meals or to heat up and moisten towels.

In the lower illustration, the elements 12 are arranged on the base, but they can also be temporarily fixed there.

10

Articles (illustrated on the left-hand side) which are to be heated up or containers (illustrated on the right-hand side) which contain meals and are composed of a material which cannot be inductively heated or can
15 be only poorly inductively heated (for example uncoated porcelain, plastic) can then be placed above these electrically conducting elements 12.

The electrically conducting elements 12 may also be in
20 the form of films or foils, emulsions or layers.

The intention in Figure 8 is to clearly show the defined insertion of insert elements 5 into a device according to the invention in a highly schematic form.

25

In this case, there are profiled elements 6 on the opposite sides of the inner wall of the housing 1 or on a functional tray 2. Downwardly directed open profiles 7 into which the profiled elements 6 can engage are
30 formed on the outer edges of an insert element 5 in the insertion direction along the corresponding outer edges. It is therefore possible to insert insert elements 5 above a functional tray 2 into a device according to the invention in a defined manner on the
35 correct side and to precisely position in three dimensions meals to be heated up, in order to generate steam and/or heat up articles within alternating electromagnetic fields.

One advantageous embodiment of insert elements 5 can also be explained using Figure 8.

5 In this case, a profiled section 8' which surrounds a receptacle 8 are formed on said receptacle and here may be in the form of a circumferential u-shaped groove.

As shown in Figure 8, it is therefore possible for dishes which can be closed by a cover to be inserted
10 into a receptacle 8 of insert elements 5. An edge which projects from the circumference of the container/dish can rest on part of the circumferential profiled section 8' here, so that the dish/container is kept at a specific distance above a functional tray 2. The
15 abovementioned optimum positioning within an alternating electromagnetic field can thus be ensured.

The circumferential profiled section 8' may be designed and dimensioned in such a way that a cover is raised
20 when the dish/container is inserted into a receptacle 8, and a chance to supply steam is thus created.

Steam can then be introduced through a gap between the inner circumferential edge of the profiled section 8'
25 and the edge of the cover.

Another possible way of supplying steam is indicated on one side of the illustration from Figure 8.

30 In this case, the cover which closes or else covers the dish/container does not extend directly as far as the base of the circumferential profiled section 8', so that steam can pass through the gap there into the interior of a dish/container.

35

As indicated in Figure 8, the formation of gaps at the lower edge of a cover only in regions may be sufficient to be able to provide openings for the introduction of

steam into the interior.

Patent claims

1. A device for heating up meals, in which one or more functional tray or trays is/are arranged within a housing which can be closed by a door and has a shielding effect for electromagnetic waves, where

functional trays (2) each contain at least one induction coil (4) for producing an alternating electromagnetic field within which heating can be achieved,

characterized in that an electrically conducting element (3) is arranged at end faces of functional trays (2) which are oriented in the direction of a door opening in the housing (1), and each electrically conducting element (3) is respectively connected to the local potential, housing potential and/or ground potential and forms a shield for electromagnetic waves.

20

2. The device as claimed in claim 1, characterized in that electrically conducting elements (3) are routed over the entire length of the respective end face of a functional tray (2).

25

3. The device as claimed in claim 1 or 2, characterized in that electrically conducting elements (3) are routed at least along regions of side faces of functional trays (2) which point in the direction which is orthogonal to the outwardly pointing end face.

30

4. The device as claimed in one of the preceding claims, characterized in that electrically conducting elements (3) are connected to functional trays (2) in an interlocking, force-fitting and/or cohesive manner.

35

5. The device as claimed in one of the preceding

claims,
characterized in that electrically conducting elements
(3) are in the form of U- or angled profiles, or
coatings, or are integrated in a functional tray (2).

5

6. The device as claimed in one of the preceding
claims,
characterized in that at least one electrically
conducting element (3) is fixed to a door of the
10 housing and is positioned so as to face an end face of
a functional tray (2) in the closed position.

7. The device as claimed in one of the preceding
claims,
15 characterized in that the distance between electrically
conducting elements (3) and the housing and/or
respectively an adjacent electrically conducting
element (3) is ≤ 500 mm.

20 8. The device as claimed in one of the preceding
claims,
characterized in that the housing (1) contains
connecting elements for complementary connecting
elements on functional trays (2) for the purpose of
25 producing an electrical connection.

9. A device as claimed in one of the preceding
claims,
characterized in that connecting elements for ensuring
30 that an equipotential difference is maintained are
present on the electrically conducting elements (3).

10. The device as claimed in one of the preceding
claims,
35 characterized in that elements or regions which can be
inductively heated up on functional trays (2) are
arranged within an alternating electromagnetic field of
induction coils (4).

11. The device as claimed in one of the preceding claims,
characterized in that sensor elements and/or sensor
switching elements are arranged within and/or on
5 functional trays (2).

12. The device as claimed in claim 11,
characterized in that there are temperature sensors or
temperature sensor switching elements (21).
10

13. The device as claimed in one of the preceding
claims,
characterized in that flat elements which shield
electromagnetic waves can be inserted into the interior
15 of the housing (1).

14. The device as claimed in claim as claimed in 13,
characterized in that shielding elements are connected
to a functional tray (2) or are an integral component
20 of functional trays (2).

15. The device as claimed in claim 13 or 14,
characterized in that the shielding elements are formed
from a ferritic material or have a material of this
25 type.

16. The device as claimed in one of the preceding
claims,
characterized in that heat-conducting elements are
30 present on the functional trays (2) and are in contact
with the inner wall of the housing.

17. The device as claimed in one of the preceding
claims,
35 characterized in that induction coils (4) of functional
trays (2) are held by means of thermally stable flat
elements.

18. The device as claimed in claim 17,
characterized in that the thermally stable flat
elements are substantially formed from mica.

5 19. The device as claimed in one of the preceding
claims,
characterized in that profiled elements (6) for guiding
and positioning insert elements (5) are present on
diametrically opposite outer edges of functional trays
10 (2) or of the inner wall of the housing (1), and
profiles (7) which are formed to complement the
profiled elements (6) are present on the insert
elements (5).

15 20. The device as claimed in claim 19,
characterized in that the profiled elements (6) and
profiles (7) differ at the two opposite sides.

20 21. The device as claimed in one of the preceding
claims,
characterized in that receptacles (8) for containers
containing meals and products to be heated are present
on the insert elements (5), so that these containers
can be positioned in relation to induction coils (4).

25 22. The device as claimed in one of the preceding
claims,
characterized in that cavities (9, 9') for generating
steam are formed on the insert elements (5) within
30 alternating electromagnetic fields of the induction
coils (4), or can be inserted into insert elements (5).

23. The device as claimed in one of the preceding
claims,
35 characterized in that the insert elements (5) can be
closed by a cover (10).

24. The device as claimed in one of the preceding

claims,
characterized in that the insert element (5) and cover
(10) can be temporarily connected in an interlocking
manner and/or can be stacked one above the other.

5

25. The device as claimed in one of the preceding
claims,
characterized in that channels (11) for conducting
steam emerging from the cavities (9) are formed the
10 cover (10) on that surface which points in the
direction of containers containing meals.

26. The device as claimed in one of the preceding
claims,
15 characterized in that elements (12) or regions (12)
which can be inductively heated up and can be
positioned within an alternating electromagnetic field
of induction coils (4) are present on insert elements
(5).

20

27. The device as claimed in one of the preceding
claims,
characterized in that coding elements (23) for
individual identification in the device are present on
25 insert elements (5) and/or covers (10).

28. The device as claimed in one of the preceding
claims,
characterized in that a refrigeration system (15) is
30 present on or integrated in the device.

29. The device as claimed in one of the preceding
claims,
characterized in that there is at least one connection
35 for supplying a cooling medium.

30. The device as claimed in one of the preceding
claims,

characterized in that the supply of cooling media between individual functional trays can be controlled.

31. The device as claimed in one of the preceding
5 claims,
characterized in that there is at least one delivery line for steam which is produced externally.