

PCT **World Organization for Intellectual Property**
International Office

International application published according to the Patent Cooperation Treaty (PCT)

(51) International patent classification 6:

E04C 5/06, E04B 5/43

A1

(11) International publication number: WO 99/32737

(43) International date of publication: July 1, 1999

(21) International file number: PCT/EP98/08031

(22) International date of application: December 10, 1998

(30) Priority dates:

197 56 358.9

December 18, 1997 DE

(71) Applicant (for all contracting states except the US):

DEHA ANKERSYSTEME GMBH&CO. KG (DE/DE); Breslauerstr. 3,
D-64521 Gross-Gerau, Germany

(72) Inventor; and

(75) Applicant/inventor (only for the US): ERNST, Peter (DE/DE); Lindenstr. 7, D-65795 Hattersheim, Germany, SCHRADER, Gerhard (DE/DE); An der Herrenwiese 14, D-60529 Frankfurt am Main, Germany

(74) Attorney: KATSCHER, Helmut, Fröbelweg 1, D-64291, Darmstadt, Germany

(81) Contracting states: CA, CZ, JP, NO, PL, SG, SI, SK, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published: With international search report.

Prior to termination of the approved term for changes of claims; publication is repeated if changes are submitted.

(54) Title: SHEARING REINFORCEMENT FOR FLAT CEILINGS AND DOWEL STRIP THEREFOR

[Drawing]

(57) Abstract

A shearing reinforcement arranged in a bearing area for flat ceilings, comprising several dowel strips (6) arranged in a substantially radial position with respect to a stay (2) and respectively consisting of a dowel rail (7) and several vertical, parallel and interspaced dowels. The dowels (8, 8') have a respective oblong shank (9, 9') and an enlarged head (10) at least on one end opposite to the rail. The diameter of the shanks (9) of the dowels (8), which are adjacent to the stay (2), is greater than the diameter of the shanks (9') of the dowels (8') which are located further away from the stay (2).