



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : E01F 13/00, 13/04, B66D 1/60, E05B 53/00	A1	(11) International Publication Number: WO 00/20692 (43) International Publication Date: 13 April 2000 (13.04.00)
(21) International Application Number: PCT/AU99/00846 (22) International Filing Date: 1 October 1999 (01.10.99) (30) Priority Data: PP 6306 1 October 1998 (01.10.98) AU PQ 1385 2 July 1999 (02.07.99) AU (71) Applicant (for all designated States except US): MATILDA PRODUCTS LTD. [AU/AU]; Level 42, 152 St. Georges Terrace, Perth, W.A. 6000 (AU). (72) Inventors; and (75) Inventors/Applicants (for US only): THOMPSON, Ian, Reginald [AU/AU]; 25 Juniper Way, Duncraig, W.A. 6023 (AU). SARICH, Ralph, Tony [AU/AU]; Level 42, 152 St. Georges Terrace, Perth, W.A. 6000 (AU). (74) Agent: WATERMARK PATENT & TRADEMARK ATTORNEYS; Durack Centre, 4th floor, 263 Adelaide Terrace, Perth, W.A. 6000 (AU).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: CABLE GATE (57) Abstract A gate for controlling passage through an opening including a first support means located on one side of the opening, a second support means located on the other side of the opening, at least one elongate member, having a first and a second end, extendable across the opening between the first and second support means; and a control means for releasing the at least one elongate member to thereby enable passage through the opening, and drawing in the elongate member to thereby restrict passage through the opening.		