

(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织
国际局

(43) 国际公布日
2024 年 2 月 8 日 (08.02.2024)



(10) 国际公布号
WO 2024/026645 A1

(51) 国际专利分类号:
H04W 72/23 (2023.01) *H04B 7/0456* (2017.01)
H04L 5/00 (2006.01) *H04B 7/06* (2006.01)

(21) 国际申请号: PCT/CN2022/109538

(22) 国际申请日: 2022 年 8 月 1 日 (01.08.2022)

(25) 申请语言: 中文

(26) 公布语言: 中文

(71) 申请人: 北京小米移动软件有限公司 (BEIJING XIAOMI MOBILE SOFTWARE CO., LTD.) [CN/CN]; 中国北京市海淀区西二旗中路 33 号院 6 号楼 8 层 018 号, Beijing 100085 (CN)。

(72) 发明人: 高雪媛 (GAO, Xueyuan); 中国北京市海淀区西二旗中路 33 号院 6 号楼 8 层 018 号, Beijing 100085 (CN)。

(74) 代理人: 北京三高永信知识产权代理有限公司 (BEIJING SAN GAO YONG XIN INTELLECTUAL PROPERTY AGENCY CO., LTD.); 中国北京市海淀区上地信息产业基地三街 1 号楼四层 C 段 457, Beijing 100085 (CN)。

(81) 指定国(除另有指明, 要求每一种可提供的国家保护): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CV, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IQ, IR, IS, IT, JM, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW。

(54) Title: INFORMATION INDICATION METHOD AND APPARATUS, MEDIUM, AND PRODUCT

(54) 发明名称: 信息指示方法、装置、介质及产品

终端接收携带有第一指示域的DCI, 第一指示域中的部分码点用于指示在基于单个DCI调度的STxMP配置下以及终端在上行数据信道调度为单个面板向单TRP的上行传输下所关联的SRS资源集以及SRI/TPMI域

602

图 6

602 A terminal receives DCI carrying a first indication field, wherein some of code points in the first indication field are used for indicating an SRS resource set and an SRI/TPMI field associated under STxMP configuration scheduled on the basis of a single DCI, and when the terminal is scheduled to perform uplink transmission to a single TRP via a single antenna panel on an uplink data channel

(57) Abstract: The present disclosure relates to the field of communications. Disclosed are an information indication method and apparatus, a medium, and a product. The method comprises: receiving DCI carrying a first indication field, wherein some of code points in the first indication field are used for indicating an SRS resource set and an SRI/TPMI field associated under STxMP configuration scheduled on the basis of a single DCI, and when a terminal is scheduled to perform uplink transmission to a single TRP via a single antenna panel on an uplink data channel. The method is used for supporting an indication of dynamic switching between s-TRP and m-TRP during simultaneous uplink transmission based on a multi-antenna panel terminal; according to new STxMP transmission characteristics, a design is made to enhance a dynamic indication field introduced into R17, so that the indication and dynamic switching of a transmission scheme can be better and flexibly supported.

(57) 摘要: 本公开公开了一种信息指示方法、装置、介质及产品, 属于通信领域。该方法包括: 接收携带有第一指示域的DCI, 第一指示域中的部分码点用于指示在基于单个DCI调度的STxMP配置下以及终端在上行数据信道调度为单个天线面板(panel)向单TRP的上行传输下所关联的SRS资源集以及SRI/TPMI域。该方法用于支持基于多天线面板终端上行同时传输时的s-TRP和m-TRP之间的动态切换指示, 根据新的STxMP传输特性, 对于R17引入的动态指示域做增强设计, 从而更好更灵活地支持传输方案的指示和动态切换。

[见续页]

WO 2024/026645 A1

(84) 指定国(除另有指明, 要求每一种可提供的地区
保护): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA,
RW, SC, SD, SL, ST, SZ, TZ, UG, ZM, ZW), 欧亚 (AM,
AZ, BY, KG, KZ, RU, TJ, TM), 欧洲 (AL, AT, BE, BG,
CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU,
IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO,
RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG)。

本国际公布:

— 包括国际检索报告(条约第21条(3))。