[CLAIMS]

1. A linking system, comprising:

a first linking control device which performs control such that a first building management system that manages building facilities provided in a first building and a first device connected to an internet are linked to realize a specific function,

wherein the first linking control device comprises:

a memory which stores linking procedure information indicating procedures for realizing the linking of the specific function; and

a linking controller which controls (i) an output to the first device in response to an input from the first building management system or (ii) an output to the first building management system in response to an input from the first device so as to realize the specific function based on the linking procedure information stored in the memory,

the linking procedure information includes corresponding command information indicating a command for requesting correspondence linking, and procedure instruction information indicating an instruction subject, a conditional operation, an execution subject, and an execution content, and

the linking procedure information is an information

that causes the linking controller to execute a control so that a device designated as the execution subject executes a process specified as the execution content when a device designated as the instruction subject satisfies the conditional operation.

2. The linking system according to claim 1, wherein the first linking control device is included in a building integrated management system which integrally manages the facilities in a plurality of buildings.

3. The linking system according to claim 2,

wherein the building integrated management system includes a second linking control device in addition to the first linking control device, the second linking control device performing control so as to realize a specific function between a second building management system that manages building facilities provided in a second building and a second device, and

the first linking control device individually performs control to realize the specific function between the first building management system and the first device when the first device is a device provided in the first building.

4. The linking system according to claim 2, wherein the

first device is a building facility or a device provided in a second building.