



(51) International Patent Classification:
F41H 13/00 (2006.01)

(21) International Application Number:
PCT/US2023/028370

(22) International Filing Date:
21 July 2023 (21.07.2023)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
63/393,190 28 July 2022 (28.07.2022) US

(71) Applicant: **AXON ENTERPRISE, INC.** [US/US]; 17800 N 85th Street, Scottsdale, Arizona 85255 (US).

(72) Inventors: **GROFF, John**; 17800 N 85th Street, Scottsdale, Arizona 85255 (US). **SCOTT, Trevor**; 17800 N 85th Street, Scottsdale, Arizona 85255 (US). **ROMNEY, Landon**; 17800 N 85th Street, Scottsdale, Arizona 85255 (US). **DRISCOLL, Samuel R.**; 17800 N 85th Street, Scottsdale, Arizona 85255 (US).

(74) Agent: **POWLEY, Justin**; 17800 N 85th Street, Scottsdale, Arizona 85255 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CV, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IQ, IR, IS, IT, JM, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, MG, MK, MN, MU, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, CV, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SC, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, ME, MK, MT, NL, NO, PL, PT, RO, RS, SE,

(54) Title: ELECTRODE FOR A CONDUCTED ELECTRICAL WEAPON




FIG. 5B

(57) Abstract: An electrode for a conducted electrical weapon may comprise an electrode body and an electrode head coupled to a first end of the electrode body. The electrode head may comprise one or more circumferential grooves. A filament may be stored in the electrode body and may be circumferentially wound into the one or more circumferential grooves to couple the filament to the electrode head. The electrode may comprise an absorber coupled to the electrode head. The absorber may comprise a core to provide rigidity and structure to the absorber. An impact spreader may be positioned forward the absorber. In response to an impact, the impact spreader may provide a force to the absorber to cause the absorber to expand radially outward.

[Continued on next page]

SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments (Rule 48.2(h))*

(88) Date of publication of the international search report:

13 June 2024 (13.06.2024)