housed in the shoe must not be known to any person. That is, high security is required for the casino shoe. In particular, when opening the package, taking out the plurality of playing cards and loading them into the shoe, it is necessary to prevent a player and the dealer from knowing the contents of the playing cards.

[0006]

Moreover, the game must be interrupted while the new playing cards are loaded into the shoe. In a case where this interruption is long, game participants become bored and casino sales decreases. Therefore, it is desirable that the loading of the playing cards into the shoe can be performed smoothly.

[0007]

Embodiments of the present disclosure seek to provide a security electronic shoe for a casino which can load a playing card smoothly while ensuring security.

[0008]

A security electronic shoe for a casino according to an aspect of the present disclosure is a security electronic shoe for a casino configured to house a plurality of playing cards and to read the rank and suit of cards that are drawn one by one for a game, comprising: a housing portion configured to house a stacked plurality of playing cards; an opening portion configured to expose a leading playing card among the plurality of playing cards housed in the housing portion; a draw guide portion configured to guide draw of the leading playing card from the opening portion; a weight configured to push a last playing card of the plurality of playing cards toward the opening portion; a card drawing restricting member configured to restrict the leading playing card to be drawn from the opening portion so that no card is drawn out; and a two-card drawing restricting member configured to restrict two playing cards to be drawn from at a same time so that the cards are correctly drawn one at a time, wherein a bottom portion of the housing portion slopes so as to descend toward the opening portion, the weight is configured to be movable

on the bottom portion of the housing portion toward the opening portion in a state pushing the last playing card toward the opening portion, according to that the last playing card moves toward the opening portion, accompanying that the leading playing card is drawn in sequence, the draw guide portion includes a two-card drawing restricting member configured to restrain the playing card to be drawn to prevent two playing cards from being drawn at a same time, and depending on an effect of the card restriction member, drawing of the leading playing card is restricted, and depending on an effect of the two-card drawing restriction member, drawing of a following playing card is restricted.